

4K HDMI Audio De-Embedder Specification

Input	1 x HDMI
Output	1 x HDMI
	1 x OPTICAL (Toslink)
	1 x COAX (orange RCA)
	1 x L/R (red & white RCA)
Bandwidth	10.2GBps
HDMI	HDMI1.4
HDCP	HDCP1.4, HDCP2.2
HDMI resolutions	Up to 3840x2160@60Hz (4:2:0)
HDMI Audio Format	(L)PCM 2 / 5.1 / 7.1CH, Dolby Digital, DTS 5.1CH, Dolby Digital Plus, Dolby TrueHD, and DTS-HD Master Audio
HDMI Distance	50 feet (15 meters) at 1080p, 33 feet (10 meters)
Micro USB	Firmware Upgrade
Operating Temperature	-10 °C ~ +50 °C / 14 °F ~ 122 °F
Storage Temperature	-20 °C ~ 60 °C / -4 °F ~ 140 °F
Operating Humidity	20~ 90% RH (non-condensing)
Storage Humidity	20 ~90% RH (non-condensing)
Power Supply	DC 5V 1A
Chassis Material	Aluminum
Dimensions	W152 x D74 x H24 (mm) / W5.98 x D2.91 x H0.95 (inch)
Power Consumption	1.8W
Weight	125g / 0.276lb