



## Introduction

The Atlona AT-HDR-H2H-88MA is an 8x8 HDMI matrix switcher for high dynamic range (HDR) formats. It is HDCP 2.2 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI data rates up to 18 Gbps. The HDR-H2H-88MA is ideal for residential applications with the latest as well as emerging 4K/UHD and HDR sources and displays. It is compatible with all video resolutions, audio formats, and color space formats supported in the HDMI 2.0b specification, plus the ability to pass metadata for HDR content. The HDR-H2H-88MA includes EDID and HDCP management features, and can send CEC display control independently to each output. An unbalanced analog audio output is paired with each HDMI input for sending de-embedded HDMI audio to a whole-house audio system. The HDR-H2H-88MA can be controlled via Ethernet, RS-232, and IR.

## Applications

- Residential installations**  
 The HDR-H2H-88MA is designed for AV systems with the latest UHD and HDR sources such as Ultra HD Blu-ray players, plus compatible televisions and projectors.
- TV showrooms**  
 The HDR-H2H-88MA can be used for reliable content distribution to televisions, to properly demonstrate the quality and appeal of 4K and HDR programming.
- Professional AV applications**  
 Atlona 4K HDR products are ideal for full-motion, highly detailed 4K graphics presentations for visualization, 3D renderings, simulations, and more.

## Key Features

### 8x8 HDMI matrix switcher

- Delivers high performance, reliable HDMI signal matrix switching.
- Easy to install and deploy in residential and commercial applications.

### 4K/UHD capability @ 60 Hz with 4:4:4 chroma sampling, plus support for HDR formats

- Compatibility with new and emerging 4K/UHD and HDR-capable sources and displays.
- Fully supports video resolutions, audio formats, and color space formats in the HDMI 2.0b specification.

### HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between devices.

### Independent CEC display control to each output

- Sends display power on/off control to a specific HDMI output. CEC control can be triggered by IP or RS-232 control commands.
- Enables independent control of displays connected to the matrix switcher.

### HDMI audio de-embedding for each input

- Extracts HDMI two-channel PCM audio to an unbalanced analog audio output paired with a corresponding HDMI input.
- Provides an additional integration option for whole-house as well as commercial audio systems.

### TCP/IP, RS-232, and IR control

- Flexible control options for compatibility with third-party control systems.
- Reduces integration time and costs.

## Specifications

Video		
Signal	Input - HDMI Output - HDMI	
UHD/HD/SD	4096x2160@60/50/30/25/24Hz 3840x2160@60/50/30/25/24Hz 2048x1080p 1920x1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1920x1080i@30/29.97/25Hz	720p@60/59.94/50Hz 576p@50Hz 576i@25Hz 480p@60/59.96Hz 480i@30Hz
VESA All resolutions are 60Hz	2560x2048 2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1600x900 1440x900 1400x1050	1366x768 1360x768 1280x1024 1280x800 1280x768 1152x864 1024x768 800x600
Color Space	YUV, RGB	
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0	
Color Depth	8-bit, 10-bit, 12-bit	
HDR	Up to 4K HDR10 @ 60 Hz and 4K Dolby® Vision™ @ 60 Hz <sup>(1)</sup>	

Audio			
HDMI / HDBaseT Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	up to 24-bit		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Distance	Feet	Meters
HDMI IN / OUT @ 4K	15	5
HDMI IN / OUT @ 1080p	30	10

Signal	
Bandwidth	18 Gbps
CEC	Yes
HDCP	2.2

Temperature	Fahrenheit	Celsius
Operating	32 to 122	0 to 50
Storage	-40 to 158	-40 to 70
Humidity (RH)	20% to 90%, non-condensing	

Power	
Consumption	43.3W
Idle Consumption	21.7 W
BTU/h	147.7
Supply	Input: 110 - 240 VAC, 50 / 60 Hz Output: 24V DC, 2.7 A

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.73 x 17.24 x 10	44 x 438 x 254
Unit w/feet/ears	2.18 x 18.93 x 10.23	55.5 x 481 x 260
Power Supply	1.26 x 1.93 x 4.69	32 x 49 x 119
Unit Rack Size	1 RU	

Weight	Pounds	Kilograms
Device	8.81	4

Certification	
Power Supply	CE, FCC, UL, and LVD certificates Level VI compliant
Unit	CE, FCC

Warranty	
Device	To view the product warranty, use the following link: <a href="https://atlona.com/warranty">https://atlona.com/warranty</a>

## Accessories

SKU	Description
AT-LC-H2H-1M	LinkConnect HDMI to HDMI 1 Meter Cable
AT-LC-H2H-2M	LinkConnect HDMI to HDMI 2 Meter Cable
AT-LC-H2H-3M	LinkConnect HDMI to HDMI 3 Meter Cable

## Copyright, Trademark, and Registration

© 2025 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).