HD-100A Compact Full HD HDMI POV Camera



The HD-100A has a Full HD Progressive Scan CMOS sensor that provides vivd and detailed images even under different light conditions. Its advanced digital imaging processor utilizes White Balance, and Noise Reduction, while featuring a motion compensated temporal noise reduction to be able to maintain a quality image with motion blur. The HD-100A is compatible with other industry leading products.



HD-100A Compact Full HD HDMI Camera





Video

Resolution/Rate 1080 60p/59.94p/50p/30p/29.97p/25p/24p

1080 60i/59.94i/50i 720 60p/59.94p/50p

Output HDMI 1.3a

Color Space 4:2:2 (YCbCr) 10bit

Min. Illumination 0.2 Lux (Day), 0.1 Lux (Night), 0.005 Lux (Slow Shutter ON)

White Balance Auto & Manual (9,000°K - 11,000°K)

Lens

Lens C/CS Mount (Default 4mm HD Lens)

Audio

Audio Input 3.5mm Stereo Mic-In & Line in over I/O Cable

Sample Rate 16/24/32 Bits

Physical

Camera Control RS-485 VISCA, OSD Button

Operation Temp 32°F - 104°F

Dimension 39mm x 39mm x 50.50mm / 1.53" x 1.53" x 1.99" (With default 4mm lens)

Weight 140g / 0.30Lbs

Power 6W at 12VDC (+9 - +15VDC)

Package contents



I/O Breakout cable



DC12v Power supply & Socket adaptor



4mm Megapixel Lens (Pre-installed)



Sensor cap



C-Mount lens adaptor



Hex. wrench

