



## Introduction

The Atlona AT-HDVS-CAM is an enterprise-grade PTZ camera designed for use in video conferencing and other applications such as lecture capture and distance education. It features a USB 2.0 interface for video and camera control. The HDVS-CAM seamlessly integrates with the Omega™ Series, HDVS-300 System, and OmniStream™ for a complete, automated conferencing system that includes AV and USB extension. The HDVS-CAM delivers high performance, professional-quality imaging with video resolutions up to 1080p @ 30 Hz, as well as fast and accurate auto-focusing, and a fast yet quiet pan and tilt mechanism. Also available is H.264 or H.265 streaming over IP with support for RTMP and RTSP protocols. This PTZ camera is ideal for a wide range of small to medium-sized meeting spaces, classrooms, and training rooms. The HDVS-CAM is available in black or white.

The HDVS-CAM is part of a family of PTZ cameras that includes the HDVS-CAM-HDBT with HDBaseT output, as well as the HDVS-CAM-HDMI, with HDMI output plus USB 2.0 interface. It includes a handheld IR remote control, plus mounting hardware for convenient on-wall installation. Available as an option is the AT-HDVS-CAM-CMNT for inverted ceiling mounting.

The HDVS-CAM includes a handheld IR remote control, plus mounting hardware for convenient on-wall installation.

## Applications

- **Meeting spaces and conference rooms**  
The HDVS-CAM works together with the USB extension capability of an Omega Series or OmniStream system to enable simple, clean connectivity from the front wall to PCs at the meeting table. The camera is universally compatible with any PC using the standard USB video driver.
- **Classrooms and other instructional spaces**  
The HDVS-CAM is ideal for distance learning and collaboration, as well as recording lectures.

## Key Features

- Designed for video conferencing with AV systems supporting USB interfacing and extension.
- USB 2.0 interface for video and camera control.
- Universal PC compatibility through standard UVC 1.1 (USB Video Class) driver.
- Works with popular soft codec and UC clients such as Microsoft® Teams, Zoom™, BlueJeans™, Slack™, WebEx®, and GoToMeeting®.
- Up to 255 camera presets available, 10 accessible from IR remote.
- Supports VISCA, Pelco-D, and Pelco-P camera control protocols.
- H.264 and H.265 video over IP network streaming available, with support for RTMP and RTSP protocols.
- Fast and accurate auto focus, plus auto white balance and auto exposure modes.
- Fast and quiet pan and tilt mechanism.
- Picture controls available for brightness, color, saturation, contrast, sharpness, and gamma.
- Easy, GUI-based configuration using integrated web server.
- TCP/IP, RS-232, USB, and IR control – convenient handheld IR remote control included.
- Available video resolutions from 176×144 up to 1080p @ 30 Hz.
- High performance imaging, fine detail, and color rendering with 1/2.8" low-noise, HD CMOS sensor.
- Multi-element zoom lens with 10x optical zoom and a 60.9° horizontal field of view.
- Camera can be mounted on a wall, or inverted for ceiling installation with the optional AT-HDVS-CAM-CMNT ceiling mount kit.
- Includes installation guide, wall mounting bracket, IR remote control, 2 meter (6.5 foot) USB Type-A male to male cable, VISCA to RS-232 DB-9 adapter, lens cap, and external universal power supply.
- Available in black or white.

## Specifications

| Video              |                                                                                                |
|--------------------|------------------------------------------------------------------------------------------------|
| Signal             | USB                                                                                            |
| HD                 | 1920x1080p@60/59.97/50/30/29.97/25 Hz<br>1920x1080i@60/59.94/50 Hz<br>1280x720p@60/59.94/50 Hz |
| Color Space        | YUV, RGB                                                                                       |
| Chroma Subsampling | 4:4:4, 4:2:2, 4:2:0                                                                            |

| Streaming            |                                                                      |
|----------------------|----------------------------------------------------------------------|
| Video Compression    | H.264 / H.265                                                        |
| Protocol             | TCP, UDP, RTMP, RTSP                                                 |
| Bitrate              | 46 kbps - 40960 kbps                                                 |
| Compression Profiles | BP, MP, HP                                                           |
| Bitrate Control      | VBR                                                                  |
| Multi-Stream         | Main Stream / Sub Stream (simultaneous stream output) <sup>(1)</sup> |
| Latency              | 175 ms                                                               |

| Camera               |                                                              |
|----------------------|--------------------------------------------------------------|
| Sensor               | 1/2.8" HD CMOS                                               |
| Effective Pixels     | 16:9, 2.07 MP                                                |
| Optical Zoom         | $f = 4.7 \sim 47$ mm                                         |
| View Angle           | 6.43° (telephoto), 60.9° (wide-angle)                        |
| Av                   | $f/1.6 - f/3.0$                                              |
| Digital Zoom         | 10X                                                          |
| Minimum Illumination | 0.5 lm ( $f/1.8$ with AGC On)                                |
| DNR                  | 2D / 3D                                                      |
| White Balance        | Auto / Manual / One Push / 3000 K / 4000 K / 5000 K / 6500 K |
| Focus                | Auto / Manual                                                |
| Aperture             | Auto / Manual                                                |
| Electronic Shutter   | Auto / Manual                                                |
| BLC                  | ON / OFF                                                     |
| WDR                  | Off / Dynamic Level Adjustment                               |

| Camera           |                                                                           |
|------------------|---------------------------------------------------------------------------|
| Video Adjustment | Brightness, Color, Saturation, Contrast, Sharpness, B/W Mode, Gamma Curve |
| SNR              | > 55 dB                                                                   |

| PTZ                |                                                       |
|--------------------|-------------------------------------------------------|
| Pan Rotation       | $\pm 170^\circ$                                       |
| Tilt Rotation      | $-30^\circ \sim +90^\circ$                            |
| Pan Control Speed  | 0.1 - $180^\circ$ / sec                               |
| Tilt Control Speed | 0.1 - $80^\circ$ / sec                                |
| Preset Speed       | Pan: $60^\circ$ / sec, Tilt: $30^\circ$ / sec         |
| Preset Number      | 255 (10 presets using the included IR remote control) |

| Connectors |                     |
|------------|---------------------|
| USB        | 1 x USB, Type A     |
| LAN        | 1 x RJ45, 100Base-T |
| AUDIO IN   | 1 x 3.5 mm, stereo  |
| RS-232     | 2 x 9-pin DIN       |
| 12VDC      | 1 x HEC3800         |

| Temperature             | Fahrenheit                 | Celsius   |
|-------------------------|----------------------------|-----------|
| Operating               | 14 to 122                  | -10 to 50 |
| Storage                 | -14 to 140                 | -10 to 60 |
| Operating Humidity (RH) | 20% to 80%, non-condensing |           |
| Storage Humidity (RH)   | 20% to 95%, non-condensing |           |

| Power       |                                                         |
|-------------|---------------------------------------------------------|
| Consumption | 12 W                                                    |
| BTU/h       | 40.9                                                    |
| Supply      | Input: 110 - 220 V AC, 50/60 Hz<br>Output: 12 V DC, 1 A |

| Dimensions (H x W x D)      | Inches             | Millimeters       |
|-----------------------------|--------------------|-------------------|
| Unit                        | 6.59 x 5.90 x 5.90 | 167.5 x 150 x 150 |
| Power Supply (AT-PS-122-NL) | 1.26 x 1.97 x 3.7  | 32.05 x 50 x 94   |

| Weight | Pounds | Kilograms |
|--------|--------|-----------|
| Device | 3.08   | 1.4       |

| Certification |         |
|---------------|---------|
| Device        | CE, FCC |

| Warranty |                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------|
| Device   | To view the product warranty, use the following link:<br><a href="https://atlona.com/warranty">https://atlona.com/warranty</a> |

## Accessories

| SKU              | Title                             |
|------------------|-----------------------------------|
| AT-HDVS-CAM-CMNT | Ceiling Mount Kit for AT-HDVS-CAM |

## Footnotes

(1) Tested using VLC media player connected to the camera.

## Copyright, Trademark, and Registration

© 2025 Atlona Inc. All rights reserved. “Atlona” and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).