

## Datasheet for ANY-MANAGER-1700/3600

<b>Model number</b>	ANY-MANAGER-1700	ANY-MANAGER-3600
<b>Description</b>	Total 17 slots modular chassis	Total 36 slots modular chassis
<b>Control Slot</b>	1	1
<b>Inputs Slot</b>	1~16	1~35
<b>Outputs Slot</b>	1~16	1~35
<b>Inputs card</b>	1 card 1-port input card , supports 3.5mm audio embedded DVI, VGA, CVBS, HDMI, 3G-SDI, YPbPr, HDBT, Fiber Optic	
<b>Output card</b>	1 card 1-port output card, supports TV Wall function, 3.5mm audio de-embedded function, seamless switching. DVI, VGA, CVBS, HDMI, 3G-SDI, YPbPr, HDBT, Fiber Optic	
<b>Resolution</b>	Supports 1920x1200@60Hz (VESA standard) and 180i~10180p@60Hz (HDTV Standards)	
<b>Protocol</b>	Supports DVI1.0 and HDMI1.3, HDCP and EDID management	
<b>Color Space</b>	Supports RGB4:4:4, YUV4:4:4, YUV4:2:0 and YUV4:2:0	
<b>Transmission Bandwidth</b>	10.2Gbps	
<b>Transmission Distance</b>	15m/45ft(Digital Cable), 20m/60ft(Analog Cable), 100m/330ft(Cat6 ), 300m/900ft(LC, MM Fiber Optic), 2km/6000ft(LC SM Fiber Optic)	
<b>Control Ways</b>	Front Buttons, IR, RS232 and LAN control	
<b>Working</b>	Temperature: -20°C to +70°C, humidity: 10% to 90%	
<b>Storage</b>	Temperature: -20°C to +50°C, humidity: 10% to 80%	
<b>Dimension</b>	440x400x98mm (2U)	440x400x225mm (5U)
<b>Weight</b>	12.5Kg	21Kg
<b>Power</b>	100W	200W
<b>Power supply</b>	100~260V 50/ 10Hz	
<b>Safety guarantee</b>	Supports 7x24 no stopping working ability	
<b>Average obstacle time</b>	10,000 hours	