

4K HDBaseT ROBOTIC
PAN TILT HEAD
PTR-15T
Instruction Manual

www.datavideo.com

Table of Contents

FCC COMPLIANCE STATEMENT	4
WARNINGS AND PRECAUTIONS	4
WARRANTY	5
<i>STANDARD WARRANTY</i>	<i>5</i>
<i>THREE YEAR WARRANTY</i>	<i>5</i>
DISPOSAL	6
1. PRODUCT OVERVIEW	7
1.1 <i>FEATURES</i>	<i>7</i>
1.2 <i>SYSTEM DIAGRAM</i>	<i>7</i>
2. SYSTEM OVERVIEW	8
2.1 <i>BOTTOM PANEL</i>	<i>9</i>
2.2 <i>TOP PANEL</i>	<i>11</i>
2.3 <i>INSTALLING YOUR CAMERA</i>	<i>13</i>
3. CONNECTIONS.....	15
3.1 <i>POWER.....</i>	<i>15</i>
3.2 <i>VIDEO</i>	<i>15</i>
3.3 <i>TALLY.....</i>	<i>15</i>
4. CONTROL FUNCTIONS	16
4.1 <i>RS-422 VISCA COMMUNICATION PROTOCOL</i>	<i>16</i>
4.2 <i>HDBASET</i>	<i>17</i>
4.3 <i>REMOTE OUT</i>	<i>19</i>
<i>Remote Port</i>	<i>19</i>
LANC	20
BX-Lens	22
2-Port Pana	22
<i>RS-232/422 OUT.....</i>	<i>22</i>
RS-232	22
RS-422	23
4.4 <i>TALLY.....</i>	<i>23</i>
4.5 <i>IR REMOTE CONTROL.....</i>	<i>24</i>
<i>Function Descriptions.....</i>	<i>25</i>
<i>OSD Menu</i>	<i>26</i>
Set Camera.....	36
OSD Function	36
Menu Function	37
LANC Zoom Offset Limit	37
LANC Zoom Start Delay.....	37
LANC Zoom Speed Limit	37
Set Motor.....	37
P/T Acceleration	37
P/T Speed	37
PAN Torque	37
Tilt Torque	37
Pan Offset	37
Tilt Offset.....	38
Pan Min Limit.....	38
Pan Max Limit	38

Tilt Min Limit.....	38
Tilt Max Limit	38
Pan L/R Offset.....	38
Tilt U/D Offset.....	38
Memory	38
Preset Position.....	38
Group 1 – 8.....	38
Remote Control.....	38
PAN/TILT Reverse	38
Set RS-422.....	38
Set DVIP	39
Set IR.....	39
Set Remote Out	39
PTZ Info. Output	40
PTZ Coordinate Adjustment.....	40
Append Zoom Position to P/T Info	41
System	41
Tally Light.....	41
Model No.	41
Power OUT Limit.....	41
Display	41
Reset All	41
Update Software.....	41
Reset P/T.....	41
4.6 ZOOM SENSOR MINI-DIN PORT	42
5. FIRMWARE UPDATE	43
5.1 FIRMWARE UPGRADE REQUIREMENTS	43
5.2 UPGRADE PROCEDURE.....	43
6. FREQUENTLY-ASKED QUESTIONS	44
7. DIMENSIONS	46
8. SPECIFICATIONS	47
SERVICE AND SUPPORT	52

Disclaimer of Product & Services

The information offered in this instruction manual is intended as a guide only. At all times, Datavideo Technologies will try to give correct, complete and suitable information. However, Datavideo Technologies cannot exclude that some information in this manual, from time to time, may not be correct or may be incomplete. This manual may contain typing errors, omissions or incorrect information. Datavideo Technologies always recommend that you double check the information in this document for accuracy before making any purchase decision or using the product. Datavideo Technologies is not responsible for any omissions or errors, or for any subsequent loss or damage caused by using the information contained within this manual. Further advice on the content of this manual or on the product can be obtained by contacting your local Datavideo Office or dealer.

FCC Compliance Statement

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Warnings and Precautions

1. Read all of these warnings and save them for later reference.
2. Follow all warnings and instructions marked on this unit.
3. Unplug this unit from the wall outlet before cleaning. Do not use liquid or aerosol cleaners. Use a damp cloth for cleaning.
4. Do not use this unit in or near water.
5. Do not place this unit on an unstable cart, stand, or table. The unit may fall, causing serious damage.
6. Slots and openings on the cabinet top, back, and bottom are provided for ventilation. To ensure safe and reliable operation of this unit, and to protect it from overheating, do not block or cover these openings. Do not place this unit on a bed, sofa, rug, or similar surface, as the ventilation openings on the bottom of the cabinet will be blocked. This unit should never be placed near or over a heat register or radiator. This unit should not be placed in a built-in installation unless proper ventilation is provided.
7. This product should only be operated from the type of power source indicated on the marking label of the AC adapter. If you are not sure of the type of power available, consult your Datavideo dealer or your local power company.
8. Do not allow anything to rest on the power cord. Do not locate this unit where the power cord will be walked on, rolled over, or otherwise stressed.
9. If an extension cord must be used with this unit, make sure that the total of the ampere ratings on the products plugged into the extension cord do not exceed the extension cord rating.
10. Make sure that the total amperes of all the units that are plugged into a single wall outlet do not exceed 15 amperes.
11. Never push objects of any kind into this unit through the cabinet ventilation slots, as they may touch dangerous voltage points or short out parts that could result in risk of fire or electric shock. Never spill liquid of any kind onto or into this unit.
12. Except as specifically explained elsewhere in this manual, do not attempt to service this product yourself. Opening or removing covers that are marked "Do Not Remove" may expose you to dangerous voltage points or other risks, and will void your warranty. Refer all service issues to qualified service personnel.



13. Unplug this product from the wall outlet and refer to qualified service personnel under the following conditions:
- When the power cord is damaged or frayed;
 - When liquid has spilled into the unit;
 - When the product has been exposed to rain or water;
 - When the product does not operate normally under normal operating conditions. Adjust only those controls that are covered by the operating instructions in this manual; improper adjustment of other controls may result in damage to the unit and may often require extensive work by a qualified technician to restore the unit to normal operation;
 - When the product has been dropped or the cabinet has been damaged;
 - When the product exhibits a distinct change in performance, indicating a need for service.

Warranty

Standard Warranty

- Datavideo equipment is guaranteed against any manufacturing defects for one year from the date of purchase.
- The original purchase invoice or other documentary evidence should be supplied at the time of any request for repair under warranty.
- The product warranty period begins on the purchase date. If the purchase date is unknown, the product warranty period begins on the thirtieth day after shipment from a Datavideo office.
- All non-Datavideo manufactured products (product without Datavideo logo) have only one year warranty from the date of purchase.
- Damage caused by accident, misuse, unauthorized repairs, sand, grit or water is not covered under warranty.
- Viruses and malware infections on the computer systems are not covered under warranty.
- Any errors that are caused by unauthorized third-party software installations, which are not required by our computer systems, are not covered under warranty.
- All mail or transportation costs including insurance are at the expense of the owner.
- All other claims of any nature are not covered.
- All accessories including headphones, cables, batteries, metal parts, housing, cable reel and consumable parts are not covered under warranty.
- Warranty only valid in the country or region of purchase.
- Your statutory rights are not affected.


Three Year Warranty

- All Datavideo products purchased after July 1st, 2017 qualify for a free two years extension to the standard warranty, providing the product is registered with Datavideo **within 30** days of purchase.
- Certain parts with limited lifetime expectancy such as LCD panels, DVD drives, Hard Drive, Solid State Drive, SD Card, USB Thumb Drive, Lighting, Non-PCIe Card and third party provided PC components are covered for 1 year.



- The three-year warranty must be registered on Datavideo's official website or with your local Datavideo office or one of its authorized distributors within 30 days of purchase.

Disposal



For EU Customers only - WEEE Marking

This symbol on the product or on its packaging indicates that this product must not be disposed of with your other household waste. Instead, it is your responsibility to dispose of your waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help to conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop off your waste equipment for recycling, please contact your local city office, your household waste disposal service or the shop where you purchased the product.



CE Marking is the symbol as shown on the left of this page. The letters "CE" are the abbreviation of French phrase "Conformité Européene" which literally means "European Conformity". The term initially used was "EC Mark" and it was officially replaced by "CE Marking" in the Directive 93/68/EEC in 1993. "CE Marking" is now used in all EU official documents.

1. Product Overview

Datavideo's brand new PTR-15T is a robotic pan-tilt head that is designed to turn any small size video cameras or block cameras into a PTZ camera.

A sleek design fits seamlessly in your studio. With its weight of 3.7 Kg, it can be placed on the heavy-duty tripod or mounted on the wall and ceiling which bring up a lot of flexibilities for your video production.

The PTR-15T can be controlled by IR Controller, VISCA Protocol Controller, Datavideo RMC-180 MARK II Camera Controller, RMC-300A Universal Remote Control Panel, and is compatible with serial or Ethernet.


1.1 Features

- Strong and sturdy aluminum frame
- Various interfaces: SDI, HDMI, RS-232, RS-422, HDBaseT, Tally and LANC
- Supports 12G-SDI and HDMI 2.0
- Built-in timecode/genlock interface
- IP control output to the mounted camera
- Supports multiple protocols for controlling compatible cameras
- Multiple controller choices: RMC-180 MARK II, RMC-300A and ShowCast 100
- Built-in tally lights
- D-tap connector for DC output
- Selectable DC voltage output (12/24 V) for different camera types
- Support optional Datavideo ZEK-2 Zoom Control Kit for Tilta Nucleus-M motors, actively driving and recording zoom positions of mounted cameras
- Control Sony, Panasonic, Canon, and JVC cameras
- Easy control of Zoom, Focus, IRIS, Shutter, and White Balance using Datavideo's remote controllers



1.2 System Diagram



2. System Overview



2.1 Bottom Panel



Power Switch

Power the device ON/OFF

DC IN 19V



DC IN 19V

Connect the supplied 19V PSU to DC IN socket.



DC OUT 12V

DC OUT socket supplies 12V.

Note: The connection can be secured by screwing the outer fastening ring of the DC plug to the socket.



HDMI OUT

Delivers camera video to external devices such as a video switcher. The OSD menu will overlay on the output video of this port.




3G-SDI OUT

Delivers HD camera video to external devices such as a video switcher.



12G-SDI OUT

Delivers 4K camera video to external devices such as a video switcher.



RS-422 IN

Connect any VISCA controller utilizing RS-422 interface such as Datavideo's RMC-180 Mark II or RMC-300A controller. Use the DIP switch to set the PTR-15T's VISCA ID.

See the section on [RS-422 VISCA Communication Protocol](#) for detailed descriptions and example system setup.



HDBaseT

Connects between PTR-15T and HBT-11 receiver/HS-1600T mobile switcher. See [HDBaseT](#) for details.




Tally IN

Receives tally information from external devices such as a video switcher.



IR Receiver


Operate the PTR-15T using an IR remote control.



Genlock/TC

An I/O port designed for genlock or timecode synchronization.

2.2 Top Panel



REMOTE




REMOTE


Connect through a remote cable to various camera brands in order to control camera's zoom and focus as well as other functions. See the [REMOTE](#) section for cable pinout information, connection instructions as well as a list of compatible cameras.

Note: A remote cable (8pin mini-din to 2.5mm phone jack) accompanying the PTR-15T is designed for connecting to various camera brands.

Warning: The 8pin snap-and-lock mini-din connector of the remote cable will be securely fastened once plugged into the Remote port. To remove, use two fingers to gently hold the part of the plug labelled by two arrows then pull the connector outward.



RS-232/422 OUT



RS-232/422 OUT

Connect to the camera mounted, relaying serial control signals between the camera and controllers via RS-232 or RS-422 interface, which is selectable through the [OSD menu](#).

ZOOM SENSOR



Zoom Sensor mini-DIN port

Connect to Datavideo's ZEK-1/ZEK-2 Zoom Encoder Kit in order to detect and return zoom position of the camera mounted. See the *respective user manuals* for installation instructions and the [Zoom Sensor mini-DIN Port](#) section for more information about using the ZEK-1/ZEK-2 to achieve smooth and responsive PTZ camera control.



DIP Switch

The DIP switch allows users to configure the PTR-15T's VISCA ID. Refer to the table below for the corresponding bit combinations and their associated VISCA IDs.

4	RESERVED					
	VISCA ID					
3	100	1	001	4	111	7
2	010	2	101	5		
1	110	3	011	6		

1 ← → □



D-tap DC OUT (12/24 V)

The **D-tap DC OUT** port supplies DC power to the camera via a D-tap to DC power cable. Use the power switch to select the output voltage. The available output voltages are 12V and 24V. **To protect the camera, the D-tap DC OUT is by default capped at 12V. To enable the 24V output option, open the OSD menu, navigate to the System submenu, and activate the "High Volt-Out" setting under Power Out Limit.**

Note: The **D-tap-to-DC5.5** cable accompanying the PTR-15T is designed for supplying power to Datavideo's block cameras.

LAN



LAN Port

The LAN port is internally connected to the HDBaseT port on the bottom panel. To control a camera mounted on the PTR-15T via HDBaseT, connect the LAN port to the camera, the HDBaseT port to the HBT-18, and the HBT-18's DVIP port to an Ethernet switch or router.

GENLOCK/TC



Genlock/TC

An I/O port designed for genlock or timecode synchronization.



3G SDI IN

HD Video IN from the mounted camera



12G SDI IN

4K Video IN from the mounted camera



HDMI IN

Video IN from the mounted camera



Tally OUT

Delivers tally information to the mounted camera.



F/W Upgrade

Insert a USB disk containing the latest firmware. *See [Firmware Update](#) for detailed instructions.*

2.3 Installing your Camera


Follow the steps outlined below to install the camera:

1. First place the camera on the camera mount base.
2. Align the 1/4" screw hole found at the base of the camera with the 1/4" screw hole in the camera mount base.

Note: If there is only a 3/8" threaded screw hole at the base of the camera, put a 3/8" to 1/4" nut adapter in the hole then tighten with a coin or a flat head screwdriver.

3. Lastly secure the camera with a 1/4" hand screw.





Note: It is recommended to use a flat head screwdriver to tighten the 1/4" D-ring screw as this can more effectively secure the screw.

3. Connections

Before starting to use your robotic pan tilt head, make sure you have connected the power and camera video.

3.1 Power

DC IN 19V

Connect the supplied 19V PSU to DC IN socket.

DC OUT 12V

DC OUT socket supplies 12V to the camera mounted.

Note: The connection can be secured by screwing the outer fastening ring of the DC plug to the socket.

D-tap DC OUT (12/24 V)

The **D-tap DC OUT** port supplies DC power to the camera via a D-tap to DC power cable.

3.2 Video

SDI / HDMI IN

Receives video delivered from the mounted camera via SDI or HDMI interface.

SDI / HDMI OUT

Delivers camera video to external devices such as a video switcher via SDI or HDMI interface.

Note: 3G-SDI interface is designed for delivering HD videos and 12G-SDI interface is designed for delivering 4K videos.

HDBaseT

Using one single Ethernet cable, you will be able to send video of the source device connected to HDMI IN to external devices such as a switcher.

See the section on [HDBaseT](#) for detailed descriptions and example system setup.

3.3 Tally

The **Tally IN** port receives tally signals from external devices such as a switcher.

The **Tally OUT** port delivers tally signals to the camera mounted.


4. Control Functions

Various control methods are described in this section.


4.1 RS-422 VISCA Communication Protocol

Via the RS-422 VISCA communication protocol, the RMC-180 MARK II and RMC-300A Camera Controllers are able to control up to 4 and 8 PTR-15T devices respectively. See the diagrams below for example system setups

RMC-180 MARK II Camera Controller




RMC-300A Camera Controller



To control the camera mounted on PTR-15T using the camera controller, first connect one of the RJ-45 ports provided on the controller rear to PTR-15T's RS-422 IN port via an RJ-45 cable. Then depending on the protocol used, either connect PTR-15T to the camera via the Remote port (LANC/BX-


Lens) through a remote cable or via the RS-232/422 OUT port (RS-232/RS-422) through an RJ-45 cable. For information about the corresponding cable and the connection, see the section on [Remote OUT](#).

See below for information about RJ-45 cabling (RS-422 wiring scheme between the camera controller and PTR-15T) in the RS-422 setup.



After successfully establishing physical RS-422 connection, please note that the PTR-15T's RS-422 settings such as VISCA ID and baud rate can be configured using the OSD menu by following the menu path Main Menu → Remote Control → Set RS422.

Alternatively, you can use the DIP switch on the top panel to set the VISCA ID. Refer to the table below for the corresponding bit combinations and their associated VISCA IDs.




For operations of specific controllers, see the relevant user manual.

4.2 HDBaseT

The HDBaseT port allows you to connect an HDBaseT switcher via any **standard Ethernet cables** from which the PTR-15 device is controlled. Before connecting, follow the menu path Main Menu → Remote Control → Set DVIP → DVIP Baud Rate to set the baud rate.

Note: HDBaseT is fully HDMI-compliant and works with HDMI only.




See the system diagram below for establishing connection between an HDBaseT switcher and multiple PTR-15T devices.



The table below lists the maximum transmission distance that the CAT. 6 Ethernet cable is able to provide at different resolutions.

Resolution	Transmission Distance (Max)
2160p30	70 m
1080p60	100 m


In addition to HDBaseT switchers, as illustrated in the system diagram below, you can also connect multiple PTR-15T devices to an SE-500MU 4K switcher and an RMC-180 MARK II camera controller via HBT-11 HDBaseT receivers.



4.3 Remote OUT

In the OSD menu, there are five connection modes available in the **Remote OUT Mode** option for the user to select in order to connect your PTR-15T device to the camera mounted. Available connection modes are BX Lens, LANC, OK Protocol, 2-Port Pana, RS-232C and RS-422.

If BX Lens or LANC is selected, use the Remote Port to connect. If RS-232C or RS-422 is selected, use the RS-232/422 OUT port to connect. To use the 2-Port Pana mode, you will need the PCB-1 camera control box which is designed to establish connection between the PTR-15T and the Panasonic camera mounted thereon.



Remote Port

The **Remote** port, when connected to the camera mounted, allows you to access certain functions of various camera brands such as **ZOOM** and **FOCUS**. To use this function, you will need to first enable

LANC or BX-Lens mode by accessing the OSD menu option, **Remote Out Mode**, on your PTR-15T device. Follow the menu path below:

5. Remote Control

→6. Set Remote Out


→1. Remote Out mode

- 2-Port Pana
- LanC (JVC)
- LanC (Panasonic)
- LanC (Canon)
- LanC (Sony)
- OK Protocol-2
- OK Protocol-1
- BX-Lens
- RS-232C
- RS-422


LANC

As cameras of different manufacturers offer different PTZ speeds, we have broken down LanC mode into four different options which are LanC (Sony), LanC (Panasonic), LanC (Canon) and LanC (JVC). Each brand’s LanC option is customized to allow you to better control the camera. If you are using camera brands other than Sony, Panasonic, Canon and JVC, we recommend setting Remote Out Mode to LanC (Sony).

If the LANC mode is enabled, connect the Remote port of PTR-15T to the camera’s 2.5 mm earphone jack via a remote cable. The remote cable is an 8pin mini-din to 2.5mm phone jack cable as depicted below. The pinout information is also shown.



Warning: The 8pin snap-and-lock mini-din connector of the remote cable will be securely fastened once plugged into the Remote port. To remove, use two fingers to gently hold the part of the plug labelled by two arrows then pull the connector outward.



Camera models allowing you to access certain camera functions in LANC mode are listed in the table below.

Please note that Datavideo has specifically designed and manufactured the cable for connecting the REMOTE port. The remote cable will be shipped along with the product. The part number of the cable is G07620000138.

The table below lists all camera brands and models that work with the corresponding LanC options as well as the functions that you can access via the PTR-15T.

LanC (Sony)

Model	Brand	Power Consumption	DC Input	Accessible Functions
PXW-Z280V	Sony	24 – 31 W	12V	Zoom, Focus, Iris, OSD Menu, OSD Display, Shutter, White Balance Mode, Gain and ND
Z90	Sony			Zoom and Focus
PXW-Z190V	Sony	22 – 29 W	12V	Zoom, Focus, Iris and White Balance
PXW-Z150	Sony	6.3 – 6.6 W	8.4V	Zoom, Focus and Iris
HNR-NX5R	Sony	7.5 – 7.8 W	8.4V	Zoom, Focus, Iris and White Balance
FS7	Sony			Zoom, Focus, Iris and White Balance
FS5	Sony			Zoom and Focus

LanC (Panasonic)

Model	Brand	Power Consumption	DC Input	Accessible Functions
AG-CX350PX	Panasonic	11.5 – 17 W	12V	Zoom and Focus
AG-UPX360MC	Panasonic	11.5 – 17 W	12V	
BGH-1	Panasonic		12V	Zoom, Focus and Iris

LanC (JVC)

Model	Brand	Power Consumption	DC Input	Accessible Functions
GY-HC550/500	JVC	24 W	12V	Zoom, Focus and Iris
GY-HM660	JVC	12 W	12V	Zoom, Focus, Iris and White Balance

LanC (Canon) / OK Protocol

Model	Brand	Power Consumption	DC Input	Accessible Functions
XF705	Canon	20.8 W	24V	Zoom, Focus, Iris and White Balance
XF605	Canon		24V*	
XF405	Canon	8.4 W	8.4V	Zoom and Focus
XF305	Canon	8.5 – 8.9 W	8.4V	
XA-55	Canon			Zoom, Focus, Iris and White Balance
XA-40/45	Canon			Zoom, Focus and Iris
XLH1	Canon	7.8 W	7.4V	Zoom and Focus
XHG1	Canon	7.1 – 7.3 W	7.4V	

***Use the camera's power supply instead of the power supplied by PTR-15T.**

BX-Lens

If the BX-Lens mode is selected, use Sony's 8 pin to 8 pin remote control cable to establish device connection, which allows you to adjust the zoom function **ONLY**. The supported cameras are Sony's PXW-X200 (X280) and EX3. Datavideo's part number of the 8 pin to 8 pin remote control cable is G07620000133. See the table below for the required DC input and power consumption of the supported cameras.

Model	Brand	Power Consumption	DC Input	Accessible Functions
PXW-X200 (X280)	Sony	18 – 23 W	12V	Zoom
EX3	Sony			Zoom

2-Port Pana

2-Port Pana is a Remote Out mode designed specifically for controlling Panasonic cameras via the PTR-15T. Supported cameras are listed in the table below:


Model	Brand	Power Consumption	DC Input	Accessible Functions
AG-UX180MC	Panasonic	19.7 W	12V	Zoom, Focus and Iris
AG-HPX265	Panasonic			
AG-HPX255	Panasonic			

To use the 2-Port Pana mode, you will need the PCB-1 camera control box which is designed to establish connection between the PTR-15T and the Panasonic camera mounted thereon. After connection is established, you will be allowed to adjust the camera's zoom, focus and iris. See the PCB-1's user manual for installation and operations.


RS-232/422 OUT

If either of the **RS-422** and **RS-232** modes of connection is selected in **Remote Out Mode**, you may mount Datavideo's BC-80 or BC-200 on the PTR-15T and use a custom made RJ-45 cable to establish physical connection. See below for pinout information.

RS-232



RS-422




4.4 Tally

Two tally sockets can be found on your PTR series device. **Tally IN** receives tally information from external devices such as a video switcher. **Tally OUT** delivers tally information to the mounted camera.

Tally Light Definitions

Message	On Air/Live	Standby/Cued	Free/Safe
Light	Red	Green	No Light

A simple test tool is illustrated in the diagram below.














4.5 IR Remote Control

Operate PTR-15T by an IR remote control.



Function Descriptions

No	Function Keys	Descriptions
1		Power Button Press to switch between Standby and Operation modes.
2		Camera Select Keys 1-4 In a multi-camera environment, use the camera select keys (CAM1 – CAM4) to navigate between the four cameras. Follow the menu path, Main/Remote Control/Set IR/IR Group ID , to assign an ID number from 1 to 4 to the cameras intended for operation.
3		Preset Keys 1 – 4 Use the preset keys to save and recall PTZ settings. Saving to the Preset Key: First configure the camera's focus, zoom, pan and tilt settings, then press the STR key followed by one of the preset keys to save to the selected preset. Recalling the Preset: Simply press one of the preset keys to load the settings saved therein.
4		Focus Button Auto focus will be disabled as the Focus button (either F or N) is pressed. Press F to focus on a far object and N to focus on a near object.
5		Zoom Button The zoom function adjusts the size of the image. Press T (telephoto lens) to zoom in on a subject from far away and W (wide-angled lens) to zoom out.
6		PT Joystick Use the joystick to pan and tilt the camera head. Press the up and down arrow keys to tilt; press the left and right arrow keys to pan. While the OSD menu is opened, press the up and down keys to move between options. Press the right and left keys to toggle between values. Press the center button to enter a sub menu or confirm a selection. To exit a sub menu, press the MENU or Back button.

No	Function Keys	Descriptions
7		<p>Reset IP Button Press and hold for about 3 seconds to reset the PTR-15's network settings to DHCP.</p> <p>Note: If there is no DHCP server on your network, the camera will use static IP to connect after the reset. The default IP address is 192.168.100.100.</p>
8		<p>STR Button Use the STR button along with the preset keys to save the PTZ settings. See Preset Keys 1 – 4 for more information.</p>
9		<p>AF Button Press to enable Auto Focus.</p>
10		<p>Back Button Press to return the camera head to its default position. When the OSD menu is opened, press to return to the previous item on the menu.</p>
11		<p>MENU Button Press the "MENU" button to open the OSD menu on the connected monitor. See OSD Menu for descriptions of various menu options.</p>

OSD Menu

The OSD menu allows you to modify various device settings such as pan and tilt and control protocols. Pressing the menu button on your remote control opens the OSD menu shown below.

OSD MENU

1. Set Camera
2. Set Motor
3. Memory
4. Remote Control
5. System
6. Reset P/T
7. Escape

The table below summarizes the main option items and their sub-options.

Main Options						
Set Camera	Set Motor	Memory	Remote Control	System	Reset P/T	Escape
Sub-Options	1. OSD FUNC.	1. P/T Acceleration	1. Preset Position	1. PAN/TILT Reverse	1. Tally Light	1. Reset Pan/Tilt
	2. MENU FUNC.	2. P/T Speed	2.Group-1	2. Set RS-422	2. Model No.	
	3. LANC-Zoom-Offset-Limit	3. PAN Torque	3. Group-2	3. Set DVIP	3. Power-Out-Limit	
	4. LANC-Zoom-Start-Delay	4. Tilt Torque	4. Group-3	4. Set IR	4. Display	
	5. LANC-Zoom-Speed-Limit	5. Pan Offset	5. Group-4	5. Set Remote Out	5. Reset All	
	6. Escape	6. Tilt Offset	6. Group-5	6. PTZ INFO. Output	6. Update Software	
		7. Pan Min Limit	7. Group-6	7. PTZ Coordinate ADJ	7. Escape	
		8. Pan Max Limit	8. Group-7	8. Append Zoom POS. TO P/T Info		
		9. Tilt Min Limit	9. Group-8	9. Escape		
		10. Tilt Max Limit	10. Escape			
		11. Pan L/R Offset				
		12. Tilt U/D Offset				
		13. Escape				

Details of all options in the on-screen menu are listed in the table below.

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
1. Set Camera	1. OSD FUNC.			
	2. MENU FUNC.			
	3. LANC-ZOOM-OFFSET-LIMIT (%)	2		
		3		
		4		
		5		
		6		
		7		
		8		
		9		
	4. LANC-ZOOM-START-DELAY	0 – 60; Step: 1		
	5. LANC-ZOOM-SPEED-LIMIT	1		
		2		
		3		
		4		
		5		
		6		

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
	6. Escape			
2. Set Motor	1. P/T Acceleration	Auto	Use this mode only if the ZEK-1 Zoom Encoder Kit is installed. See Section 4.6 Zoom Sensor mini-DIN Port for more information.	
		Fast	For responsive camera control; push the joystick slightly to pan/tilt the camera but may blur the image.	
		Middle		
		Slow	For smooth camera control; slow motor acceleration maintains stable image quality.	
	2. P/T Speed	Normal		
		Auto Speed	Use this mode only if the ZEK-1 Zoom Encoder Kit is installed. See Section 4.6 Zoom Sensor mini-DIN Port for more information.	
		X2, Sports		
		X4, Sports-2		
	3. PAN torque ADJ	LOW		
		+1~+3		
	4. TILT torque ADJ	LOW		
		+1~+3		
	5. PAN Offset ADJ	+5.4		
		+4.5		
		+3.6		
		+2.7		
		+1.8		
		+0.9		
		0.0		
		-0.9		
		-1.8		
		-2.7		
		-3.6		
		-4.5		
		-5.4		
	6. TILT Offset ADJ	+6.3		
		+5.4		
		+4.5		
		+3.6		
		+2.7		
		+1.8		
		+0.9		
		0.0		
		-0.9		
		-1.8		

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description	
		-2.7			
		-3.6			
		-4.5			
		-5.4			
		-6.3			
	7. PAN Min Limit	-170 – -1; Step: 1			
	8. PAN Max Limit	+1 – +170; Step: 1			
	9. TILT Min Limit	-45 – -1; Step: 1			
	10. TILT Max Limit	+45 – +1; Step: 1			
	11. Pan L/R Offset	0 – 80; Step: 1 (0.056°)			
	12. Tilt U/D Offset	-99 – +99; Step: 1 (0.028°)			
	13. Escape				
	3. Memory	1. Preset Position	1-199 P/T/Z	1. P/T Speed	1 – 18
2. Focus				Auto	
				MF	
3. Iris				Auto	
4. Shutter				06	
5. WB Mode				AWB	
			MWB		
6. Escape					
51. ESCAPE					
2. Group – 1		1-16: ----/OF_SPD-- _W---_NEXT	PRESET NO.	1~199	
			Note: The preset information will appear at the bottom of the OSD menu in the following format: PS-01: P---./T---./Z----		
			ITEM ON/OFF	ON/OFF	
			SPEED LIMIT	1~18	
			WAITING TIME	0~180	
			NEXT POSITION	NEXT ITEM	
				RETURN	
				GROUP – 1	
				GROUP – 2	
				GROUP – 3	
				GROUP – 4	
				GROUP – 5	
				GROUP – 6	
			GROUP – 7		
		GROUP – 8			
ESCAPE					
17. ESCAPE					
3. Group – 2		1-16	PRESET NO.	1~199	
			ITEM ON/OFF	ON/OFF	

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
			SPEED LIMIT	1~18
			WAITING TIME	0~180
			NEXT POSITION	NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
				GROUP – 6
				GROUP – 7
			GROUP – 8	
			ESCAPE	
		17. ESCAPE		
	4. Group – 3	1-16	PRESET NO.	1~199
			ITEM ON/OFF	ON/OFF
			SPEED LIMIT	1~18
			WAITING TIME	0~180
			NEXT POSITION	NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
				GROUP – 6
				GROUP – 7
			GROUP – 8	
			ESCAPE	
		17. ESCAPE		
	5. Group – 4	1-16	PRESET NO.	1~199
			ITEM ON/OFF	ON/OFF
			SPEED LIMIT	1~18
			WAITING TIME	0~180
			NEXT POSITION	NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
				GROUP – 6
				GROUP – 7
			GROUP – 8	
			ESCAPE	
		17. ESCAPE		

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
	6. Group – 5	1-16	PRESET NO.	1~199
			ITEM ON/OFF	ON/OFF
			SPEED LIMIT	1~18
			WAITING TIME	0~180
			NEXT POSITION	NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
				GROUP – 6
			GROUP – 7	
			GROUP – 8	
			ESCAPE	
		17. ESCAPE		
		7. Group – 6	1-16	PRESET NO.
	ITEM ON/OFF			ON/OFF
	SPEED LIMIT			1~18
	WAITING TIME			0~180
	NEXT POSITION			NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
				GROUP – 6
	GROUP – 7			
	GROUP – 8			
	ESCAPE			
	17. ESCAPE			
	8. Group – 7		1-16	PRESET NO.
		ITEM ON/OFF		ON/OFF
		SPEED LIMIT		1~18
		WAITING TIME		0~180
		NEXT POSITION		NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
				GROUP – 6
		GROUP – 7		
		GROUP – 8		

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
			ESCAPE	
		17. ESCAPE		
	9. Group – 8	1-16	PRESET NO.	1~199
			ITEM ON/OFF	ON/OFF
			SPEED LIMIT	1~18
			WAITING TIME	0~180
			NEXT POSITION	NEXT ITEM
				RETURN
				GROUP – 1
				GROUP – 2
				GROUP – 3
				GROUP – 4
				GROUP – 5
GROUP – 6				
GROUP – 7				
GROUP – 8				
ESCAPE				
17. ESCAPE				
10. Escape				
4. Remote Control	1. PAN/TILT Reverse	OFF		
		P		
		T		
		P+T		
	2. Set RS-422	1. CAMERA ID MODE	BY MENU	
			BY SWITCH	
		2. CAMERA ID	1~7	
		3. RS-422 BAUD RATE	9600	
			19200	
			38400	
			115200	
		4. Recall’s Response	Tailer	
			Leader	
	5. ESCAPE			
	3. Set DVIP	1. DVIP BAUD RATE	9600	
			19200	
			38400	
			115200	
		2. DVIP-MEM-No- OFST	0	
			1	
		3. ESCAPE		
	4. Set IR	1. IR GROUP ID	CAM1~4	
		2. ESCAPE		
	5. Set Remote Out	1. Remote Out Mode	2-Port Pana	
			LANC JVC	
			LANC Panasonic	
			LANC Canon	

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
			LANC Sony	
			OK-Protocol-2	
			OK-Protocol-1	
			BX Lens	
			RS-232C	
			RS-422	
		2. Remote Out Baud Rate	9600	
			19200	
			38400	
			115200	
		3. Remote Out ID	1–7	
		4. BX ZOOM OFFSET	3	
			2	
			1	
			0	
			-1	
			-2	
			-3	
		5. ZOOM Encoder Mode	Trace Camera	
			Tilta-Reverse	
			Tilta-CTL	
			ZEK-1 Reverse	
			ZEK-1 Normal	
		6. Tilta Torque	Off	
			5	
			10	
			15	
			20	
			25	
			30	
			35	
			40	
			45	
			50	
			55	
			60	
			65	
			70	
			75	
			80	
			85	
			90	
			95	
			99	
		7. Tilta Zoom Offset	0 – 990 (Step size: 10)	

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
		8. Zoom Filter Mode	0	
			1	
			2	
			3	
		9. ZEK1 Stop Filter	0 – 20; Step: 1	
		10. ZEK1 High Filter	0080	
			0090	
			00A0	
			00B0	
			00C0	
			00D0	
			00E0	
			00F0	
			0100	
			0110	
			0120	
			0130	
			0140	
			0150	
			0160	
			0170	
			0180	
			0190	
			01A0	
			01B0	
			01C0	
			01D0	
			01E0	
			01F0	
			0200	
			0210	
			0220	
			0230	
			0240	
			0250	
			0260	
			0270	
			0280	
			0290	
			02A0	
			02B0	
			02C0	
			02D0	
			02E0	
			02F0	
			0300	

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
			0310	
			0320	
			0330	
			0340	
			0350	
			0360	
			0370	
			0380	
			0390	
			03A0	
			03B0	
			03C0	
			03D0	
			03E0	
			03F0	
			0400	
		11. ZEK1 Low Filter	0 – 10; Step: 1	
		12. ESCAPE		
	6. PTZ INFO. Output	Free-D		
		PTR-15		
		OFF		
	7. PTZ Coordinate ADJ	1. PAN Coordinate Direction	+(Normal)	
			-(Reverse)	
		2. TILT Coordinate Direction	+(Normal)	
			-(Reverse)	
		3. PAN Coordinate Delay	0 – 9 Frame; Step: 1	
		4. TILT Coordinate Delay	0 – 9 Frame; Step: 1	
		5. ZOOM Coordinate Delay	0 – 9 Frame; Step: 1	
		6. ESCAPE		
	8. Append Zoom POS. TO P/T Info	ON/OFF (VISCA)		
	9. ESCAPE			
5. System	1. Tally Light	RED/GREEN		
		GREEN		
		RED		
		OFF		
	2. Model No.	0150/0010		
	3. Power Out Limit	1. Mask HIGH VOLT-OUT	Disable High-Volt	
			Enable High-Volt	
		2. Power OUT Volt. Limit	12 V	
		3. Escape		
	4. Display	1. P/T OSD	1. PAN OSD	ON/OFF

First Level Main Options	Second Level Sub-Options	Third Level Parameters	Fourth Level Parameters	Sub-Option Description
			2. TILT OSD	ON/OFF
			3. CZOOM OSD	ON/OFF
			4. FOCUS OSD	ON/OFF
			5. ESCAPE	
		2. Debug OSD	1. DEBUG IR OSD	ON/OFF
			2. DEBUG CAM. OSD	ON/OFF
			3. DEBUG RS422 OSD	ON/OFF
			4. DEBUG DVIP OSD	ON/OFF
			5. DEBUG M_CTL OSD	ON/OFF
			6. DEBUG MA_BD OSD	ON/OFF
			7. DEBUG VOUT TEST	ON/OFF
			8. DEBUG FreeD OSD	ON/OFF
			9. ESCAPE	
		3. HDMI IN Reminder	ON/OFF	Once enabled, the HDMI input status will be prompted at the top of the screen.
		4. ESCAPE		
	5. Reset All	YES/NO		
	6. Update Software	1. SW VERSION		
		2. MB CPU	V00.76d	
		3. MCTL CPU	V00.28	
		4. PWRB CPU	V00.26a	
		5. UPDATE ALL	YES/NO	
		6. ESCAPE		
	7. Escape			
6. Reset Pan/Tilt	Reset Pan/Tilt	YES/NO		
7. Escape				

Set Camera

In this sub menu, you can toggle the visibility of the on-screen display and OSD menu. If you are connecting the camera via LANC interface, you also configure the zoom settings.

OSD Function

Toggles the visibility of the On-Screen Display (OSD).

Menu Function

Toggles the visibility of the PTR-15's OSD menu.

LANC Zoom Offset Limit

LANC-Zoom-Offset-Limit sets the **zoom range limit**. It determines the maximum zoom range the camera can reach when controlled via the LANC interface. By adjusting this setting, you can restrict or extend the zoom capabilities, preventing over-zooming or unwanted distortion from the lens.

LANC Zoom Start Delay

This setting controls the delay before the zoom function starts when triggered via LANC. The value ranges from **0 to 60 milliseconds**, with a step size of **1 millisecond**.

LANC Zoom Speed Limit

This sets the maximum speed at which the zoom motor operates when controlled via LANC.

Set Motor

Use the **Set Motor** menu for **adjusting motor-related parameters**

P/T Acceleration

Adjusts the acceleration of the pan and tilt motors. Fast mode results in responsive camera control, while slow mode provides smoother starts and stops.

P/T Speed

Sets the speed for pan and tilt movements.

Normal: Standard pan and tilt speed setting.

Auto: Use this mode only if the ZEK-1 Zoom Encoder Kit is installed. See [Section 4.6 Zoom Sensor mini-DIN Port](#) for more information.

X2, Sports: Doubles the pan and tilt speed for faster movements, ideal for fast-paced environments like sports broadcasting where rapid camera adjustments are necessary.

X4, Sports-2: Quadruples the pan and tilt speed, offering the fastest response for extreme sports or other high-speed applications where immediate tracking and camera movements are essential.

PAN Torque

Sets the torque of the pan motor. Higher torque settings provide more force and are useful for heavier camera setups or resisting external forces like wind.

Tilt Torque

Sets the torque of the tilt motor. Higher values improve performance for heavier or off-balance setups.

Pan Offset

Adjusts the home position of the pan axis to correct alignment issues or compensate for mechanical discrepancies.

Tilt Offset

Adjusts the home position of the tilt axis to correct alignment issues or compensate for mechanical discrepancies.

Pan Min Limit

Defines the minimum angle the head can pan to, creating a leftward movement boundary.

Pan Max Limit

Defines the maximum angle the head can pan to, setting a rightward movement boundary.

Tilt Min Limit

Sets the lowest angle the head can tilt downward.

Tilt Max Limit

Sets the highest angle the head can tilt upward.

Pan L/R Offset

The **Pan L/R Offset** fine-tunes the **home position** of the pan axis.

Tilt U/D Offset

The **Tilt U/D Offset** fine-tunes the **home position** of the tilt axis.

Memory

The Memory submenu enables the configuration of multiple presets, which can then be programmed to create an automated tour of predefined PTZ movements.

Preset Position

A preset is a saved configuration of the camera's PTZ position along with pan and tilt speeds, focus mode, iris mode, shutter speed and white balance mode. The PTR-15 offers 199 preset slots.

Set the camera to the desired PTZ position then adjust the related settings as needed.

Group 1 – 8

Use **Group** to link up to 16 selected Presets in a sequence to create a tour. As the group is selected, the camera should automatically transition between these presets at specified intervals. You are allowed to set the speed (Speed Limit) of each movement as well as the dwell time (Waiting Time).

Remote Control

Configure various remote control interfaces.

PAN/TILT Reverse

This option, when enabled, reverses the direction of the normal pan and tilt movements. This is useful when the device is installed upside down, such as on a ceiling mount.

Set RS-422

In this sub-menu, you can configure the device's RS-422 serial communication settings. First, select a method for assigning an ID to the PTR-15: either through the OSD menu or using the DIP switch. You can assign an ID number from **1 to 7** to the device. The available **baud rates** are **9600, 19200, 38400, and 115200**. The **Recall** responses can be set to either **tailer** or **leader**. If tailer is selected, the

response is sent at the end of the communication. If leader is selected, the response is sent at the beginning of the communication.

Set DVIP

DVIP is a Datavideo proprietary communication protocol used for IP-based control systems. It allows the device to be remotely controlled over an IP network using DVIP commands. Select a baud rate, the options are 9600, 19200, 38400 and 115200.

DVIP-MEM-No-Offset toggles between **0** and **1**, controlling the use of memory offsets for DVIP communication. A **memory offset** refers to an adjustment value that is applied to a stored preset.

0: Offset Enabled – The camera will apply memory offsets when recalling or setting presets. This means any pre-stored positions will include the offset values.

1: No Offset – The camera will not use memory offsets when recalling or setting presets.

Set IR

IR Group ID: This setting allows you to assign the IR Group ID (CAM1, CAM2, CAM3, or CAM4) to different cameras via the remote control. By assigning an IR Group ID to a camera, the remote control can be used to select and control the corresponding camera. See the [previous section](#) for details of the IR remote control.

Set Remote Out

In this sub-menu, you will be allowed to configure the Remote Port for connecting the camera mounted.

Remote Out Mode: Select from the following options:

- 2-Port Pana
- LANC JVC
- LANC Panasonic
- LANC Canon
- LANC Sony
- OK-Protocol-2
- OK-Protocol-1
- BX Lens
- RS-232C
- RS-422

Remote Out Baud Rate: This setting allows you to configure the communication speed (baud rate) for the selected **Remote Out Mode**. The supported baud rates are listed as follows:

- 9600
- 19200
- 38400
- 115200

Remote Out ID: This assigns a unique identifier (ID) from 1 to 7 to the PTR-15, allowing easy access to the camera mounted thereon.

BX Zoom Offset: This option adjusts the zoom responsiveness for Sony cameras mounted, particularly the **PXW-X200** and **EX3** models. A positive value increases the responsiveness, making the zoom faster, while a negative value reduces the responsiveness, making the zoom slower.

Zoom Encoder Mode: Select a zoom control mode from the following:

- Trace Camera: Uses the camcorder's internal zoom encoder.
- Tilt-Reverse: Reverses the direction of the Tilt Nucleus-M motor of the ZEK-2 Zoom Encoder.
- Tilt-CTL: The standard mode for the ZEK-2 Zoom Encoder.
- ZEK-1 Reverse: Reverses the direction of the gear of the ZEK-1 Zoom Encoder.
- ZEK-1 Normal: The standard mode for the ZEK-1 Zoom Encoder.

Notes:

The ZEK-1 Zoom Encoder Kit is an electromechanical device designed by Datavideo to add automatic zoom positioning to the camcorder mounted. Compatible camcorder models are Sony Z280, Sony X200, Sony EX-3 and Panasonic AG-HPX255.

The ZEK-2 Zoom Encoder Kit is a mechanical device that utilizes the Tilt Nucleus-M motor to add automatic zoom positioning to the Panasonic Lumix BGH-1 camcorder.

For more information about using ZEK-1 and ZEK-2, refer to the respective user manuals.

Tilt Torque: Adjusts the torque of the ZEK-2's Tilt Nucleus-M motor.

Tilt Zoom Offset: Fine-tunes the zoom position via the ZEK-2's Tilt Nucleus-M motor.

Zoom Filter Mode: Applies a filter to the zoom control to smooth out zoom movements. Select 0 to turn off filtering and 3 for maximum filtering.

ZEK1 Stop Filter: Use the stopband filter to eliminate jerky stops.

ZEK1 High Filter: Use the highpass filter in a more responsive system where rapid zoom reactions are crucial.

ZEK1 Low Filter: Use the lowpass filter to smooth out zoom movements by removing high frequency noise.

PTZ Info. Output

You can output the PTZ Info via the RS-422 or DVIP port. Select Free-D protocol to output via the DVIP port and PTR-15 to output via the RS-422 interface.

PTZ Coordinate Adjustment

In this sub menu, you can select the PAN and Tilt directions and introduce delays to smooth out individual pan, tilt and zoom movements.

PAN Coordinate Direction: Select the minus sign to reverse the direction of the normal pan movement.

TILT Coordinate Direction: Select the minus sign to reverse the direction of the normal tilt movement.

PAN Coordinate Delay: Introduce a delay before panning starts. Select 0 to turn off the delay and 9 for maximum delay.

TILT Coordinate Delay: Introduce a delay before the tilt starts. Select 0 to turn off the delay and 9 for maximum delay.

ZOOM Coordinate Delay: Introduces a delay before the zoom starts. Select 0 to turn off the delay and 9 for maximum delay.

Append Zoom Position to P/T Info

Toggle ON to append the zoom position to the pan/tilt information, and the combined data can be sent to external devices via the RS-422 VISCA interface.

System

The System submenu allows users to configure essential system settings, including enabling high power output for the D-tap DC port, setting the output voltage limit (12V or 24V), and accessing device information like tally light, model number, firmware updates, on-screen display and factory resets.

Tally Light

Select **Red** or **Green** to enable the red or green tally. You can also enable both lights at the same time by selecting the Red/Green option.

Model No.

Select the device model number. If your device is a **PTR-15**, select **0150**; if it is a **PTR-10**, select **0010**.

Power OUT Limit

This option sets the D-tap DC Output. First, use the **Mask HIGH VOLT-OUT** to enable the D-tap DC output port, and set the output voltage to either 12V or 24V using **Power OUT Volt. Limit**.

Display

In the Display section, you can turn on/off several on-screen displays. There are three main options, which are P/T OSD, Debug OSD and HDMI IN Reminder.

In P/T OSD, you can turn on/off on-screen information of pan, tilt, czoom and focus settings.

In Debug OSD, you can enable/disable debug information for IR signal (DEBUG IR OSD), camera settings (DEBUG CAM. OSD), RS-422 interface (DEBUG RS422 OSD), DVIP (DEBUG DVIP OSD), motor control (DEBUG M_CTL OSD), motherboard (DEBUG MA_BD OSD), video output (DEBUG VOUT TEST) and FreeD (DEBUG FreeD OSD).

HDMI IN Reminder, once enabled, will prompt the HDMI input status at the top of the screen.

Reset All

Select to reset all settings on the PTR-15 to their factory defaults.

Update Software

This option allows you to **update the device's firmware**. See [Firmware Update](#) for more details.

Reset P/T

Manually resets the Pan and Tilt functions to their default positions, restoring the system's original alignment.

4.6 Zoom Sensor mini-DIN Port

The zoom sensor mini-DIN port allows you to connect the ZEK-1/ZEK-2 Zoom Encoder Kit, which is an electromechanical device that adds automatic zoom positioning to the camcorder mounted on PTR-15T Robotic Pan Tilt Head. See the **ZEK-1 user manual** for installation instructions.

With the ZEK-1 installed, you can set **P/T Acceleration** and **P/T Speed** to **Auto** (recommended) for smooth PTZ camera control.

The P/T Acceleration defines the rate at which the pan and tilt movement will reach its top speed. When set to **Auto**, the acceleration changes according to the zoom direction. When zooming out, the acceleration increases for responsive PTZ movement; when zooming in, the acceleration decreases for smooth PTZ movement.

The P/T Speed defines how fast or slow the pan and tilt movement will be. The PTR device offers 18 levels of speed of P/T movement. When set to **Auto**, the speed changes according to the zoom direction as well. When zooming out, the speed will be automatically increased to 18 for responsive PTZ movement. When zooming in, the speed will be automatically decreased to a value in the range between 3 and 6 for smooth PTZ movement.

To set P/T Acceleration and P/T Speed, follow the menu paths below:

Setting **P/T Acceleration** to **Auto**

Set Motor

- ➔ P/T Acceleration
- ➔ Auto

Setting **P/T Speed** to **Auto**

Set Motor

- ➔ P/T Speed
- ➔ Auto

If you are using ZEK-2, set the ZOOM Encoder Mode ([OSD Menu](#) ➔ [Remote Control](#) ➔ [Set Remote Out](#) ➔ Zoom Encoder Mode) to Tilta-CTRL or Tilta-Reverse. For details, refer to Zoom Encoder Mode in the [Set Remote Out](#) section.

5. Firmware Update

Datavideo usually releases new firmware containing new features or reported bug fixes from time to time. Customers can either download the firmware as they wish or contact their local dealer or reseller for assistance.

This section outlines the firmware upgrade process which should take ***approximately few minutes to complete***.

The existing settings should persist through the *firmware upgrade process, which should not be interrupted once started* as this could result in a non-responsive unit.

5.1 Firmware Upgrade Requirements

- USB thumb drive
- Latest firmware files

5.2 Upgrade Procedure

- 1) Copy firmware image files (MB and MCTL) into the root directory of a USB hard drive (<16 GB) and insert it into the F/W Upgrade USB port.

- 2) Use the IR remote control to open the OSD menu.

Note: If you are using more than one camera in your environment, first select the camera by pressing the corresponding CAM button; the default is CAM1.



- 3) Main Menu

=> 5: SYSYEM

=> 6: UPDATE SOFTWARE

=> UPDATE ALL

=>YES

=> ENTER

- 4) Wait for another five minutes until the following lines appear on the screen


- Updated Mot-BD=>OK.
- Updated MCPU =>OK

The OSD menu screen will flash "Write OK/Power ON Again" alternately; the update process should take approximately 5-7 minutes to complete.

- 5) Turn off the device by unplugging the power cord and plug the power cord back into the socket to turn on the device again.
- 6) FW Update is complete.

6. Frequently-Asked Questions





This section describes problems that you may encounter while using PTR-15T. If you have any questions, please refer to related sections and follow all suggested solutions. If problem still exists, please contact your distributor or the service center.

No.	Problems	Solutions
1.	The device stops responding unexpectedly.	When the PTR-15T is overloaded, the device power will be automatically disconnected. To resume power, first turn off the device, unplug the power cable for more than 15 seconds, then reconnect the power and turn on the device.
2	DC Out does not supply power.	Once the short circuit protection is activated to cut the power, you will need to reboot the device to resume supplying power to the camera.
3	How to prevent activation of short circuit protection after we start supplying power to the device.	We recommend establishing all cable connections to the camera first before switching ON the PTR-15T.
4	The PTR-15T fails to respond to commands issued by the remote control and RMC-180 MARK II.	This issue is caused by incomplete boot. To solve this issue, shut down PTR-15T and wait for 5 seconds before turning on the power again.
5	Only a 3/8" threaded screw hole is found at the base of the camera so cannot secure the camera with the 1/4" hand screw.	Put a 3/8" to 1/4" nut adapter in the 3/8" threaded screw hole and tighten then secure the camera with a 1/4" hand screw.
6	How to achieve smooth PTZ camera control?	In the OSD menu, set P/T Acceleration to Slow for smooth PTZ camera control. Follow the menu path below: 2. Set Motor → P/T Acceleration → Slow
7	How to achieve responsive PTZ camera control?	In the OSD menu, set P/T Acceleration to Fast for responsive PTZ camera control. Follow the menu path below: 2. Set Motor → P/T Acceleration → Fast
8	Can HBT-11 power up the PTR-15T?	No, HBT-11 cannot power up the PTR device. Please use HBT-12 and connect using a solid Ethernet cable only. 

No.	Problems	Solutions
9	Is ZEK-1 required for controlling the Sony Z280 camcorder via LANC?	No, ZEK-1 is not required. You can gain full PTZ control of the Sony Z280 camcorder via LANC alone. However, it is recommended to connect ZEK-1 to enhance the PTZ control by setting the PTR device's P/T Acceleration and P/T Speed to AUTO. See Section 4.6 Zoom Sensor mini-DIN Port for more information.

7. Dimensions

PTR-15T



All measurements in millimeters (mm)

8. Specifications

Product Name	Robotic Pan Tilt Head
Model Number	PTR-15T
Video I/O Interface	HDMI 2.0 x 1 12G-SDI x 1 3G-SDI x 1 RJ45 x 1 (HDBaseT)
Video Output Format	2160p 60/59.94/50 2160p 30/29.97/25 1080p 60/59.94/50 1080p 30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50
Supported Controller	RMC-180 MARK II HS-1600T HS-1600T MARK II RMC-300A ShowCast 100 VISCA Protocol Controller IP Control IR Remote
Genlock	Yes
Timecode	Yes
Pan/Tilt Range	PAN: 340° MAX TILT: +45° to -45° MAX
Pan/Tilt Speed	PAN: 0.12 – 15° / Sec TILT: 0.06 – 10° / Sec
Presets	199 PAN/TILT positions
Control Distance	RS-422: 1200 m DVIP: 100 m
Control Protocol	Sony VISCA DVIP
Control Interface	RS-422 / HDBaseT
Maximum Load	4.0 Kg Max.
Control Output	RS-232 RS-422 IP Control BX-Lens Lanc
Power Requirement	DC 14V – 20V, 90W
Power Supply (Output)	DC 24/12V, 36W Max
Operating Temp.	0 – 40°C
Operating Humidity	10 – 80%
Storage Temp.	-10 – 60°C
Storage Humidity	5 – 80%

Weight	3.7 Kg
Dimensions (LxWxH)	241 x 191 x 300 mm
Optional Accessories	ZEK-1 ZEK-2 PCB-1 WM-10 WM-11 CM-10

Notes

Notes

Notes

Service & Support

It is our goal to make owning and using Datavideo products a satisfying experience. Our support staff is available to assist you to set up and operate your system. Contact your local office for specific support requests. Plus, please visit www.datavideo.com to access our FAQ section.

Please visit our website for latest manual update.

www.datavideo.com/product/PTR-15T



@DatavideoUSA @DatavideoIndia2016
@DatavideoEMEA @DatavideoJapan
@DatavideoTaiwan @DatavideoLatam
@DatavideoAsia @DatavideoBrasil



@Datavideo
@Datavideo_EMEA
@Datavideo_Taiwan



@DatavideoUSA
@DVTWDCN



@DatavideoUSA
@DatavideoEurope