



# kramer

## KT-2015

### 15-Inch Wall & Table Mount PoE Touch Panel

---



KT-2015 is a new powerful, 15-inch, IPS, multi-touch, touch panel with 1920x1080 resolution. Elegantly designed for decorative room integration, this portable touch panel can be deployed either on a tabletop or wall. KT-2015, with the latest Android 11, supports wired PoE (Power over Ethernet) and advanced Wi-Fi connectivity options. The touch panel has a built-in speaker and camera and comes either with a tabletop or a wall mount. The touch panel is easy to assemble, using elegant wiring, secured mounting, reliable operation and flexible deployment. KT-2015 is a touch panel that is ideal for any 24/7 Kramer-supported commercial AV or control application and features a user-friendly, fully customizable graphical user interface configured by Kramer software

## FEATURES

---

**Elegant Design** - Smooth integration with room furniture design, either on table or wall, with flexible panel cabling and locking design options

**Superior User Experience** - IPS 1920x1080 hi-resolution screen with  $\pm 80^\circ$  horizontal and vertical wide viewing angles, ambient light sensor, proximity sensor, with advanced multi-touch points and 2-finger gesture capabilities

**Powerful Processing** - i.MX8M Plus Quad Core A53, 4GB RAM, 32GB ROM processing performance, smoothly running complicated media and graphics-rich applications, such as H.265 video, audio streams encoding and decoding, and seamless hi-resolution 5Mp FF camera operation

**Flexible Services** - Latest Android 11 operating system

**Easy Installation** - Powering and connectivity via a single Ethernet cable

**Flexible Mounting** - Including table and wall mounts

**Optional Connectivity** - Simple wireless Bluetooth 5 as well as connection to USB peripheral devices for either table or wall-mount installations, using the included USB cable

**Reliable Networking** - Seamless switching between wired and wireless 802.11ac connectivity

**Versatile Powering Options** - PoE and power adapter (sold separately)

**Auto Sensing** - Optimized performance and operation according to automatically detected LAN speed

**Firmware Update** - Define automatic updates on a predefined time of the day or update manually using USB port

**Secured Operation** - Highly secured operation of applications using password protection, hidden control buttons and more. Red LED alert when camera is active

**Secured Deployment** - Flexible locking options to prevent unwanted panel mount removal, elegantly designed to remain out of site



# kramer

## TECHNICAL SPECIFICATIONS

---

Ports	1 Ethernet: On an RJ-45 connector with PoE 802.3at 1 USB: On a USB type C (ADB) connector 1 USB: On a USB Type A connector
General	CPU Performance: ARM Quad-core Cortex-A53 up to 1.8GHz (64 bit) System Memory: 4GB LPDDR4 Internal Storage Memory: 32GB eMMC Touch Panel Type: Capacitive multi-touch Wireless Communication: Wi-Fi 6, 802.11 a/b/g/n/ax/ax+BT 5.0 Ethernet: 10/100/1000 Mbps LAN Display Screen: Multi-touch (PCAP) Display Size 15" (16:9 diagonal), 1920 RGB (H) x 1080(V) pixels VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA mount Contrast Ratio: 350cd/m2 brightness, 1000:1 Back-light: LED Side-light type
Audio	Speaker Unit: built-in, 2x 1W Microphone: 2, Built-in Audio Codecs: MPEG/OGG/AAC
Video	Camera: 5Mp FF Video Format: H.264 / H.265, VC-1, MPEG-4, VP9/VP8 Image Codecs: JPEG/BMP/GIF/PNG
Power	PoE: Power over Ethernet 802.3af(/at) Source: 12V/2A DC adapter (optional)
User Interface	Controls: Volume, menu, and power buttons Indicators: LED sidebars to indicate room status (requires 3rd party integration)
Accessories	Included: Table mount for KT-2015 or on-wall mounting bracket & panel mounting bracket for KT-2015WM, installation screws
Environmental Conditions	Operating Temperature & Humidity: 0° to +40°C (32° to 104°F), 5% to 85% Storage Temperature & Humidity: -20° to +60°C (-4° to 140°F), 5% to 90%
Regulatory Compliance (Standards Compliance)	Safety: CE, FCC, UL, UKCA Environmental: RoHs, WEEE
PHYSICAL	Product Dimensions: 130x178x13 W,D,H

Package Dimensions: 60cm x 49.2cm x 35.5cm W, D, H

Product Weight: 1.78kg approx

KT-2015 Package Weight: 2.83kg approx

Product Dimensions 37.34cm x 24.30cm x 2.62cm (14.70" x 9.57" x 1.03" ) W, D, H

Product Weight 1.8kg (3.9lbs) approx

Shipping Dimensions 60.00cm x 49.20cm x 35.60cm (23.62" x 19.37" x 14.02" ) W, D, H

Shipping Weight 2.7kg (5.9lbs) approx



# kramer

## CONFIGURATIONS

---

KT-2015	15-Inch Table Mount PoE Touch Panel
KT-2015WM	15-Inch Wall Mount PoE Touch Panel

---