

T-IN6-REC1

Baseline, In-Table elegant tabletop connectivity for 6 modules



Tabletop connectivity that's easy and reliable to install, maintain and use, with versatile, robust, able-mount solutions designed for today's meeting room furniture. TBUS components are all installed and maintained from above the table, saving time, effort and hassle. With its mix and match modules, simple slide and lock mechanism and advanced technology, TBUS is extremely flexible, simple to fix and upgrade. With its small, slim design that integrates into table surfaces, Kramer's TBUS keeps workspaces neat and tidy, without interrupting the table's look and feel

FEATURES

Cutout Dimensions - 331 x 58mm (13.03" x 2.28")

Easy installation and maintenance - Install all units and modules quickly and easily from above. Slide modules into position - no screws involved!

Proven reliability - Products comply with global industry standards, including CE, FCC, UL, CB, BIS, and many others

Designed for sustainability - Packaging uses minimal materials.

Optimized supply chain to minimize carbon footprint from production to delivery.

Recyclable materials follows ROHS / REACH standards

Minimalistic look and feel - Meeting modern aesthetics

Smooth and minimal design blends with the tabletop.

All modules are perfectly positioned without gaps.

Outer frame is sleek and small, with narrow edges, and no visible screws.

The bezel and lid are available in a choice of three prestige colors to suit any table surface and room decor



TECHNICAL SPECIFICATIONS

COLOR: Black - RAL 9011

White - RAL 9002 Aluminum Natural

OPERATING

TEMPERATURE

0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE -40° to +70°C (-40° to 158°F)

HUMIDITY 10% to 90%, RHL non-condensing

STORAGE HUMIDITY 5 to 95% RHL, non-condensing

RANGE

DIMENSIONS: Table cutout dimensions: 331 x 58mm (13.03" x 2.28")

Outer dimensions (L, W, H) - 342 x 66 x 83mm (13.46" x 2.6" x 3.26")

WEIGHT T-IN6-REC1: 0.9kg (2lbs) approx.

Accessories (Frame, Locking device): 0.2kg (0.44lbs)

BALANCED LINE

LEVEL INPUT

ACCESSORIES Frame (Black), Locking device (Black)



CONFIGURATIO	NIC

Fable In-Surface, Baseline, Black Rectangle, 6 modules. Includes – Black frame + Black locking device Fable In-Surface, Baseline, White Frame Rectangle, 6 modules. Includes –White
ocking device
Table In-Surface, Baseline, Aluminum Frame Rectangle, 6 modules. Includes -White locking device
Black Locking device. 3/PP, when sold separately
White Locking device. 3/PP, when sold separately
Table In-Surface, Baseline, Black Rectangle, 6 modules. Includes – Black frame + Black locking device
Γable In-Surface, Baseline, White Frame Rectangle, 6 modules. Includes – White ocking device
Γable In-Surface, Baseline, Aluminum Frame Rectangle, 6 modules. Includes – White locking device
Black Locking device. 3/PP, when sold separately
White Locking device. 3/PP, when sold separately
T (