




# USER MANUAL

**MODEL:**

**WP-SW2-EN7**  
**4K AVoIP Encoder**



# Contents

|   |           |
|---|-----------|
| <b>Introduction</b>                         | <b>3</b>  |
| Getting Started                             | 3         |
| Overview                                    | 4         |
| Typical Applications                        | 5         |
| <b>Defining WP-SW2-EN7</b>                  | <b>6</b>  |
| <b>Mounting WP-SW2-EN7</b>                  | <b>8</b>  |
| <b>Connecting WP-SW2-EN7</b>                | <b>9</b>  |
| Connecting to WP-SW2-EN7 via RS-232         | 10        |
| <b>Operating and Controlling WP-SW2-EN7</b> | <b>11</b> |
| Configuring the Network Switch              | 11        |
| Configuring the WP-SW2-EN7                  | 11        |
| Operating via Ethernet                      | 12        |
| Connecting Ethernet Port Directly to a PC   | 12        |
| <b>Using WP-SW2-EN7 Embedded Web Pages</b>  | <b>15</b> |
| Opening the WP-SW2-EN7 Web Pages            | 15        |
| Setting AV Routing Parameters               | 17        |
| Defining Switching Mode                     | 18        |
| Defining Signal Loss Timeouts               | 19        |
| Activating HDCP Protection                  | 20        |
| Defining Audio Settings                     | 21        |
| Managing EDID                               | 22        |
| Defining General Settings                   | 23        |
| Defining Network Settings                   | 26        |
| Defining an NTP Time and Date Server        | 29        |
| Setting WP-SW2-EN7 Security                 | 30        |
| Controlling User Access                     | 32        |
| Defining WP-SW2-EN7 Gateway Settings        | 35        |
| Viewing WP-SW2-EN7 Status                   | 37        |
| Viewing WP-SW2-EN7 Connections Status       | 38        |
| Viewing the WP-SW2-EN7 Logs                 | 39        |
| Viewing the About Page                      | 40        |
| <b>Upgrading Firmware</b>                   | <b>41</b> |
| <b>Technical Specifications</b>             | <b>42</b> |
| Default Communication Parameters            | 43        |
| Default EDID                                | 43        |
| Default Parameters                          | 46        |
| <b>Protocol 3000</b>                        | <b>47</b> |
| Understanding Protocol 3000                 | 47        |
| Protocol 3000 Commands                      | 48        |
| Result and Error Codes                      | 58        |

# Introduction

Welcome to Kramer Electronics! Since 1981, Kramer Electronics has been providing a world of unique, creative, and affordable solutions to the vast range of problems that confront the video, audio, presentation, and broadcasting professional on a daily basis. In recent years, we have redesigned and upgraded most of our line, making the best even better!

## Getting Started

We recommend that you:

- Unpack the equipment carefully and save the original box and packaging materials for possible future shipment.
- Review the contents of this user manual.



Go to [www.kramerav.com/downloads/WP-SW2-EN7](http://www.kramerav.com/downloads/WP-SW2-EN7) to check for up-to-date user manuals, application programs, and to check if firmware upgrades are available (where appropriate).

## Achieving Best Performance

- Use only good quality connection cables (we recommend Kramer high-performance, high-resolution cables) to avoid interference, deterioration in signal quality due to poor matching, and elevated noise levels (often associated with low quality cables).
- Do not secure the cables in tight bundles or roll the slack into tight coils.
- Avoid interference from neighboring electrical appliances that may adversely influence signal quality.
- Position your Kramer WP-SW2-EN7 away from moisture, excessive sunlight and dust.

## Safety Instructions



### Caution:

- This equipment is to be used only inside a building. It may only be connected to other equipment that is installed inside a building.
- For products with relay terminals and GPIO ports, please refer to the permitted rating for an external connection, located next to the terminal or in the User Manual.
- There are no operator serviceable parts inside the unit.



### Warning:

- Use only the power cord that is supplied with the unit.
- To ensure continuous risk protection, replace fuses only according to the rating specified on the product label which is located on the bottom of the unit.

## Recycling Kramer Products

The Waste Electrical and Electronic Equipment (WEEE) Directive 2002/96/EC aims to reduce the amount of WEEE sent for disposal to landfill or incineration by requiring it to be collected and recycled. To comply with the WEEE Directive, Kramer Electronics has made arrangements with the European Advanced Recycling Network (EARN) and will cover any costs of treatment, recycling and recovery of waste Kramer Electronics branded equipment on arrival at the EARN facility. For details of Kramer's recycling arrangements in your particular country go to our recycling pages at [www.kramerav.com/quality/environment](http://www.kramerav.com/quality/environment).

---

## Overview

Congratulations on purchasing your Kramer **WP-SW2-EN7 4K AVoIP Encoder**.

**WP-SW2-EN7** is an auto switcher and advanced encoder for streaming 4K@60Hz (4:2:0) a selected video signal, RS-232, or CEC signals via Ethernet over copper cable in unicast (one-to-one) or multicast (one-to-many) configurations.

**WP-SW2-EN7** encodes and streams the video signal from one of two selectable inputs, and transmits USB, RS-232, or CEC signals over an IP network. The Kramer **WP-DEC7** decodes the video signal and receives USB, RS-232, or CEC signals.

**WP-SW2-EN7** provides exceptional quality, advanced and user-friendly operation, and flexible control.

## Exceptional Quality

- Instantaneous Switching Time – 1 second switching time between video inputs.
- Video Streaming Transmitter/receiver - Streams up to 4K@60Hz (4:2:0) resolution signals over a 1G network interface.
- HDR Support – HDR10 up to 4K@30Hz 4:2:2 12bits.
- Supports HDCP 2.2.
- Streaming Support – Provides unicast and multicast streaming.
- Flexible Analog Audio Embedding – Embed analog audio into the streaming audio signal and HDMI output, using the unbalanced 3.5mm stereo connector.

## Advanced and User-friendly Operation

- Convenient and Comprehensive Control – Control the unit using intuitive embedded web pages, Protocol 3000 API commands via Ethernet, or the front panel channel display and recessed navigation buttons (on the US model access to the recessed buttons requires removal of the frame).
- PoE Support – Device power is supplied by a PoE (Power over Ethernet) connection from a PoE LAN switch.
- Control Gateway – Users can control/communicate with connected devices using P3K commands, a TCP connection with RS-232 or CECs.
- Separate Service LAN Port – A second LAN port is available for physical separation

between AV and command streams to improve security and reliability.

## Flexible Connectivity

- Selectable Inputs – 1 HDMI and 1 USB-C input.
- Analog/embedded audio input.
- Plug-and-play with Netgear M4250 AVoIP switches, Kramer Control, KDS-USB2, etc.

---

## Typical Applications

**WP-SW2-EN7** is ideal for the following typical applications:

- Real-time essential installations such as command and control rooms.
- Large scale AV content sharing installations using existing wires and infrastructure in corporate offices and government applications.
- AV distribution systems with one or more sources and multiple displays in schools, universities, and public venues.


## Controlling your **WP-SW2-EN7**

Control your **WP-SW2-EN7** via:

- The Ethernet using built-in user-friendly web pages.
- Protocol commands.

# Defining WP-SW2-EN7

EU/UK



US






Figure 1: WP-SW2-EN7 4K AVoIP Encoder

| # | Feature                               | Function   |   |
|---|---------------------------------------|--|---|
| ① | HDMI IN Connector                     | Connect to an HDMI source.   |   |
| ② | USB-C IN Port                         | Connect to a USB-C source.<br>When powered by a Kramer 20V power supply (optional), charges sources (that support USB Power Delivery 2.0) up to 60W.   |   |
| ③ | HDMI LED                              | Lights Green   | HDMI input is selected, HDMI is connected, and signal is received.  |
|   |                                       | Flashes Green  | HDMI input is selected, HDMI is connected, and no signal is received.   |
|   |                                       | Off  | The HDMI is not selected or not connected.  |
| ④ | USB LED                               | Lights Green   | USB-C input is selected, USB-C is connected, and signal is received.  |
|   |                                       | Flashes Green  | USB-C input is selected, USB-C is connected, no signal is received.   |
|   |                                       | Off  | USB-C is not selected or not connected.   |
| ⑤ | ON LED                                | Flashes Red  | On fallback address acquiring, device 'ON' LED flashes continuously in slow 0.5/10sec cadence.                              |
|   |                                       | Lights Green   | When power is on.   |
|   |                                       | Flashes Green Fast   | Firmware is downloaded in the background.   |
|   |                                       | Flashes Green Very Fast (for 60sec)  | A device identification command is sent (Flag me).  |
|   |                                       | Lights Orange  | The default IP address 192.168.1.39 is in use, device is using fall back IP addresses in range 192.168.0.0 to 192.168.0.16. |
| ⑥ | CH+ / CH-                             | Click the recessed CH buttons to configure the channel ID. The selected channel ID is shown in the display panel (8). On the US model, access to these buttons requires removal of the frame.                    |   |
| ⑦ | RESET                                 | Press and hold for 10 seconds to reset the device to its factory default values. All LEDs flash. On the US model, access to this button requires removal of the frame.   |   |
| ⑧ | Display Panel                         | Shows the number of the channel used by WP-SW2-EN7 for streaming.  |   |
| ⑨ | AUDIO IN 3.5mm Mini Jack              | Connect to an audio source.  |   |
| ⑩ | LAN MEDIA 1G(PoE) RJ-45 Port          | Unicast: connect for streaming either directly to a decoder or via LAN.<br>Multicast: connect to multiple decoders or connect to one decoder to which multiple decoders are daisy-chained via SERVICE (1G) port. |   |
| ⑪ | 20V/6A DC Connector                   | Connect to the power adapter (purchased separately).   |   |
| ⑫ | LAN SERVICE 1G RJ-45 Port             | Used optionally for physical separation between AV and command streams to separate LAN for security and reliability purposes.  |   |
| ⑬ | Ring Tongue Terminal Grounding Screw  | Connect to grounding wire (optional).  |   |
| ⑭ | RS-232 3-pin Terminal Block Connector | Connect to an RS-232 device to use as a Gateway and bi-directional signal extension (even when no AV signal is extended).  |   |

# Mounting WP-SW2-EN7

This section provides instructions for mounting **WP-SW2-EN7**. Before installing, verify that the environment is within the recommended range:



- Operation temperature – 0° to 40°C (32 to 104°F).
- Storage temperature – -40° to +70°C (-40 to +158°F).
- Humidity – 10% to 90%, RHL non-condensing.



**Caution:**

- Mount **WP-SW2-EN7** before connecting any cables or power.




**Warning:**


- Ensure that the environment (e.g., maximum ambient temperature & air flow) is compatible for the device.
- Avoid uneven mechanical loading.
- Appropriate consideration of equipment nameplate ratings should be used for avoiding overloading of the circuits.
- Reliable earthing of rack-mounted equipment should be maintained.
- Maximum mounting height for the device is 2 meters.

Insert the device into the in-wall box (first connect the RS-232 and LAN/POE RJ-45 Connector cables and/or power) and connect the parts as shown in the illustration:

EU/UK Version



US-D Version



DECORA® design frames are included in US-D models.

We recommend that you use standard 2 gang in-wall junction boxes (or their equivalent):

**US-D:** 2 gang US electrical junction boxes.

**EU:** 2 gang in-wall junction box, with a cut-hole diameter of 2x68mm and depth that can fit in both the device and the connected cables (DIN 49073).

**UK:** 2 gang in-wall junction box (BS 4662), 135x75mm (W, H) and depth that can fit in both the device and the connected cables.

**EU/UK:** 2 gang in-wall junction box (use the recommended Kramer in-wall box available at [www.kramerav.com/product/WP-SW2-EN7](http://www.kramerav.com/product/WP-SW2-EN7)).

# Connecting WP-SW2-EN7



By-default, this device uses PoE (Power over Ethernet) for powering the device. Optionally, you can separately purchase a power adapter to connect to the product and plug into the mains electricity.

Always switch off the power to a device before connecting it to your **WP-SW2-EN7**. After connecting your devices, connect their power and then switch on the power to each device.

In this example, **WP-SW2-EN7** is connected to **WP-DEC7**, but it can be connected to any compatible decoder.




Figure 2: Connecting the WP-SW2-EN7 and WP-DEC7

## To connect WP-SW2-EN7 as illustrated in the example in [Figure 2](#):

1. Either connect an HDMI source (for example, a server or a media player) to the HDMI IN connector ① on the **WP-SW2-EN7**, or connect a video source (for example, a laptop) to the USB IN connector ② on the **WP-SW2-EN7**.
2. Connect a stereo audio source (for example, the server audio connector) to the AUDIO IN connector ⑨ on the **WP-SW2-EN7**.
3. Connect the LAN MEDIA 1G(PoE) RJ-45 port ⑩ on the **WP-SW2-EN7** to a LAN switch with PoE and connect the LAN MEDIA 1G(PoE) RJ-45 port on the Kramer **WP-DEC7** decoder to the same LAN switch.

4. Connect the HDMI OUT connector on the **WP-DEC7** to an HDMI acceptor (for example, a display).
  5. On **WP-DEC7**, connect a mouse and a keyboard to the two USB type A ports.
  6. Connect RS-232 3-pin terminal block connectors:
    - On the **WP-SW2-EN7**, connect the RS-232 port <sup>(14)</sup> to a laptop/controller.
    - On the **WP-DEC7**, connect RS-232 to the display.
- i** RS-232 bidirectional signals can be sent between the display and the laptop connected to the HDMI OUT connector on the **WP-DEC7**.

## Connecting to **WP-SW2-EN7** via RS-232


You can connect to **WP-SW2-EN7** via an RS-232 connection <sup>(14)</sup> using, for example, a PC.

**WP-SW2-EN7** features an RS-232 3-pin terminal block connector allowing the RS-232 to control **WP-SW2-EN7**.

Connect the RS-232 terminal block on the rear panel of **WP-SW2-EN7** to a PC/controller, as follows:

From the RS-232 9-pin D-sub serial port, connect:

- Pin 2 to the TX pin on the **WP-SW2-EN7** RS-232 terminal block
- Pin 3 to the RX pin on the **WP-SW2-EN7** RS-232 terminal block
- Pin 5 to the G pin on the **WP-SW2-EN7** RS-232 terminal block



# Operating and Controlling WP-SW2-EN7

This section describes the following actions:

- [Configuring the Network Switch](#) on page [11](#).
- [Configuring the WP-SW2-EN7](#) on page [11](#).
- [Operating via Ethernet](#) on page [12](#).
- [Connecting Ethernet Port Directly to a PC](#) on page [12](#).

---

## Configuring the Network Switch

Before setting the system, make sure that your AV over IP network switch meets the following minimum requirements:

- Support for PoE, if it is being used to power **WP-SW2-EN7**.
  - Jumbo Frames – On. (at least 8000 bytes).
  - IGMP Snooping – On.
  - IGMP Querier – On.
  - IGMP Immediate/Fast Leave – On.
-  **WP-SW2-EN7** supports multicast IGMPv2 version.
- Unregistered Multicast Filtering – On.

---

## Configuring the WP-SW2-EN7

To start operating the **WP-SW2-EN7**:

- Use the recessed CH+/- buttons **⑥** to set the channel on which the encoded output is streamed. When reset or started for the first time, the device assigns a unique channel number for streaming, which is  $n + 1$ , where  $n$  is the highest channel number in use on the network.
- If **WP-SW2-EN7** detects a video signal from the HDMI port or the USB-C port that video is automatically streamed. By default, **WP-SW2-EN7** streams the USB-C input when a video signal is detected on both input ports.
- When video is streamed, the USB-C LED or HDMI LED light green, depending on the input port being streamed; The LEDs will flash green if no valid video is detected.

Use the Web UI to configure **WP-SW2-EN7** (see [Using WP-SW2-EN7 Embedded Web Pages](#) on page [15](#)).

---

## Operating via Ethernet

The **WP-SW2-EN7**'s embedded Web UI provides high-level configuration options. Access to this UI requires an ethernet connection to the **WP-SW2-EN7** and that you identify its IP address.

To identify the device's IP address, use any of the following methods:

- Connect the **WP-SW2-EN7** ethernet port directly to a PC.

For instructions, see [Connecting Ethernet Port Directly to a PC](#) on page [12](#).

When connected to a PC, the **WP-SW2-EN7** is given the default static IP address: 192.168.1.39. If this IP address is already in use, the system will provide a random unique IP in the range of 192.168.X.Y

- Connect the Ethernet port of **WP-SW2-EN7** to the Ethernet port to a network hub, switch or router using a straight-through cable with RJ-45 connectors.

Make sure your PC is connected to the same LAN as the **WP-SW2-EN7**.

By default, the **WP-SW2-EN7** is DHCP-enabled. Make sure that there is a DHCP server in the network so the device can obtain a valid IP address.

You can change the Ethernet parameters via the embedded web pages (see [Using WP-SW2-EN7 Embedded Web Pages](#) on page [15](#)).

- Use the Kramer **KDS-7-MNGR** to discover the IP address, see [www.kramerav.com/product/KDS-7-MNGR](http://www.kramerav.com/product/KDS-7-MNGR).

---

## Connecting Ethernet Port Directly to a PC

You can connect the Ethernet port of **WP-SW2-EN7** directly to the Ethernet port on your PC using a crossover cable with RJ-45 connectors.



This type of connection is recommended for identifying **WP-SW2-EN7** with the factory configured default IP address.

After connecting **WP-SW2-EN7** to the Ethernet port, configure your PC as follows:

1. Click **Start > Control Panel > Network and Sharing Center**.
2. Click **Change Adapter Settings**.
3. Highlight the network adapter you want to use to connect to the device and click **Change settings of this connection**.

The Local Area Connection Properties window for the selected network adapter appears as shown in [Figure 3](#).




Figure 3: Local Area Connection Properties Window

4. Highlight either **Internet Protocol Version 6 (TCP/IPv6)** or **Internet Protocol Version 4 (TCP/IPv4)** depending on the requirements of your IT system.
5. Click **Properties**.

The Internet Protocol Properties window relevant to your IT system appears as shown in [Figure 4](#) or [Figure 5](#).




Figure 4: Internet Protocol Version 4 Properties Window




Figure 5: Internet Protocol Version 6 Properties Window

6. Select **Use the following IP Address** for static IP addressing and fill in the details as shown in [Figure 6](#).

For TCP/IPv4 you can use any IP address in the range 192.168.1.1 to 192.168.1.255 (excluding 192.168.1.39) that is provided by your IT department.




Figure 6: Internet Protocol Properties Window

7. Click **OK**.
8. Click **Close**.
9. Continue with [Using WP-SW2-EN7 Embedded Web Pages](#) on page [15](#).

# Using WP-SW2-EN7 Embedded Web Pages

**WP-SW2-EN7** can be operated remotely using the embedded web pages. Access to the web pages requires a Web browser and an Ethernet connection.

Before attempting to connect:

- Perform the procedures in [Operating via Ethernet](#) on page [12](#).
- Ensure that your browser is supported.

The following operating systems and Web browsers are supported:

| Operating Systems | Browser |
|-------------------|---------|
| Windows 7         | Firefox |
|                   | Chrome  |
|                   | Safari  |
| Windows 10        | Edge    |
|                   | Firefox |
|                   | Chrome  |
| Mac               | Safari  |
| iOS               | Safari  |
| Android           | N/A     |

 If a web page does not update correctly, clear your Web browser's cache.

## Opening the WP-SW2-EN7 Web Pages

**To Browse the WP-SW2-EN7 Web Pages:**

1. Open your Internet browser.
2. Type the IP number of the device in the Address bar of your browser. For example, the default IP number: .
3. If your device is password-protected, the Login window appears.




Figure 7: Login Window

4. Enter the Username and Password (admin/admin, by default).

The **WP-SW2-EN7** Main page (AV Routing tab) opens.




Figure 8: Controller Application Page with Navigation List on Left

5. The Web UI has six pages, accessed from the Navigation menu on the left side. The Navigation menu has the following options:

**Home** **Main** page: AV routing tab.

**AV** **AV Settings** page: Auto Switch tab, Video tab, Audio tab and EDID tab.

**Device Settings** page: General tab, Network tab, Time & Date tab, Security tab and Users tab.

**Control** page: Settings tab (CEC and RS-232 parameters).

**Diagnostics** page: Status tab, Connections tab and Advanced tab.

**About** page.

Use the embedded web pages to perform the following actions:

- [Setting AV Routing Parameters](#) on page [17](#).
- [Activating HDCP Protection](#) on page [20](#).
- [Defining Audio Settings](#) on page [21](#).
- [Managing EDID](#) on page [22](#).
- [Defining General Settings](#) on page [23](#).
- [Defining Network Settings](#) on page [26](#).
- [Defining an NTP Time and Date Server](#) on page [29](#).
- [Setting WP-SW2-EN7 Security](#) on page [30](#).

- [Controlling User Access](#) on page [32](#).
- [Defining WP-SW2-EN7 Gateway Settings](#) on page [35](#).
- [Viewing WP-SW2-EN7 Status](#) on page [37](#).
- [Viewing WP-SW2-EN7 Connections Status](#) on page [38](#).
- [Viewing the WP-SW2-EN7 Logs](#) on page [39](#).
- [Viewing the About Page](#) on page [40](#).

## Setting AV Routing Parameters

Set the **WP-SW2-EN7** input port and streaming channel.

**To set AV routing parameters:**

1. Open the  **Main** page, (default) **AV Routing** tab.




Figure 9: Controller Application Page with Navigation List on Left

2. Select an input from the drop-down box (HDMI IN1 or USB IN2).
3. Define the following settings:
  - **Channel ID:** Set Channel ID and click **APPLY**.  
Channel ID defines the device input ID (1 to 999).
  - **Channel Name:** Enter the Stream Name and click **APPLY**.  
Stream name is identical to Host name (see [Defining General Settings](#) on page [23](#)) can include up to 24 characters; “-” and “\_” are allowed. The default name is the model name and MAC address connected by “-”.

- **Volume:** Use the slider to adjust the analog audio output volume (0 to 100%). Default is 80, 100% is 12dB and 0 is mute.
- **Mute:** Mute/unmute all audio outputs (HDMI OUT and MEDIA port).
- **Play/Stop:** Start or stop streaming of video, audio, IR, RS-232 and USB signals.

4. View the streaming parameters: HDCP Encryption (digital copyright protection), Resolution, Aspect Ratio, Audio Channels, Audio Rate and Audio Format.

AV routing parameters are defined.

## Defining Switching Mode

Configure how the system switches between the input ports when both HDMI and USB-C have valid video sources.

To define auto switching settings:

1. Open the **AV** AV Settings page, Auto Switch tab.




Figure 10: AV Settings Page – Auto Switch Tab

2. Set the **Switching Mode**:

- **Last Connected** (default) – WP-SW2-EN7 streams the last used input port. The device automatically switches input if the video source is disconnected.
- **Priority** – WP-SW2-EN7 streams the input port with the highest priority. The device automatically switches input if the video source is disconnected.
- **Manual** – The input port is set manually and does not change automatically.




Figure 11: Setting Priority Auto Switching

3. Click **SAVE**.

 If you need to reboot the device after changing the switching mode, wait at least 30 seconds. Switching mode settings will be lost if the device is rebooted less than 30 seconds after the change.

Auto switching mode is defined.

## Defining Signal Loss Timeouts

Set waiting times (timeouts) for **WP-SW2-EN7** when a signal is lost or a cable is disconnected.

To define signal loss timeouts:

1. Open the **AV** **AV Settings** page, Auto Switch tab.




Figure 12: AV Settings Page – Auto Switch Tab

2. Set the following timeouts (in seconds):

- **Signal Loss Switching Delay** – The length of time from when **WP-SW2-EN7** detects a signal loss, to when it switches to a different input (default 10).
- **Signal Detection Delay** – The length of time from when **WP-SW2-EN7** detects a signal, to when it switches to that input (default 0).
- **Cable Plug Delay** – The length of time from when **WP-SW2-EN7** detects a cable connected, to when it switches to that input (default 0).
- **Cable Unplug Delay** – The length of time from when **WP-SW2-EN7** detects a disconnected cable to when it switches to a different input (default 0).
- **Signal Loss Switching Power Off Delay** – The length of time from detection of a signal loss to turning off the 5V power output (default 900).
- **Signal Loss Switching Manual Override Delay** – The length of time from manual override's signal loss to the system switching to a different input (default 10).

3. Click **SAVE**.

Signal loss timeouts are defined.

## Activating HDCP Protection

High-bandwidth Digital Content Protection (HDCP) encrypts video content to prevent unauthorized copying. You can enable or disable this feature.

To activate / deactivate HDCP control:

1. Open the **AV** **AV Settings** page, Video tab.




Figure 13: AV Settings Page – Video Tab

2. Define the following settings:

- **Input 1** and **Input 2**: enable (**ON**)/disable (**OFF**) HDCP support for the input port.
- **Image Preview**: shows a preview of the video stream.
- **Maximum Bit Rate**: select the maximum transmission bandwidth. Select bandwidth (10Mbps, 50Mbps, 100Mbps, 150Mbps and 200Mbps) or Best Effort (default) to set bandwidth for best video quality output, allowing the peak bandwidth to reach 850Mbps.



After setting the maximum bit rate you need to restart the device.

- **Maximum Video Frame Rate (%)**: use the slider to configure the maximum frame rate in proportion. 100% (default) means zero compression on the frame rate.

3. Click **SAVE**.

HDCP protection is activated.

## Defining Audio Settings

The WP-SW2-EN7 output stream can take the audio from an analog input (14) the 3.5mm mini-jack) or stream the digital audio associated with the active HDMI or USB-C input.

To define Audio settings:

1. Open the **AV** **AV Settings** page, Audio tab.





Figure 14: AV Settings Page – Audio Tab


2. Define the **Audio Source Mode** selection:

**Last Connected:** the device uses the last connected audio source for the output stream.




Last Connected ▾

**Priority:** The device uses the highest priority audio input for the output stream; set the connection priority by clicking and dragging the input.




Priority ▾

**Manual:** The device does not switch the audio source unless it is manually selected in this screen or set by a Protocol 3000 command.



Manual ▾

Audio Source Selection



▲

3. Set the Audio Connection Guard Time (10 seconds, by default), which is the audio signal timeout period for the Last Connected or Priority modes. For example, if the active audio signal is lost (either becomes silent or is unplugged), after 10 seconds the second available audio source is automatically selected.
4. Click **SAVE**: Audio settings are updated.

## Managing EDID

Extended Display Identification Data (EDID) are used by video transmitters to define the display device capabilities. This information may be transmitted by display devices.

**WP-SW2-EN7** can manually load a specific EDID definition and can be locked to that EDID definition.

**To manage EDID:**

1. Open the **AV** **AV Settings** page, EDID tab.




Figure 15: AV Settings Page – EDID Management Tab

2. Set the EDID Lock:
  - Click **ON**, to lock to the last acquired EDID.
  - Click **OFF**, to unlock and acquire a new EDID.

3. After setting the **EDID Lock** to OFF, select an **EDID Mode** from the drop-down box:

**Default EDID:** Use the default built-in EDID.

EDID Lock  On  Off

EDID Mode  Default EDID

**Passthrough:** Acquire the EDID from a specific decoder:

- Enter the decoder's IP address.
- Click **READ**.

The EDID is copied from the decoder to the encoder.

EDID Lock  On  Off

EDID Mode  Passthrough

Read EDID from Specific Decoder  0.0.0  READ

**Custom:** download the EDID file from an external source.

To remove an EDID from the list:

- Select an EDID file from the list.
- Click **REMOVE**.

To upload an EDID file:

- Click **UPLOAD**.
- Select an EDID file from the Open window.
- Click **UPLOAD**. the EDID file is added to the list.
- Select the file and click **UPLOAD**.

EDID Mode  Custom

User EDID

|                              |                               |
|------------------------------|-------------------------------|
| default.bin                  | <input type="button"/> UPLOAD |
| 4K30_2.0CH_SDR.bin           | <input type="button"/> REMOVE |
| 4K30_Dolby_DTS7.1_SDR.bin    | <input type="button"/> APPLY  |
| 1080P50_Dolby_DTS7.1_SDR.bin |                               |
| 720P50_2.0CH_SDR.bin         |                               |
| 720P50_Dolby_DTS7.1_SDR.bin  |                               |



You can load up to 8 EDID files. If 8 files are loaded, you need to remove a file from the list. default.bin cannot be deleted.

The list returns to its default list upon factory reset.

## Defining General Settings

The  **Device Setting** page's (default) **General** tab enables performing the following actions:

- [Changing the Device's Host Name](#) on page [23](#).
- [Hiding the Channel Number on the Front Panel](#) on page [24](#).
- [Importing/Exporting Device Settings](#) on page [24](#).
- [Locating the Device \(making the LEDs flash\)](#) on page [25](#).
- [Managing the Firmware](#) on page [25](#).
- [Restarting or Resetting the Device](#) on page [26](#).

### Changing the Device's Host Name

To change the device's network ID (also known as the host name):

1. Open the **General** tab of the  **Device Setting** page.




Figure 16: Device Settings – General Tab

2. Enter a new Host Name and click **Apply**.

The Host Name has a maximum 24 characters and can include the special characters hyphen “-” and underscore “\_”, but not at the start or end of the name.

The default host name is **WP-SW2-EN7-xxxxxxxxxxxx** (“xxxxxxxxxxxx” = MAC address).

Host name is changed.

## Hiding the Channel Number on the Front Panel

The front panel display (8) of the **WP-SW2-EN7** shows the ethernet channel number on which the video is streamed. The display can be locked, hiding the channel number from users.

To hide the channel number:

1. Open the **Device Settings** page, General tab.
2. Set **Front Panel Lock** to ON.

The channel number is no longer visible on the front panel.

## Importing/Exporting Device Settings

Device settings can be exported to a backup file and uploaded to the device. Settings are imported/exported in a series of JSON files zipped into a single tar.gz file. Use the **Export** button to output examples.

### To export the device settings:

1. Open the  **Device Setting** page's (default) **General** tab.
2. Select the type of information you want to export or import:
  - **All without IP** – Outputs all the settings, including the logs but without network settings.
  - **Streams** – Outputs the content of the channel definitions set on the Main page, AV Routing tab.
  - **AV Settings Only** – Outputs the content of the AV Settings page: Auto-Switch, Video, Audio and EDID tabs.
  - **All including IP** – Outputs all the settings including the logs and network settings.



Figure 17: Device Settings page – Import/Export Device Settings

3. Click **Export** to output a list of JSON files compressed into a single **tar.gz** file.

Device settings exported.

## Locating the Device (making the LEDs flash)

To make the LEDs on the **WP-SW2-EN7** front panel flash for 60 seconds, so that you can identify the device:

1. Open the  **Device Setting** page's default **General** tab.
2. Click **Apply** on the **Locate Device** field.

The LEDs flash for 60 seconds and device is located.

## Managing the Firmware

### To view or upgrade the firmware version:

1. Open the  **Device Setting** page's default **General** tab.
2. Click **Upgrade** to run a firmware upgrade. For a detailed procedure, see [Upgrading Firmware](#) on page [41](#).




Figure 18: Device Settings Page – Firmware

3. The system saves the **Last Upgrade Date/Time** and previous firmware version (the **Standby Version**) in memory:
  - Click **Rollback** to roll back the firmware to the last loaded version.

For example, if the current firmware version is v0.8.5, and the standby version is v0.8.10; After “Rollback”, the device will update the firmware to the v0.8.10 version.

4. Click **RESTART** to reboot the device and activate the firmware.

Firmware is managed.

## Restarting or Resetting the Device

To reboot the device or restore it to default factory settings:

1. Open the  **Device Setting** page's default **General** tab.
2. Next to Device Reset:
  - Click **RESTART** to reboot the device.
  - Click **RESET** to restore default factory settings.
3. Refresh the page to see the new settings.

Device is restarted / reset.

---

## Defining Network Settings

The  **Device Settings** page, **Network Settings** tab controls the Ethernet port and IP settings of the **WP-SW2-EN7** and provides the following capabilities:

- [Using the Service Port for P3K & Gateway transmissions](#) on page [26](#).
- [Defining IP Casting Mode Setting and TTL](#) on page [28](#).
- [Managing TCP/UDP Ports](#) on page [28](#).

## Using the Service Port for P3K & Gateway transmissions

WP-SW2-EN7 has two Ethernet ports (SERVICE 1G and MEDIA 1G). By default, all network connections go to the MEDIA port with DHCP enabled and 802.1Q disabled.




Figure 19: Ethernet Ports on the Rear of the WP-SW2-EN7

WP-SW2-EN7 can use the Service port (with a separate IP address) for P3K & Gateway traffic. Video and other types of streaming always use the MEDIA port.

## To separate P3K & Gateway from the AV streams:

1. Open the  **Device Setting** page's default General tab and select the **Network** tab.




Figure 20: Device Settings Page – Network Tab

2. Change the following settings in the **Interface Settings** section of the **Network** tab (**Device Settings** page):

- In the **Port** column select **Service** and set **802.1Q** to **On**.
  - In the **VLAN ID** column, enter an integer number (2 – 4093) for P3K & Gateway services.
- This separates the P3K & Gateway packets.



802.1Q and VLAN are not required for the Media port.

3. If you want the P3K & Gateway port to have a static IP, set DHCP to **Off** and enter a subnet mask and gateway address.

If there is no valid DHCP server in the system, it will look for the random unique IP in the range of 169.254.X.Y. The allocated IP address is shown in the IP address field.

4. Click **SAVE**.

a RESTART Message appears. Click **RESTART** to apply the change.




Figure 21: Device Settings Page – RESTART Message

Gateway and p3K are separated from AV streams.

## Defining IP Casting Mode Setting and TTL

The **IP Casting Mode** is set by the Encoder. The setting on this field needs to be the same as that on the encoder:

- **Unicast** – The encoded stream is intended for a specific decoder.
- **Multicast** (default) – Any decoder can access the encoded stream.

**TTL** (time to live) limits the lifetime of the streamed data in the computer network. It prevents the IP packet from propagating endlessly through the network. The default value is 64, which means that after 64 hops the data packet is dropped.

To define casting mode and TTL:

1. Open the  **Device Setting** page's default General tab and select the **Network** tab.
2. In the IP casting area, check **Unicast** or **Multicast** (default) mode.
3. Set TTL (default, 64).
4. Click **SAVE**.

a RESTART Message appears (see [Figure 21](#)). Click **RESTART** to apply the change.

IP Casting and TTL are defined.

## Managing TCP/UDP Ports

TCP and UDP are protocols that define how data is streamed. The port on which the data is received must be defined in the system.

To manage TCP and UDP ports:

1. Open the  **Device Settings** page, Network tab.
2. Set TCP/UDP port number.  
The default values are **TCP Port** – 5000 and **UDP Port** – 50000.
3. Click **SAVE**.

a RESTART Message appears (see [Figure 21](#)). Click **RESTART** to apply the change.

TCP/UDP ports are managed.

## Defining an NTP Time and Date Server

You can sync the device time and date to a network time protocol (NTP) server.

To sync device time and date to a server:

1. Open the  **Device Settings** page, **Time and Date** tab.




Figure 22: Device Settings Page – Time and Date Tab

2. Set **NTP Time Server Usage** to **Yes**. This enables the NTP fields.
3. Enter the NTP time server address and set a daily sync hour.
4. Click **SAVE**.

The date and time are synchronized to the time server.

## Setting WP-SW2-EN7 Security

The  **Device Settings** page's Security tab enables HTTPS/TLS to encrypt communication with authenticated peers over the network and enables 802.1x authentication to prevent unauthorized access.

This section describes the following actions:

- [Configuring HTTPS](#) on page [30](#).
- [Defining 802.1x Authentication](#) on page [31](#).



Contact your IT administrator for the network access authentication.

### Configuring HTTPS

HTTPS encrypts communication with the **WP-SW2-EN7**.

**To configure HTTPS:**

1. Open the  **Device Settings** page, **Security** tab.





Figure 23: Device Settings Page – Security Tab

2. For HTTPS server, click **On** to enable HTTPS authentication service (default) or **Off** to disable HTTPS authentication.

3. When set to On, select one of the following:

- **Internal Certificate** – To use the factory default certificate for authentication.
- **Server Certificate** – To submit a certificate from the server for authentication. To do so, click  to upload the certificate. Enter the private key password (assigned by the IT administrator).



Internal Certificate

Server Certificate

Upload Certificate  

Private Key Password

**APPLY & REBOOT**

Figure 24: Security Tab – Server Certificate


4. Click **APPLY & REBOOT**.

HTTPS is configured.

## Defining 802.1x Authentication

To configure security for the WP-SW2-EN7:

1. Open the  **Device Settings** page, **Security** tab.
2. Click **ON** to enable the 802.1x authentication service. 802.1x supports authentication based on port and MAC address.
3. Select one of the following:
  - **PEAP-MSCHAP V2** – Enter a Username (up to 24 alphanumeric characters, including “\_” and “-“ characters within the username) and Password (up to 24 ASCII characters):



802.1x

IEEE 802.1x Authentication **On** **Off**

Authentication Method

PEAP-MSCHAP V2

Username

Password

Figure 25: Security Tab – EAP-MSCHAP V2 Authentication

- **EAP-TLS** – Enter a Username, click  to upload the certificates and keys and enter the private key password (assigned by IT administrator).

#### 4. Set Server Certificate On.

The screenshot shows a configuration interface for IEEE 802.1x authentication. At the top, 'IEEE 802.1x Authentication' is set to 'On'. The 'Authentication Method' section shows 'EAP-TLS' selected. Below this are fields for 'Username', 'Client Certificate', 'Private Key', and 'Private Key Password', each with a file selection icon. At the bottom, 'Server Certificate' is also set to 'On'.

Figure 26: EAP-TLS – Certificates and Password

#### 5. Click **APPLY**.

Security is configured.

## Controlling User Access

The  **Device Settings, Users** tab activates password-based device security and inactivity locking on the **WP-SW2-EN7**, preventing unauthorized access to the embedded web pages. The default password is **admin** (the user is always "admin"). By default, this security is disabled.

- [Activating Password-Based Device Security](#) on page [33](#).
- [Inactivity Locking](#) on page [34](#).
- [Changing the Password](#) on page [34](#).

## Activating Password-Based Device Security

To enable password-based device security:

1. Open the  **Device Settings** page, **Security** tab.




Figure 27: Device Settings Page – Users Tab

2. Set **Security Status** to On (Off by default). The following message appears.




Figure 28: Security Tab – Security Status


3. Click **PROCEED** and enter a password. The default user is "admin" and the default password is "admin".

Security is enabled and access requires authentication.

## Changing the Password

To change the password:

1. Open the  **Device Settings** page, **Security** tab.
2. Set **Security Status** to On (this activates password use).



Device Settings > Users

General Network Time and Date Security 

**Password**

Security Status  On  Off

Old Password  CHANGE

New Password

Confirm Password

Inactivity auto-logout time (min)  10  APPLY

Figure 29: Device Settings – Users Tab

3. Enter the **Old Password** and the **New Password**.



The new password must include at least one number, one special character (excluding spaces or commas), one uppercase and one lowercase letter and should be 8 to 24 characters long.

4. **Confirm** the new password.

5. Click **CHANGE**.

The password has changed.

## Inactivity Locking

Set the Inactivity auto-logout time (in minutes), to cause the page to log out automatically.

This option requires password-controlled access to the embedded web-pages (Security Status set to On). The default password is **admin** (the user is always "admin").

To set inactivity locking:

1. Open the  **Device Settings** page, **Security** tab.
2. Set **Security Status** to On (this activates password use).

By default, the device locks after 10 minutes. If necessary, enter a new time in minutes.

## Defining WP-SW2-EN7 Gateway Settings

WP-SW2-EN7 enables configuring CEC or RS-232 gateway Control. You can perform the following actions:

- [Configuring CEC Settings](#) on page [35](#).
- [Configuring RS-232 Settings](#) on page [36](#).

### Configuring CEC Settings

Consumer Electronics Control (CEC) is a feature of HDMI that enables users of remote devices to control them from a single source. WP-SW2-EN7 can send CEC commands to remote devices connected to the decoder, via the WP-SW2-EN7 built-in control gateway.

To set the CEC Gateway:

1. Open the  **Control** page (Settings tab).




Figure 30: Control > Settings Page – CEC Settings


2. **Enable** the CEC gateway.
  3. Enter a CEC command in hex format, up to 32 hex digits.
  4. Click **SEND**.
  5. View the CEC-enabled device response.
- CEC Gateway is configured.

## Configuring RS-232 Settings

Control systems connected by LAN to the **WP-SW2-EN7**, can transmit RS-232 commands to devices connected to the **WP-SW2-EN7** RS-232 port. The RS-232 Gateway must be enabled for this feature.

### To set RS-232 Gateway:

1. Open the  **Control** page, (default) Settings tab.



| RS-232 Settings                     |  |
|-------------------------------------|--|
| Gateway                             | <input type="button" value="Enable"/> <input type="button" value="Disable"/> |
| Gateway Port                        | 5001 <input type="button" value="^"/> <input type="button" value="v"/>       |
| Baud Rate                           | 115200 <input type="button" value="^"/> <input type="button" value="v"/>     |
| Data Bits                           | 8 <input type="button" value="^"/> <input type="button" value="v"/>          |
| Parity                              | None <input type="button" value="^"/> <input type="button" value="v"/>       |
| Stop Bits                           | 1 <input type="button" value="^"/> <input type="button" value="v"/>          |
| <input type="button" value="SAVE"/> |  |

Figure 31: Control > Settings Page – RS-232 Settings

2. **Enable** the RS-232 Settings **Gateway**.
3. Set the RS-232 **Gateway Port** (5001, by default).
4. Enter the **Baud Rate**: 9600, 19200, 38400, 57600 or 115200 (default).
5. Enter the **Data Bits**: 5, 6, 7 or 8 (default).
6. Enter **Parity**: None (default), Odd or Even.
7. Enter **Stop Bits**: 1 (default) or 2.
8. Click **SAVE**.

RS-232 Gateway is configured.

## Viewing WP-SW2-EN7 Status

The  **Diagnostics** page's **Status** tab displays general status information for the device:

**To view the device status:**

1. Open the  **Diagnostics page**, the (default) Status tab appears.




Figure 32: Diagnostics – Status Tab

2. View the device status:

- **Active**, for normal operation (green circle).
- **Standby**, device is powered Off, booting or in standby mode (yellow circle).

3. View the device's heat status:

- **Normal**, for temperatures under 45°C (green circle).
- **High**, for temperatures between 45°C and 60°C (orange circle).
- **Overheat**, for temperatures higher than 60°C (red circle).

4. View the status of each input port:

- **On**, when the input has a valid signal and is transmitting a signal (green circle).
- **Off**, when an input is not connected or there is no valid signal (gray circle).

5. View the LAN output status:

- **On**, when the LAN is transmitting a signal (green circle).
- **Off**, when the LAN has no signal output (gray circle).


Device status is viewed.

## Viewing WP-SW2-EN7 Connections Status

View the IP addresses of the devices connected to the **WP-SW2-EN7**.

**To view Connections status:**

1. Open the  **Diagnostics page**, Connections tab.



| Connection Protocol | Client IP Address | Client Port | Device Port |
|---------------------|-------------------|-------------|-------------|
| TCP                 | 192.168.1.2       | 51777       | 443         |
| TCP                 | 192.168.1.2       | 51839       | 443         |

Figure 33: Diagnostics – Status Tab

2. View the active connections, including the communication protocol, client's IP address and port, and the device port.

You have viewed the IP connections.

## Viewing the WP-SW2-EN7 Logs

View the system log and gateway messages counter.

To view the log and a count of RS-232 and CEC messages:

1. Open the  **Diagnostics page**, Advanced tab.




Figure 34: Diagnostics – Advanced Tab

2. To activate the log:
  - **On**, enables the **WP-SW2-EN7** system log.
  - **Off** (default), disables the system log.
3. Click **VIEW** to view the system log online.
4. Click **EXPORT** to copy the system log to a (.txt) file.
5. View the **Gateway Messages Counter** to see a count of the RS-232 or CEC Messages.

This shows the number of sent and received RS-232 and CEC messages.

## Viewing the About Page

The  **About** page shows the device model name, the hardware version, the firmware version and the Kramer Electronics Ltd details.




Figure 35: About Page

# Upgrading Firmware

Upgrade the firmware, view the date of the last upgrade, or rollback to the previous firmware revision in case of a problem.



Click **ROLLBACK** to update to the previous FW version.



If the device firmware version is lower than 0.6.3, contact Kramer tech support team at [support@kramerav.com](mailto:support@kramerav.com) or go to our Web site at [k.kramerav.com/support/downloads.asp](http://k.kramerav.com/support/downloads.asp).

**To upgrade the firmware:**

1. Open the **Device Setting** page's default **General** tab.




Figure 36: General Tab – Upgrading the Firmware

2. In the **Version** section, click **UPGRADE**. The Open window appears.
  3. Select the firmware file and click **Open**. The firmware upgrade pop-up window appears. Wait for upgrade completion.
  4. Once completed, refresh the web page and log-In.
- The Firmware is updated.

# Technical Specifications

|                          |  |  |
|--------------------------|--|--|
| Inputs                   | 1 HDMI   | On a female HDMI connector   |
|                          | 1 USB  | On a USB-C connector   |
|                          | 1 Audio  | On a female 3.5mm mini jack  |
| Ports                    | 2 Ethernet   | On RJ-45 female connectors   |
|                          | 1 RS-232   | On a 3-pin terminal block connector  |
| Video                    | Compression Standard                                   | JPEG based, private stream   |
|                          | Max Resolution   | 4K@60Hz (4:2:0) or 3K@30 (4:4:4)   |
| Audio                    | Supported Formats                                      | LPCM upto 7.1/24-bit/192kHz<br>Dolby Atmos™, Dolby TrueHD, Dolby Digital Plus™, Dolby Digital EX, Dolby Digital 5.1, Dolby Digital 2/0 Surround, Dolby Digital 2/0<br>DTS-HD Master Audio™, DTS-HD, DTS-ES Discrete 6.1, DTS-ES Matrix 6.1, DTS Digital Surround 5.1 |
| User Interface           | Indicators   | HDMI, USB and ON LEDs, front panel channel display.  |
|                          | Recessed Buttons                                       | CH+, CH- and factory reset button  |
| Power                    | PoE  | 37V to 57V   |
|                          | Typical Power Consumption                              | 5.04W  |
|                          | Full Load (including USB-C Charging) Power Consumption | 67.68W   |
|                          | Optional power supply                                  | 20V DC, 6A Max.  |
| Environmental Conditions | Operating Temperature                                  | 0° to +45°C (32° to 113°F)   |
|                          | Storage Temperature                                    | -20° to +70°C (-4° to 158°F)   |
|                          | Humidity   | 10% to 90%, RHL non-condensing   |
| Regulatory Compliance    | Safety   | CE, FCC  |
|                          | Environmental  | RoHs, WEEE   |
| Enclosure                | Size   | 2 Gang   |
|                          | Type   | SGCC (galvanized steel) and PC (polycarbonate)   |
|                          | Cooling  | Convection Ventilation   |
| Dimensions               | EU & UK Net Dimensions (H, W, D)                       | 15.1cm x 4.6cm x 8.6cm (5.9" x 1.8" x 3.4")  |
|                          | US Net Dimensions (H, W, D)                            | 12.1cm x 4.6cm x 12.1cm (4.8" x 1.6" x 4.5")   |
|                          | EU & UK Shipping Dimensions (W, D, H)                  | 23.8cm x 13.7cm x 7.5cm (9.4" x 5.4" x 2.95")  |
|                          | US Net Dimensions (W, D, H)                            | 20cm x 13.7cm x 7.5cm (7.9" x 5.4" x 2.95")  |
| Weight                   | Net Weight   | EU version: 0.42kg (0.9lb) approx.<br>US version: 0.44kg (0.97lb) approx.  |
|                          | Shipping Weight  | EU version: 0.65 (1.4lb) approx.<br>US version: 0.7 (1.5lb) approx.  |

Specifications are subject to change without notice at [www.kramerav.com](http://www.kramerav.com)

## Default Communication Parameters

| <b>P3K</b>  |  |
|---|--|
| Example (stop encoder decoder activity)                           | #KDS-ACTION 0<CR>  |
| <b>Ethernet</b>   |  |
| Opens the embedded webpage's Main page, (default) AV Routing tab. |  |
| DHCP  | Default  |
| IP Address:   | 192.168.1.39   |
| Subnet mask:  | 255.255.0.0  |
| Default gateway:  | 0.0.0.0  |
| TCP Port #:   | 5000   |
| UDP Port #:   | 50000  |
| Default username:   | admin  |
| Default password:   | admin  |
| <b>Full Factory Reset</b>   |  |
| Embedded web pages  | Device Settings > General > RESET  |
| Front panel buttons   | Press the recessed RESET button on the front panel for 10 seconds. On the US model, access to this button requires removal of the frame. |

## Default EDID

### Block 0

|           | <b>0</b> | <b>1</b> | <b>2</b> | <b>3</b> | <b>4</b> | <b>5</b> | <b>6</b> | <b>7</b> | <b>8</b> | <b>9</b> | <b>A</b> | <b>B</b> | <b>C</b> | <b>D</b> | <b>E</b> | <b>F</b> |
|-----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| <b>00</b> | 00       | FF       | FF       | FF       | FF       | FF       | FF       | 00       | 2D       | B2       | 00       | 00       | 01       | 00       | 00       | 00       |
| <b>10</b> | 25       | 1F       | 01       | 03       | 80       | 59       | 32       | 78       | 0A       | EE       | 91       | A3       | 54       | 4C       | 99       | 26       |
| <b>20</b> | 0F       | 50       | 54       | 21       | 08       | 00       | 81       | 00       | A9       | C0       | 01       | 01       | 01       | 01       | 01       | 01       |
| <b>30</b> | 01       | 01       | 01       | 01       | 01       | 01       | 02       | 3A       | 80       | D0       | 72       | 38       | 2D       | 40       | 10       | 2C       |
| <b>40</b> | 45       | 80       | 20       | C2       | 31       | 00       | 00       | 1E       | E7       | 31       | 80       | A0       | 70       | B0       | 1D       | 40       |
| <b>50</b> | 30       | 20       | 36       | 00       | 59       | 32       | 00       | 00       | 00       | 1A       | 00       | 00       | 00       | F7       | 00       | 0A       |
| <b>60</b> | 00       | 4A       | A2       | 24       | 02       | 00       | 00       | 00       | 00       | 00       | 00       | 00       | 00       | 00       | 00       | FC       |
| <b>70</b> | 00       | 4B       | 44       | 53       | 37       | 20       | 45       | 6E       | 63       | 6F       | 64       | 65       | 72       | 0A       | 01       | 36       |

### Block Type: Base EDID

Checksum verified  
Version 1 header verified

Manufacturer: KMR  
Product Code: 0 (0000h)  
Serial #: 1 (00000001h)

Date of Manufacture: Week 37 of 2021  
EDID Version 1, Revision 3  
Number of additional blocks: 1

### Basic Display Parameters and Features

• Video Input Definition: Digital  
VESA DFP 1.x Compatible (1.3)

Horizontal Screen Size: 89 cm  
Vertical Screen Size: 50 cm  
Display Transfer Characteristics (Gamma) 2.20  
Active off: No  
Suspend: No  
Standby: No  
RGB color display  
sRGB is not used as default  
Preferred Timing is native  
Display is non-continuous frequency (multi-mode)

### Chromaticity

Red: (0.640, 0.330)  
Green: (0.300, 0.600)  
Blue: (0.150, 0.060)  
White: (0.313, 0.329)

### Established Timings I

640 x 480 @ 60Hz  
800 x 600 @ 60Hz

### Established Timings II

1024 x 768 @ 60Hz  
Manufacturer's Timings:  
None

**Standard Timings**

Timing 1: 1280 x 800 @ 60 Hz (16:10)  
 Timing 2: 1600 x 900 @ 60 Hz (16:9)  
 Timing 3: Not Used  
 Timing 4: Not Used  
 Timing 5: Not Used  
 Timing 6: Not Used  
 Timing 7: Not Used  
 Timing 8: Not Used

**Descriptor Block: Detailed Timing (DTD)**

Pixel clock: 148.500 MHz  
 Refresh Rate: 50.000 Hz (approx.)  
 Scan type: Progressive  
 Horz Active: 1920  
 Vert Active: 1080  
 Horz Blank: 720  
 Vert Blank: 45  
 HSync Delay: 528  
 HSync Width: 44  
 VSync Delay: 4  
 VSync Width: 5  
 Image size: 800 mm x 450 mm  
 Border: 0 pixels x 0 lines  
 Stereo mode: Normal display, no stereo  
 Sync: Digital Separate, VSYNC+, HSYNC+

**Descriptor Block: Detailed Timing (DTD)**

Pixel clock: 127.750 MHz  
 Refresh Rate: 49.98 Hz (approx.)  
 Scan type: Progressive  
 Horz Active: 1920  
 Vert Active: 1200  
 Horz Blank: 160  
 Vert Blank: 29  
 HSync Delay: 48  
 HSync Width: 32  
 VSync Delay: 3  
 VSync Width: 6  
 Image size: 89 mm x 50 mm  
 Border: 0 pixels x 0 lines  
 Stereo mode: Normal display, no stereo  
 Sync: Digital Separate, VSYNC-, HSYNC+

**Descriptor Block: Established Timings III**

Version: 10  
 Supported Timings  
 1280 x 768 @ 60 Hz  
 1280 x 960 @ 60 Hz  
 1280 x 1024 @ 60 Hz  
 1360 x 768 @ 60 Hz  
 1440 x 900 @ 60 Hz  
 1400 x 1050 @ 60 Hz  
 1680 x 1050 @ 60 Hz  
 1600 x 1200 @ 60 Hz  
 1920 x 1200 @ 60 Hz (RB)

**Descriptor Block: Display Product Name**

Value: KDS7 Encoder

**Block 1**

|           | 0  | 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | A  | B  | C  | D  | E  | F  |
|-----------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| <b>00</b> | 02 | 03 | 40 | F3 | 4F | 9F | 10 | 21 | 20 | 14 | 05 | 5F | 5E | 5D | 64 | 63 |
| <b>10</b> | 62 | 04 | 02 | 11 | 23 | 09 | 07 | 01 | 83 | 01 | 00 | 00 | 6E | 03 | 0C | 00 |
| <b>20</b> | 10 | 00 | 38 | 3C | 20 | 00 | 80 | 01 | 02 | 03 | 04 | 67 | D8 | 5D | C4 | 01 |
| <b>30</b> | 3C | 80 | 00 | E5 | 0E | 60 | 61 | 65 | 66 | E2 | 00 | F9 | E3 | 05 | E0 | 00 |
| <b>40</b> | 66 | 21 | 56 | AA | 51 | 00 | 1E | 30 | 46 | 8F | 33 | 00 | 59 | 32 | 00 | 00 |
| <b>50</b> | 00 | 9E | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 |
| <b>60</b> | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 |
| <b>70</b> | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 00 | 1D |

**Block Type: CTA 861**

Checksum verified

**E-EDID CTA Extension Version 3**

Reserved data block offset 64

- Native DTDs in EDID: 3
- Y: Supports underscan
- Y: Supports basic audio
- Y: Supports YCbCr 4:4:4
- Y: Supports YCbCr 4:2:2

**CTA Data Block: Tag 2, bytes 15: Video Data**

Number of Descriptors: 15

SVD #001: (31) 1920x1080p @ 50 Hz 16:9 Native  
 SVD #002: (16) 1920x1080p @ 60 Hz 16:9  
 SVD #003: (33) 1920x1080p @ 25 Hz 16:9  
 SVD #004: (32) 1920x1080p @ 24 Hz 16:9  
 SVD #005: (20) 1920x1080i @ 50 Hz 16:9  
 SVD #006: (5) 1920x1080i @ 60 Hz 16:9  
 SVD #007: (95) 3840x2160p @ 30 Hz 16:9  
 SVD #008: (94) 3840x2160p @ 25 Hz 16:9  
 SVD #009: (93) 3840x2160p @ 24 Hz 16:9  
 SVD #010: (100) 4096x2160p @ 30 Hz 256:135  
 SVD #011: (99) 4096x2160p @ 25 Hz 256:135

SVD #012: (98) 4096x2160p @ 24 Hz 256:135  
 SVD #013: (4) 1280x720p @ 60 Hz 16:9  
 SVD #014: (2) 720x480p @ 60 Hz 4:3  
 SVD #015: (17) 720x576p @ 50 Hz 4:3

#### CTA Data Block: Tag 1, bytes 3: Audio Data

Number of Descriptors: 1

Audio Format Code: LPCM (IEC 60958 PCM [30, 31])  
 Channels: 2  
 Sampling Freq: 32 kHz, 44.1 kHz, 48 kHz  
 Sampling Size (bit): 16

#### CTA Data Block: Tag 4, bytes 3: Speaker Allocation

- Front Left/Front Right (FL/FR)

#### CTA Data Block: Tag 3, bytes 14: Vendor Specific

24-bit IEEE Registration ID: 0x000C03  
**HDMI 1.4b Vendor Specific Data Block**

• CEC Physical Address: 1.0.0.0

• ISRC/ACP: Not supported

• Deep Color

  36 bits per color

  30 bits per color

  YCbCr 4:4:4 supported

• DVI dual-link: Not supported

• Max TMDS clock: 300 MHz

• Content types: None

• Latency: Not Present

• Interlaced Latency: Not Present

• Basic 3D: Not supported

• Image Size: No additional information.

• 4K x 2K Support:

  3840x2160 30Hz

  3840x2160 25Hz

  3840x2160 24Hz

  4096x2160 24Hz

#### CTA Data Block: Tag 3, bytes 7: Vendor Specific

24-bit IEEE Registration ID: 0xC45DD8

#### HDMI Forum Vendor Specific Data Block

• Version: 1

• Max\_TMDs\_Character\_Rate: 300 MHz

• Max FRL Rate: Not Supported

Y: SCDC\_Present  
 N: RR\_Capable  
 N: CABLE\_STATUS  
 N: CCBPCI  
 N: LTE\_340MHz\_scramble  
 N: Independent\_view  
 N: Dual\_View  
 N: 3D OSD\_Disparity  
 N: UHD\_VIC  
 N: DC\_48bit\_420  
 N: DC\_36bit\_420  
 N: DC\_30bit\_420

#### CTA Data Block: Extended Tag 14, bytes 5: Y420 Video Data

Number of Descriptors: 4

SVD #016: (96) 3840x2160p @ 50 Hz 16:9  
 SVD #017: (97) 3840x2160p @ 60 Hz 16:9  
 SVD #018: (101) 4096x2160p @ 50 Hz 256:135  
 SVD #019: (102) 4096x2160p @ 60 Hz 256:135

#### CTA Data Block: Extended Tag 0, bytes 2: Video Capability

CE: Always overscanned

IT: Always underscanned

PT: Supports over and underscan

RGB Quantization: Selectable (via AVI Q)

YCC Quantization: Selectable (via AVI YQ)

#### CTA Data Block: Extended Tag 5, bytes 3: Colorimetry

BT.2020-cYCC

BT.2020-YCC

BT.2020-RGB

#### Descriptor Block: Detailed Timing (DTD)

Pixel clock: 85.500 MHz

Refresh Rate: 59.790 Hz (approx.)

  Scan type: Interlace

  Horz Active: 1366

  Vert Active: 768

  Horz Blank: 426

  Vert Blank: 30

  HSync Delay: 70

  HSync Width: 143

  VSync Delay: 3

  VSync Width: 3

  Image size: 89 mm x 50 mm

  Border: 0 pixels x 0 lines

  Stereo mode: Normal display, no stereo

  Sync: Digital Separate, VSYNC+, HSYNC+

## Default Parameters

| Page Name       | Tab Name        | Fields  | Editable Field | Exportable Field | Default Values   |
|-----------------|-----------------|---|----------------|------------------|--|
| Main            | AV Routing      | Channel ID  | Yes            | Yes              | An unused ethernet channel number is automatically assigned.   |
|                 |                 | Channel Name                                      | Yes            | Yes              | WP-SW2-EN7-xxxxxxxxxxxx<br>"xxxxxxxxxxxx" is the MAC address.  |
|                 |                 | Volume  | Yes            | Yes              | 80   |
|                 |                 | Mute  | Yes            | Yes              | Off  |
|                 |                 | Play/Stop   | Yes            | Yes              | Play   |
| AV Settings     | Auto Switch     | Switching Mode                                    | Yes            | Yes              | Last Connected   |
|                 |                 | Signal Loss Switching Delay (sec)                 | Yes            | Yes              | 10   |
|                 |                 | Signal Detection Delay (sec)                      | Yes            | Yes              | 0  |
|                 |                 | Cable Plug Delay (sec)                            | Yes            | Yes              | 0  |
|                 |                 | Cable Unplug Delay (sec)                          | Yes            | Yes              | 0  |
|                 |                 | Signal Loss Switching Manual Override Delay (sec) | Yes            | Yes              | 0  |
|                 | Video           | Input HDCP Appearance Port 1                      | Yes            | Yes              | On   |
|                 |                 | Input HDCP Appearance Port 2                      | Yes            | Yes              | On   |
|                 |                 | Maximum Bit Rate                                  | Yes            | Yes              | Best Effort  |
|                 |                 | Maximum Video Frame Rate (%)                      | Yes            | Yes              | 100  |
|                 | Audio           | Audio Source Mode                                 | Yes            | Yes              | Last Connected   |
|                 |                 | Audio Source Selection                            | Yes            | Yes              | HDMI/USB-C   |
|                 |                 | Audio Connection Guard Time (sec)                 | Yes            | Yes              | 10   |
|                 | EDID Management | EDID Lock   | Yes            | Yes              | On   |
|                 |                 | EDID Mode   | No             | Yes              | Default Mode   |
| Device Settings | General         | Host Name   | Yes            | Yes              | WP-SW2-EN7-xxxxxxxxxxxx<br>("xxxxxxxxxxxx" is the MAC address) |
|                 |                 | Front Panel Lock                                  | Yes            | Yes              | Off  |
|                 |                 | Import/Export Device Settings                     | Yes            | Yes              | All including IP   |
|                 | Network         | Stream Port                                       | No             | Yes              | Media  |
|                 |                 | Stream 802.1Q                                     | No             | Yes              | N/A  |
|                 |                 | Stream VLAN Tag                                   | No             | Yes              | N/A  |
|                 |                 | Stream DHCP                                       | Yes            | Yes              | On   |
|                 |                 | P3K & Gateway Port                                | Yes            | Yes              | Media  |
|                 |                 | P3K & Gateway 802.1Q                              | Yes            | Yes              | Off  |
|                 |                 | P3K & Gateway VLAN Tag                            | Yes            | Yes              | N/A  |
|                 |                 | P3K & Gateway DHCP                                | Yes            | Yes              | N/A  |
|                 |                 | IP Casting Mode                                   | Yes            | Yes              | Multicast  |
|                 |                 | TTL   | Yes            | Yes              | 64   |
|                 | Time and Date   | TCP Port  | Yes            | Yes              | 5,000  |
|                 |                 | UDP Port  | Yes            | Yes              | 50,000   |
|                 |                 | Date  | No             | Yes              | 01-01-1970   |
|                 |                 | Time  | No             | Yes              | N/A  |
|                 |                 | Time Zone   | Yes            | Yes              | 00:00 Greenwich  |
|                 |                 | NTP Time Server Usage                             | Yes            | Yes              | No   |
|                 | Security        | NTP Time Server Address                           | Yes            | Yes              | N/A  |
|                 |                 | NTP Daily Sync Hour                               | Yes            | Yes              | N/A  |
|                 | Users           | HTTPS Server                                      | Yes            | Yes              | On; Internal Certificate                                       |
|                 |                 | IEEE 802.1x Authentication                        | Yes            | Yes              | Off  |
|                 | Control         | Security Status                                   | Yes            | Yes              | Off  |
|                 |                 | Inactivity auto-logout time                       | Yes            | Yes              | 10   |
| Diagnostics     | Advanced        | CEC Gateway                                       | Yes            | Yes              | Enable   |
|                 |                 | RS-232 Gateway                                    | Yes            | Yes              | Enable   |
|                 |                 | RS-232 Port                                       | Yes            | Yes              | 5001   |
|                 |                 | RS-232 Baud rate                                  | Yes            | Yes              | 115200   |
|                 |                 | RS-232 Data Bits                                  | Yes            | Yes              | 8  |
|                 |                 | RS-232 Parity                                     | Yes            | Yes              | None   |
|                 |                 | RS-232 Stop Bits                                  | Yes            | Yes              | 1  |
|                 |                 | Active Syslog                                     | Yes            | Yes              | Off  |

# Protocol 3000

Kramer devices can be operated using Kramer Protocol 3000 commands sent via serial or Ethernet ports.

## Understanding Protocol 3000

Protocol 3000 commands are a sequence of ASCII letters, structured according to the following.

- **Command format:**


| Prefix | Command Name | Constant (Space) | Parameter(s) | Suffix |
|--------|--------------|------------------|--------------|--------|
| #      | Command      |                  | Parameter    | <CR>   |

- **Feedback format:**

| Prefix | Device ID | Constant | Command Name | Parameter(s) | Suffix   |
|--------|-----------|----------|--------------|--------------|----------|
| ~      | nn        | @        | Command      | Parameter    | <CR><LF> |

- **Command parameters** – Multiple parameters must be separated by a comma (,). In addition, multiple parameters can be grouped as a single parameter using brackets ([ and ]).
- **Parameters attributes** – Parameters may contain multiple attributes. Attributes are indicated with pointy brackets (<...>) and must be separated by a period (.).

The command framing varies according to how you interface with **WP-SW2-EN7**. The following figure displays how the # command is framed using terminal communication software (such as Hercules):



# Protocol 3000 Commands

| Function            | Description  | Syntax  | Response  | Parameters/Attributes  | Example  |
|---------------------|--|---|---|--|--|
| #                   | Protocol handshaking.<br>NOTE: Validates the Protocol 3000 connection and gets the machine number.<br>Step-in master products use this command to identify the availability of a device.   | #<CR>   | ~nn@OK<CR><LF>  |  | #<CR>  |
| BEACON-EN           | Set beacon rate.   | #BEACON-EN<br>port_id,status,rate<CR><LF>                         | ~nn@BEACON-EN<br>port_id,status,rate<CR><LF>  | port_id – ID of the Ethernet port<br>0 – Media Port<br>1 – Service Port<br>status – Enable/Disable beacon<br>0 – Disable (default)<br>1 – Enable<br>rate – Repetition rate in seconds<br>1 – 1 second (minimum)<br>10 – 10 seconds (default)<br>1800 – 30 minutes (maximum)  | Set beacon information:<br>#BEACON-EN,0,1,10<CR>                                   |
| #BEACON-EN?         | Get beacon rate.   | #BEACON-EN?<br><CR><LF>   | ~nn@BEACON-EN<br>port_id,status,rate<CR><LF>  | port_id – ID of the Ethernet port:<br>0 – Media Port<br>1 – Service Port<br>status – Enable/Disable beacon:<br>0 – Disable (default)<br>1 – Enable<br>rate – Repetition rate in seconds:<br>1 – 1 second (minimum)<br>10 – 10 seconds (default)<br>1800 – 30 minutes (maximum)   | Get beacon information:<br>#BEACON-EN?<CR>   |
| BEACON-INFO?        | Get beacon information, including IP address, UDP control port, TCP control port, MAC address, model, name.<br>NOTE:<br>+ There is no Set command. Get command initiates a notification.<br>+ 'port_id' must be same as '#KDS-GW-ETH' used | #BEACON-INFO?<br>port_id<CR>                                      | ~nn@BEACON-INFO<br>port_id,ip_string,udp_port,tcp_port,mac_address,model,name<CR><LF> | port_id – ID of the Ethernet port:<br>0 – Media Port<br>1 – Service Port<br>ip_string – Dot-separated representation of the IP address:<br>udp_port – UDP control port<br>tcp_port – TCP control port<br>mac_address – Dash-separated mac address<br>model – Device model<br>name – Device name  | Get beacon information:<br>#BEACON-INFO?,0<CR>                                     |
| BUILD-DATE?         | Get device build date  | #BUILD-DATE?<CR>  | ~nn@BUILD-DATE<br>date,<br>time<CR><LF>   | date – Format: YYYY/MM/DD<br>time – Format: hh:mm:ss   | Get the device build date:<br>#BUILD-DATE?<CR>                                     |
| CEC-GW-PORT-ACTIVE  | Set CEC Gateway mode - Whether CEC commands coming from HDMI stream to LAN   | #CEC-GW-PORT-ACTIVE<br>gw_mode<CR>                                | ~nn@CEC-GW-PORT-ACTIVE<br>gw_mode<CR><LF>   | gw_mode:<br>0 – CEC Passthrough mode<br>1 – CEC Gateway mode – command to be sent to HDMI Input.<br>2 – CEC Gateway mode – command to be sent to HDMI Output. (KDS-DEC7 & WP-DEC7)<br>3 – CEC Gateway mode – command to be sent to HDMI Loop Through (KDS-EN7, KDS-SW2-EN7)  | Set CEC Gateway mode:<br>#CEC-GW-PORT-ACTIVE 1<CR>                                 |
| CEC-GW-PORT-ACTIVE? | Get CEC Gateway mode - Whether CEC commands coming from HDMI stream to LAN   | #CEC-GW-PORT-ACTIVE?<CR>  | ~nn@CEC-GW-PORT-ACTIVE<br>gw_mode<CR><LF>   | gw_mode:<br>0 – CEC Passthrough mode<br>1 – CEC Gateway mode – command to be sent to HDMI Input.<br>2 – CEC Gateway mode – command to be sent to HDMI Output. (KDS-DEC7 & WP-DEC7)<br>3 – CEC Gateway mode – command to be sent to HDMI Loop Through (KDS-EN7, KDS-SW2-EN7)  | Get CEC Gateway mode:<br>#CEC-GW-PORT-ACTIVE?<CR>                                  |
| CEC-NTFY            | Notify about CEC command retrieved from bus.<br>NOTE: Notification is sent to all ports upon CEC message retrieval from CEC bus  | N/A   | ~nn@CEC-NTFY<br>port_index,len,<cec_command...><CR><LF>                               | port_index – CEC port notifying the command<br>len – 1-16<br>cec_command – CEC format command (in HEX format, no leading zeros, no '0x' prefix)  | Notify about CEC command retrieved from bus:<br>~01@CEC-NTFY<br>1,2,0F36<CR>       |
| CEC-SND             | Send CEC command to port.  | #CEC-SND<br>port_index,sn_id,cmd_name,cec_len,cec_command<CR>     | ~nn@CEC-SND<br>port_index,sn_id,cmd_name,cec_len,cec_command<CR><LF>                  | port_index – CEC port transmitting the command (1 – number of ports)<br>sn_id – serial number of command for flow control and response commands from device<br>cmd_name – command name<br>cec_len – 1-16<br>cec_command – CEC format command (in HEX format, no leading zeros, no '0x' prefix)<br>cec_mode – CEC mode<br>0 – Sent (Only support Sent, other error feedback with common P3K error code) | Send CEC command to port:<br>#CEC-SND<br>1,1,1,2,E004<CR>                          |
| COM-ROUTE-ADD       | Add a communication route tunnel connection  | #COM-ROUTE-ADD<br>com_id,port_type,port_id,eth_rep_en,timeout<CR> | ~nn@COM-ROUTE-ADD<br>com_id,port_type,port_id,eth_rep_en,timeout<CR><LF>              | com_id – Machine dependent (number of ports, only 1 accepted)<br>port_type – TCP: 0 – TCP<br>port_id – port number (5000 to 5999)<br>eth_rep_en – Ethernet Reply<br>0 – COM port does not send replies to new clients<br>1 – COM port sends replies to new clients.<br>timeout – Keep alive timeout in seconds (1 to 3600)   | Add a communication route tunnel connection:<br>#COM-ROUTE-ADD<br>1,0,5001,1,1<CR> |
| COM-ROUTE-REMOVE    | Remove a communication route tunnel connection.  | #COM-ROUTE-REMOVE<br>com_id<CR>                                   | ~nn@COM-ROUTE-REMOVE<br>com_id<CR><LF>  | com_id – Machine dependent (number of ports, only 1 accepted)  | Remove a communication route tunnel connection:<br>#COM-ROUTE-REMOVE<br>1<CR>      |

| Function      | Description  | Syntax                                 | Response  | Parameters/Attributes  | Example  |
|---------------|--|--|---|--|--|
| COM-ROUTE?    | Get communication route tunnel connection state  | #COM-ROUTE?<br>com_id<CR>              | ~nn@COM-ROUTE<br>com_id,port_type,port_id,eth_rep_en,timeout<CR><LF>  | com_id – Machine dependent (number of ports, only 1 accepted). * (get all route tunnels)<br>port_type – TCP/UDP<br>0 – TCP<br>1 – UDP<br>port_id – TCP/UDP port number<br>eth_rep_en – Ethernet Reply<br>0 – COM port does not send replies to new clients<br>1 – COM port sends replies to new clients.<br>timeout – Keep alive timeout in seconds (1 to 3600)  | Get tunneling port routing for all route tunnels:<br>#COM-ROUTE?*<CR>  |
| EDID-ACTIVE   | Activate specific EDID<br>Note: only valid in custom mode. in other modes will return error.   | #EDID-ACTIVE<br>Input_id,Index<CR>     | ~nn@EDID-ACTIVE<br>Input_id,Index<CR><LF>   | Input_id – 1<br>Index - Index in EDID List   | Set custom EDID #1 active on input 1; If not in CUSTOM mode, return ERROR<br>#EDID-ACTIVE,1,1<CR>                        |
| EDID-ACTIVE?  | Get current active EDID<br>Note: only valid in custom mode. in other modes will return error.  | #EDID-ACTIVE?<br>Input_id<CR>          | ~nn@EDID-ACTIVE<br>Input_id,Index<CR><LF>   | Input_id – 1<br>Index - Index in EDID List   | Get active custom EDID index on Input 1; If not in CUSTOM mode, return ERROR<br>#EDID-ACTIVE?,1<CR>                      |
| EDID-LIST?    | Get a list of currently existing EDID's (Get only)   | #EDID-LIST?<CR>                        | ~nn@#EDID-LIST<br>[port_idx,"name"],...<CR><LF>   | port_idx – HDMI port index, only 1 is accepted<br>name – EDID file name  | Get EDID list<br>#EDID-LIST?<CR><br><br>Return:<br>~nn@EDID-LIST<br>[0,"DEFAULT"],[2,"SONY"],<br>[5,"PANASONIC"]<CR><LF> |
| EDID-MODE     | Set EDID work mode   | #EDID-MODE<br>Input_id,Mode,Index<CR>  | ~nn@#EDID-MODE<br>Input_id,Mode,Index<CR><LF>   | Input_id – 1<br>Mode:<br>PASSTHRU (get from decoder)<br>CUSTOM<br>DEFAULT<br>Index: CUSTOM should have an 'index' taken from 'EDID-LIST?'  | Set EDID to custom mode, idx is 1<br>#EDID-MODE<br>1,CUSTOM,1<CR>  |
| EDID-MODE?    | Get EDID work mode<br>Add New Command for KDS-7  | #EDID-MODE?<br>Input_id<CR>            | ~nn@#EDID-MODE<br>Input_id,Mode,Index<CR><LF>   | Input_id – 1<br>Mode:<br>PASSTHRU (get from decoder)<br>CUSTOM<br>DEFAULT<br>Index: CUSTOM should have an 'index' taken from 'EDID-LIST?'  | Get EDID Mode<br>#EDID-MODE?,1<CR>   |
| EDID-NET-SRC  | Set MAC on net device to be EDID source.<br>It is only valid when EDID-MODE is set as PASSTHRU   | #EDID-NET-SRC<br>input_id,src_ip<CR>   | ~nn@EDID-NET-SRC<br>input_id,src_ip<CR><LF>   | input_id – 1<br>src_ip – DEC IP address  | Set MAC on net device for Input 1<br>#EDID-NET-SRC<br>1,192.168.1.40<CR>   |
| EDID-NET-SRC? | Get MAC on net device of EDID source   | #EDID-NET-SRC?<br>input_id<CR>         | ~nn@EDID-NET-SRC<br>input_id,src_ip<CR><LF>   | input_id – 1<br>src_ip – DEC IP address  | Get MAC on Net device for Input 1<br>#EDID-NET-SRC?,1<CR>  |
| EDID-RM       | Remove custom EDID from EDID list.<br>Note: should return ERR if this EDID is in USE.  | #EDID-RM<br>Index<CR>                  | ~nn@#EDID-RM<br>Index<CR><LF>   | Index: 1...N - EDID index to remove. Taken from 'EDID-LIST?'. index 0 (Default) is not removable.  | remove EDID from slot 3 and delete the file<br>#EDID-RM 3<CR>  |
| ETH-PORT      | Set Ethernet port protocol.<br>NOTE: If the port number you enter is already in use, an error is returned.<br>The port number must be within the following range: 0-(2^16-1).  | #ETH-PORT<br>port_type,<br>port_id<CR> | ~nn@ETH-PORT<br>port_type,<br>port_id<CR><LF>   | port_type:<br>TCP<br>UDP<br>port_id – port_type TCP in range 5000~5099 and port_type UDP in range 50000~50999  | Set the Ethernet port protocol for TCP to port 5000:<br>#ETH-PORT<br>TCP,5000<CR>  |
| ETH-PORT?     | Get Ethernet port protocol.  | #ETH-PORT?<br>port_type<CR>            | ~nn@ETH-PORT<br>port_type, port_id<CR><LF>  | port_type:<br>TCP<br>UDP<br>port_id – port_type TCP in range 5000~5099 and port_type UDP in range 50000~50999  | Get the Ethernet port protocol for TCP:<br>#ETH-PORT?TCP<CR>   |
| ETH-TUNNEL?   | Get an open tunnel's parameters.   | #ETH-TUNNEL?<br>tunnel_id<CR>          | ~nn@ETH-TUNNEL<br>[[tunnel_id,com_id,port_type,port_id,eth_ip,re<br>mote_port_id,eth_rep_en,connection_type],...]<CR><LF> | tunnel_id – Tunnel ID number, * (get all open tunnels)<br>com_id – Machine dependent<br>1 – First COM Port<br>port_type – TCP/UDP<br>0 – TCP<br>port_id – TCP/UDP port number<br>eth_ip – Client IP address<br>remote_port_id – Remote port number<br>eth_rep_en – Ethernet Reply<br>0 – COM port does not send replies to new clients<br>1 – COM port sends replies to new clients<br>connection_type – Connection type<br>1 – wired connection | Get all open tunnel parameters:<br>#ETH-TUNNEL?*<CR>   |
| FACTORY       | Reset device to factory default configuration<br>NOTE: This command deletes all user data from the device. The deletion can take some time. Your device may require powering off and powering on for the changes to take effect. | #FACTORY<CR>                           | ~nn@FACTORY<br>ok<CR><LF>   |  | Reset the device to factory default configuration:<br>#FACTORY<CR>   |
| GTW-MSG-NUM?  | Get Control Gateway Messages Counter from the device boot done. Add Recv_Count and Send_Count<br>NOTE: <date> is legacy parameter, for KDS7 always be ignored  | #GTW-MSG-NUM?<br>message_type,date<CR> | ~nn@GTW-MSG-NUM<br>message_type,date,re<br>cv_counter,send_coun<br><CR><LF>   | message_type - where<br>1 = CEC<br>3 = RS232<br>date – Format: DD-MM-YYYY.<br>recv_counter – counter of receive messages<br>send_counter – counter of send messages  | Get Control Gateway Messages Counter from certain period<br>#GTW-MSG-NUM?,1,01-01-1970<CR>                               |
| HDCP-MOD      | Set HDCP mode.<br>NOTE: Set HDCP working mode on the device input:<br>HDCP supported - HDCP_ON [default].<br>HDCP not supported - HDCP OFF.  | #HDCP-MOD<br>in_index,<br>mode<CR>     | ~nn@HDCP-MOD<br>in_index,mode<CR><LF>   | in_index – Number that indicates the specific input: 1-N (N= the total number of inputs)<br>mode – HDCP mode:<br>0 – HDCP Off<br>1 – HDCP On   | Set the input HDCP-MODE of IN 1 to Off:<br>#HDCP-MOD,1,0<CR>   |

| Function       | Description  | Syntax                              | Response   | Parameters/Attributes   | Example   |
|----------------|--|-------------------------------------|--|---|---|
| HDCP-MOD?      | Get HDCP mode.NOTE: Set HDCP working mode on the device input:<br>HDCP supported - HDCP_ON [default].<br>HDCP not supported - HDCP OFF.<br>HDCP support changes following detected sink - MIRROR OUTPUT.                         | #HDCP-MOD?<br>in_index<CR>          | ~nn@HDCP-MOD<br>in_index,mode<CR><LF>                  | in_index – Number that indicates the specific input: 1-N (N= the total number of inputs)<br>mode – HDCP mode:<br>0 – HDCP Off<br>1 – HDCP On<br>3 – HDCP Mirror Mode - used by KDS-7 decoder to allow an HDCP 2.2 source connected to the encoder to play on an HDCP 1.4 TV/display connected to the decoder. | Get the input HDCP-MODE of IN 1 HDMI:<br>#HDCP-MOD?1<CR>                  |
| HDCP-STAT?     | Get HDCP signal status.<br>NOTE: io_mode =1 – get the HDCP signal status of the sink device connected to the specified output.<br>io_mode =0 – get the HDCP signal status of the source device connected to the specified input. | #HDCP-STAT?<br>io_mode,in_index<CR> | ~nn@HDCP-STAT<br>io_mode,in_index,stat us<CR><LF>      | io_mode – Input/Output<br>0 – Input<br>1 – Output<br>in_index – 1-N (N=total number of inputs or outputs)<br>status – Signal encryption status - valid values On/Off where 0 = HDCP Off, 1 = HDCP On  | Get the output HDCP-STATUS of IN 1:<br>#HDCP-STAT?0,1<CR>                 |
| HELP           | Get command list or help for specific command.   | #HELP<CR>                           | 1. Multi-line:<br>~nn@Device cmd_name,cmd_name<CR><LF> | cmd_name – Name of a specific command   | Get the command list:<br>#HELP<CR>  |
| HW-TEMP?       | Get device heat  | #HW-TEMP?<br>region_id,mode<CR>     | ~nn@HW-TEMP<br>region_id,temperature<CR><LF>           | region_id – Always 0<br>mode – Celsius or Fahrenheit<br>0 – Celsius<br>1 – Fahrenheit<br>temperature – Temperature of the HW region, rounded down to the closest integer  | Get temperature in Celsius of first cpu<br>#HW-TEMP?0,0<CR>               |
| HW-VERSION?    | Get hardware version   | #HW-VERSION?<CR>                    | ~nn@HW-VERSION<br>hardware_version<CR><LF>             | hardware_version – XX.XX.XXXX where the digit groups are: major.minor.version   | Get hardware version<br>#HW-VERSION?<CR>                                  |
| IDV            | Set visual indication from device.<br>NOTE: Using this command, some devices can light a sequence of buttons or LEDs to allow identification of a specific device from similar devices.  | #IDV<CR>                            | ~nn@IDV ok<CR><LF>                                     |   | #IDV<CR>  |
| KDS-ACTION     | Set action to perform by encoder/decoder.  | #KDS-ACTION<br>kds_mode<CR>         | ~nn@KDS-ACTION<br>kds_mode<CR><LF>                     | kds_mode – Action (state) for encoder/decoder<br>0 – Stop<br>1 – Play<br>2 – Save config  | Stop the encoder/decoder:<br>#KDS-ACTION?0<CR>                            |
| KDS-ACTION?    | Get last action (state) performed by encoder/decoder.  | #KDS-ACTION?<CR>                    | ~nn@KDS-ACTION<br>kds_mode<CR><LF>                     | kds_mode – Action (state) for encoder/decoder<br>0 – Stop<br>1 – Play<br>2 – Save config  | Get the last action performed by the encoder/decoder:<br>#KDS-ACTION?<CR> |
| KDS-AUD        | Set audio source/destination.<br>+ Only available on Encoder   | #KDS-AUD<br>mode<CR>                | ~nn@KDS-AUD<br>mode<CR><LF>                            | mode – Encoder/decoder audio mode<br>Streamer Audio Encoder<br>0 – Digital (HDMI or USB-C) input<br>1 – Analog input<br>2 – None<br>Streamer Audio Decoder<br>0 – HDMI output<br>1 – Analog output<br>2 – Both<br>3 – None  | Set audio source/destination:<br>#KDS-AUD?1<CR>                           |
| KDS-AUD?       | Get audio source/destination.<br>+ Only available on Encoder   | #KDS-AUD?<CR>                       | ~nn@KDS-AUD<br>mode<CR><LF>                            | mode – Encoder/decoder audio mode<br>Streamer Audio Encoder<br>0 – Digital (HDMI or USB-C) input<br>1 – Analog input<br>2 – None<br>Streamer Audio Decoder<br>0 – HDMI output<br>1 – Analog output<br>2 – Both<br>3 – None  | Get audio source/destination:<br>#KDS-AUD?<CR>                            |
| KDS-GW-ETH     | Set gateway network port   | #KDS-GW-ETH<br>gw_type,netw_id<CR>  | ~nn@KDS-GW-ETH<br>gw_type,netw_id<CR><LF>              | gw_type: 0 – Control<br>netw_id – Network ID—the device network interface (if there is more than one):<br>0 – Media Port<br>1 – Service Port  | Set Dante port to eth1<br>#KDS-GW-ETH?1,1<CR>                             |
| KDS-GW-ETH?    | Get gateway network port.  | #KDS-GW-ETH?<br>gw_type<CR>         | ~nn@KDS-GW-ETH<br>gw_type,netw_id<CR><LF>              | gw_type: 0 – Control<br>netw_id – Network ID—the device network interface (if there is more than one).<br>0 – Media Port<br>1 – Service Port  | Get Dante port<br>#KDS-GW-ETH?1<CR>                                       |
| KDS-METHOD     | Set unicast / multicast . Add Set Command ; Add Multicast  | #KDS-METHOD<br>1<CR>                | ~nn@KDS-METHOD<br>method<CR><LF>                       | method – Streaming method<br>1 - Unicast<br>2 - Multicast   | Set current streaming method of encoder/decoder:<br>#KDS-METHOD?1<CR>     |
| KDS-METHOD?    | Get unicast / multicast Add Multicast.   | #KDS-METHOD?<CR>                    | ~nn@KDS-METHOD<br>method<CR><LF>                       | method – Streaming method<br>1 – Unicast<br>2 – Multicast   | Get current streaming method of encoder/decoder:<br>#KDS-METHOD?<CR>      |
| KDS-MULTICAST  | Set multicast group address and TTL value.   | #KDS-MULTICAST<br>group_ip,ttl<CR>  | ~nn@KDS-MULTICAST<br>group_ip,ttl<CR><LF>              | group-ip – Ignored<br>ttl - Time to Live of the streamed packets.   | Set multicast group address and TTL value<br>#KDS-MULTICAST 0.0.0.64<CR>  |
| KDS-MULTICAST? | Get multicast group address and TTL value.   | #KDS-MULTICAST?<CR>                 | ~nn@KDS-MULTICAST<br>group_ip,ttl<CR><LF>              | group-ip – Ignored<br>ttl - Time to Live of the streamed packets.   | Get multicast group address and TTL value<br>#KDS-MULTICAST?<CR>          |
| KDS-RATIO?     | Get aspect ratio.  | #KDS-RATIO?<CR>                     | ~nn@KDS-RATIO<br>value<CR><LF>                         | value – Streamer Decoder Aspect Ratio width:height, for example "16:9"  | Get Aspect Ratio<br>#KDS-RATIO?<CR>                                       |

|            |                                  |  |  |  |
|------------|----------------------------------|--|--|--|
| KDS-RESOL? | Get actual AV stream resolution. | #KDS-RESOL?<br>io_mode,io_index,is_native<CR><br>~nn@KDS-RESOL?<br>io_mode,io_index,is_native,resolution<CR><LF> | io_mode – Input/Output<br>0 – Input<br>1 – Output<br>io_index – Number that indicates the specific input or output port:<br>1-N (N= the total number of input or output ports)<br>is_native – Native resolution flag<br>0 – Off<br>1 – On<br>resolution – Resolution index:<br>0=No Signal<br>1=640x480p@59.94Hz/60Hz<br>2=720x480p@59.94Hz/60Hz<br>3=(Reserved)<br>4=1280x720p@59.94Hz/60Hz<br>5=1920x1080i@59.94Hz/60Hz<br>6=720(1440)x480i@59.94Hz/60Hz<br>7-15=(Reserved)<br>16=1920x1080p@59.94Hz/60Hz<br>17=720x576p@50Hz<br>18=(Reserved)<br>19=1280x720p@50Hz<br>20=1920x1080i@50Hz<br>21-30=(Reserved)<br>31=1920x1080p@50Hz<br>32=1920x1080p@23.97Hz/24Hz<br>33=1920x1080p@25Hz<br>34=1920x1080p@29.97Hz/30Hz<br>35-38=(Reserved)<br>39=1920x1080i@50Hz<br>40-64=(Reserved)<br>65=800x600p@60Hz<br>66=1024x768@60Hz<br>67=1280x768p@60Hz<br>68=1280x1024p@60Hz<br>69=1600x1200p@60Hz<br>70=1680x1050p@60Hz<br>71=1920x1200p@60Hz<br>72=3840x2160p@24Hz<br>73=3840x2160p@25Hz<br>74=3840x2160p@30Hz<br>75=3840x2160p@50Hz<br>76=3840x2160p@60Hz<br>77-97=(Reserved)<br>98=4096x2160p@24Hz<br>99=4096x2160p@25Hz<br>100=4096x2160p@30Hz<br>101=4096x2160p@50Hz<br>102=4096x2160p@60Hz<br>103-1000=(Reserved)<br>1000=640x350@85Hz<br>1001=640x400p@85Hz<br>1002=720x400p@85Hz<br>1003=(Reserved)<br>1004=640x480p@72Hz<br>1005=640x480p@75Hz<br>1006=640x480p@85Hz<br>1007=(Reserved)<br>1008=(Reserved)<br>1009=800x600p@72Hz<br>1010=800x600p@75Hz<br>1011=800x600p@85Hz<br>1012=848x480p@60Hz<br>1013=1024x768@43Hz<br>1014=(Reserved)<br>1015=1024x768p@70Hz<br>1016=1024x768p@75Hz<br>1017=1024x768p@85Hz<br>1018=1152x864p@75Hz<br>1019=(Reserved)<br>1020=(Reserved)<br>1021=1280x768p@85Hz<br>1022=1280x800p@60Hz<br>1023=1280x800p@75Hz<br>1024=1280x800p@85Hz<br>1025=1280x800p@120Hz<br>1026=1280x960p@60Hz<br>1027=1280x960p@85Hz<br>1028=(Reserved)<br>1029=1280x1024p@75Hz<br>1030=1280x1024p@85Hz<br>1031=1360x768p@60Hz<br>1032=1366x768p@60Hz<br>1033=1400x1050p@60Hz<br>1034=1400x1050p@75Hz<br>1035=1400x1050p@85Hz<br>1036=1440x900p@60Hz<br>1037=1440x900p@75Hz<br>1038=1440x900p@85Hz<br>1039=1600x900p@60Hz<br>1040=(Reserved)<br>1041=1600x1200p@65Hz<br>1042=(Reserved)<br>1043=1600x1200p@75Hz<br>1044=1600x1200p@85Hz<br>1045=(Reserved)<br>1046=1680x1050p@75Hz<br>1047=1680x1050p@85Hz<br>1048=1792x1344p@60Hz<br>1049=1792x1344p@75Hz<br>1050=1856x1392p@60Hz<br>1051=1856x1392p@75Hz<br>1052=1920x1200p@50Hz<br>1053=(Reserved)<br>1054=1920x1200p@75Hz |  |
|------------|----------------------------------|--|--|--|

| Function    | Description  | Syntax  | Response   | Parameters/Attributes  | Example   |
|-------------|--|---|--|--|---|
|             |  |   |  | 1055=1920x1200p@85Hz<br>1056=1920x1440p@60Hz<br>1057=1920x1440p@75Hz<br>1058=(Reserved)<br>1059=2048x1152p@60Hz<br>1060=2560x1600p@60Hz<br>1061=2560x1600p@75Hz<br>1062=2560x1600p@80Hz  |   |
| LDFW        | Load new firmware file.<br>NOTE: In most devices, firmware data is saved to flash memory, but the memory does not update until receiving the "UPGRADE" command and is restarted.   | Step 1: #LDFW size<CR><br>Step 2: If ready was received, send FIRMWARE_DATA | Response 1:<br>~nn@LDFW_size ready<CR><LF><br>Response 2:<br>~nn@LDFW_size ok<CR><LF>      | size – Size of firmware data that is sent<br>firmware_data – HEX or KFW file in protocol packets<br>Using the Packet Protocol<br>Send a command: LDRV, LOAD, LDEDID<br>Receive Ready or ERR###<br>If Ready:<br>a. Send a packet,<br>b. Receive OK on the last packet,<br>c. Receive OK for the command<br>Packet structure:<br>Packet ID (1, 2, 3...) (2 bytes in length)<br>Length (data length + 2 for CRC) – (2 bytes in length)<br>Data (data length -2 bytes)<br>CRC – 2 bytes<br>01 02 03 04 05<br>Packet ID Length Data CRC<br>Response: ~nnnn.ok<CR><LF> (Where NNNN is the received packet ID in ASCII hex digits.) |   |
| LOCK-EDID   | Lock last read EDID.   | #LOCK-EDID in_index,lock_mode<CR>   | ~nn@LOCK-EDID in_index,lock_mode<CR><LF>   | in_index – 1<br>lock_mode – On/Off<br>0 – Off unlocks EDID<br>1 – On locks EDID  | Lock the last read EDID from the HDMI In 1 input<br>#LOCK-EDID,1,1<CR>  |
| LOCK-EDID?  | Get EDID lock state.   | #LOCK-EDID? in_index<CR>  | ~nn@LOCK-EDID in_index,lock_mode<CR><LF>   | in_index – 1<br>lock_mode – On/Off<br>0 – Off unlocks EDID<br>1 – On locks EDID  | Get EDID lock state for Input 1<br>#LOCK-EDID?,1<CR>  |
| LOCK-FP     | Lock the front panel.  | #LOCK-FP lock/unlock<CR>  | ~nn@LOCK-FP lock/unlock<CR><LF>  | Lock/Unlock – On/Off<br>0 – (Off) Unlocks EDID<br>1 – (On) Locks EDID  | Unlock front panel:<br>#LOCK-FP,0<CR>   |
| LOCK-FP?    | Get the front panel lock state.  | #LOCK-FP?<CR>   | ~nn@LOCK-FP lock/unlock<CR><LF>  | Lock/Unlock – On/Off<br>Off – Unlocks EDID<br>On – Locks EDID  | Get the front panel lock state:<br>#LOCK-FP?<CR>  |
| LOG-ACTION  | Reset events log.  | #LOG-ACTION action,period<CR>   | ~nn@LOG-ACTION action,period<CR><LF>   | action -<br>1 - Start, start logging<br>2 - Pause, pause logging but keep log content<br>3 - Resume, resume the logging<br>4 - Reset, clear all current logs, keep logging period - Ignored  | Reset events log :<br>#LOG-ACTION,4,1<CR>   |
| LOG-ACTION? | Get log state.   | #LOG-ACTION?<CR>  | ~nn@LOG-ACTION action,period<CR><LF>   | action - One of<br>1 - Start, start logging<br>2 - Pause, pause logging but keep log content<br>3 - Resume, resume the logging<br>4 - Reset, clear all current logs, keep logging period - Ignored   | Get log state:<br>#LOG-ACTION?<CR>  |
| LOG-TAIL?   | Get the last "n" lines of message logs.<br>NOTE: Used for advanced troubleshooting. Helps find error root causes and gets details not displayed in the error code number.  | #LOG-TAIL? line_num<CR>   | Get:<br>~nn@LOG-TAILnn<CR><LF><br>Line content #1<CR><LF><br>Line content #2<CR><LF>Etc... | line_num – Optional, default line_num is 10  | Get the last "2" lines of message logs:<br>#LOG-TAIL?,2<CR>   |
| LOGIN       | Set protocol permission.<br>NOTE: The permission system works only if security is enabled with the "SECUR" command.<br>LOGIN allows the user to run commands with an End User or Administrator permission level.<br>When the permission system is enabled, LOGIN enables running commands with the User or Administrator permission level.<br>When set, login must be performed upon each connection<br>It is not mandatory to enable the permission system in order to use the device<br>In each device, some connections allow logging in to different levels.<br>Some do not work with security at all.<br>Connection may logout after timeout. | #LOGIN login_level,password<CR>   | ~nn@LOGIN login_level,password ok<CR><LF>  | login_level – Level of permissions required (only 'admin' is acceptable)<br>password – Predefined password (by PASS command). Default password is 'admin'.   | Set the protocol permission level to Admin (when the password defined in the PASS command is 33333):<br>#LOGIN<br>admin,33333<CR> |
| LOGIN?      | Get current protocol permission level.NOTE: The permission system works only if security is enabled with the "SECUR" command.<br>For devices that support security, LOGIN allows the user to run commands with an End User or Administrator permission level.<br>In each device, some connections allow logging in to different levels.<br>Some do not work with security at all.<br>Connection may logout after timeout.  | #LOGIN?<CR>   | ~nn@LOGIN login_level<CR><LF>  | login_level – Level of permissions required (only 'admin' is acceptable).  | Get current protocol permission level:<br>#LOGIN?<CR>   |

| Function               | Description  | Syntax  | Response   | Parameters/Attributes   | Example  |
|------------------------|--|---|--|---|--|
| <b>LOGOUT</b>          | Cancel current permission level.NOTE: Logs out from End User or Administrator permission levels to Not Secure.   | #LOGOUT<CR>                                     | ~nn@LOGOUTok<CR><LF>   |   | #LOGOUT<CR>  |
| <b>LOGOUT-TIMEOUT</b>  | Set inactivity auto-logout time.   | # LOGOUT-TIMEOUT time<CR>                       | ~nn@ LOGOUT-TIMEOUT time<CR><LF>   | time – minutes of inactivity that causes automatic logout.  | Set Inactivity auto-logout time to 10<br>#LOGOUT-TIMEOUT 10<CR>  |
| <b>LOGOUT-TIMEOUT?</b> | Get inactivity auto-logout time.   | #LOGOUT-TIMEOUT?<CR>                            | ~nn@LOGOUT-TIMEOUT time<CR><LF>  | time – minutes of inactivity that causes automatic logout.  | Get Inactivity auto-logout time<br>#LOGOUT-TIMEOUT?<CR>  |
| <b>MODEL?</b>          | Get device model.<br>NOTE: This command identifies equipment connected to WP-SW2-EN7 and notifies of identity changes to the connected equipment. The Matrix saves this data in memory to answer REMOTE-INFO requests.   | #MODEL?<CR>                                     | ~nn@MODEL model_name<CR><LF>   | model_name – String of up to 24 printable ASCII chars.  | Get the device model:<br>#MODEL?<CR>   |
| <b>NAME</b>            | Set machine name.<br>NOTE: The machine name is not the same as the model name. The machine name is used to identify a specific machine or a network in use (with DNS feature on).  | #NAME interface_id,host_name<CR>                | ~nn@NAME interface_id,host_name<CR><LF>  | interface_id – always 0<br>host_name – String of up to 24 alpha-numeric chars (can include hyphen, underscore, not at the beginning or end).  | Set the machine DNS name of the device to room-442:<br>#NAME_0,room-442<CR>  |
| <b>NAME?</b>           | Get machine or DANTE (DNS) name.<br>NOTE: The machine name is not the same as the model name. The machine name is used to identify a specific machine or a network in use (with DNS feature on).   | #NAME? interface_id<CR>                         | ~nn@NAME interface_id,host_name<CR><LF>  | interface_id – always 0<br>host_name – String of up to 24 alpha-numeric chars (can include hyphen, underscore, not at the beginning or end).  | Get the DNS name of the device:<br>#NAME?_0<CR>  |
| <b>NAME-RST</b>        | Reset machine (DNS) name to factory default.NOTE: Factory default of machine (DNS) name is "KRAMER_" + 4 last digits of device serial number.  | #NAME-RST<CR>                                   | ~nn@NAME-RST OK<CR><LF>  |   | Reset the machine name (S/N last digits are 0102):<br>#NAME-RST<CR>  |
| <b>NET-CONFIG</b>      | Set a network configuration.<br><br>NOTE: For Backward compatibility, the id parameter can be omitted. In this case, the Network ID, by default, is 0, which is the Ethernet control port.<br><br>NOTE: If the gateway address is not compliant to the subnet mask used for the host IP, the command will return an error. Subnet and gateway compliance specified by RFC950.<br>NOTE: This set the device to DHCP OFF automatically.  | #NET-CONFIG netw_id,net_ip,net_mask,gateway<CR> | ~nn@NET-CONFIG netw_id,net_ip,net_mask,gateway<CR><LF>                         | netw_id – Network ID-ID of the Ethernet port:<br>0 – Media Port<br>1 – Service Port<br>net_ip – Network IP<br>net_mask – Network mask<br>gateway – Network gateway  | Set the device network parameters to IP address 192.168.113.10, net mask 255.255.0.0, and gateway 192.168.0.1:<br>#NET-CONFIG 0,192.168.113.10,255.255.0.0,192.168.0.1<CR>   |
| <b>NET-CONFIG?</b>     | Get a network configuration.   | #NET-CONFIG? netw_id<CR>                        | ~nn@NET-CONFIG netw_id,net_ip,net_mask,gateway<CR><LF>                         | netw_id – Network ID-ID of the Ethernet port:<br>0 – Media Port<br>1 – Service Port<br>net_ip – Network IP<br>net_mask – Network mask<br>gateway – Network gateway  | Get network configuration:<br>#NET-CONFIG?_0<CR>   |
| <b>NET-DHCP</b>        | Set DHCP mode.NOTE: Only 1 is relevant for the mode value. To disable DHCP, the user must configure a static IP address for the device.<br>Connecting Ethernet to devices with DHCP may take more time in some networks.<br>To connect with a randomly assigned IP by DHCP, specify the device DNS name (if available) using the NAME command. You can also get an assigned IP by direct connection to USB or RS-232 protocol port, if available.<br>For proper settings consult your network administrator.<br>NOTE: For Backward compatibility, the id parameter can be omitted. In this case, the Network ID, by default, is 0, which is the Ethernet control port. | #NET-DHCP netw_id,dhcp_state<CR>                | ~nn@NET-DHCP netw_id,dhcp_state<CR><LF>  | netw_id – Network ID-the device network interface (if there are more than one). Counting is 0 based, meaning the control port is '0', additional ports are 1,2,3,...<br>dhcp_state –<br>1 – Try to use DHCP. (If unavailable, use the IP address set by the factory or the net-ip command). | Enable DHCP mode for port 1, if available:<br>#NET-DHCP_1,1<CR>  |
| <b>NET-DHCP?</b>       | Get DHCP mode<br>NOTE: For Backward compatibility, the id parameter can be omitted. In this case, the Network ID, by default, is 0, which is the Ethernet control port.  | #NET-DHCP? netw_id<CR>                          | ~nn@NET-DHCP netw_id,dhcp_state<CR><LF>  | netw_id – Network ID-the device network interface (if there are more than one). Counting is 0 based, meaning the control port is '0', additional ports are 1,2,3,...<br>dhcp_state –<br>1 – Try to use DHCP. (If unavailable, use the IP address set by the factory or the net-ip command). | Get DHCP mode for port 1, if available:<br>#NET-DHCP?_1<CR>  |
| <b>NET-MAC?</b>        | Get MAC address.   | #NET-MAC?<CR>                                   | ~nn@NET-MAC mac_address<CR><LF>  | mac_address – Unique MAC address. Format: XX-XX-XX-XX-XX-XX where X is hex digit  | #NET-MAC?<CR>  |
| <b>NET-STAT?</b>       | Get net connection list of this machine.<br>NOTE: The response is returned in one line and terminated with<CR><LF>.<br>The response format lists signal IDs separated by commas.<br>This is an Extended Protocol 3000 command.   | #NET-STAT?<CR>                                  | ~nn@NET-STAT [<port_type>:<port_index>,<client_ip>:<client_port>],...,<CR><LF> | port_type – TCP/UDP<br>0 – TCP<br>1 – UDP<br>port_index - Device port<br>client_ip – Dot-separated representation of the IP address<br>client_port - Client port state – listen or established  | Get net connection list of this machine:<br>#NET-STATE?<CR><br>~01@NETSTAT [(TCP:80,0.0.0.0:0),LISTEN],[(TCP:5000,0.0.0.0:0),LISTEN],[(TCP:80,192.168.114.3:52400),ESTABLISHED],[(TCP:5000,192.168.1.100:51647),ESTABLISHED]<CR><LF> |

| Function        | Description  | Syntax   | Response  | Parameters/Attributes   | Example   |
|-----------------|--|--|---|---|---|
| NET-IP?         | Get a network IP address.<br>This is an UDP protocol only.   | #NET-IP?<CR>   | ~nn@NET-IP<br>net_ip<CR><LF>  | net_ip – Network IP   | Get network ip address:<br>#NET-IP?<CR>   |
| PASS            | Set password for login level.<br>The default password is "admin".  | #PASS<br>login_level,password<CR>  | ~nn@PASS<br>login_level,Password<CR><LF>  | login_level – Level of login to set (admin support only).<br><br>password – Password for the login_level, 8 to 24 characters (letters, numbers, and symbols without spaces or commas), at least including one number, one symbols without spaces or commas, one uppercase letter and one lowercase letter.  | Set the password for the admin protocol permission level to 33333:<br>#PASS admin,33333<CR> |
| PASS?           | Get password for login level.<br>The default password is "admin".  | #PASS?<br>login_level<CR>  | ~nn@PASS<br>login_level,password<CR><LF>  | login_level – Level of login to set (End User or Administrator).<br><br>password – Password for the login_level.  | Get the password for the admin protocol permission level:<br>#PASS? admin<CR>               |
| PORT-DIRECTION  | Set port direction as input or output.   | #PORT-DIRECTION<br><direction_type>.<port_format>.<port_index>.<signal_type>.<direction><CR> | ~nn@PORT-DIRECTION<br><direction_type>.<port_format>.<port_index>.<signal_type>.<direction><CR><LF> | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional<br><port_format> – Type of signal on the port:<br>ANALOG_AUDIO<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br><direction> – Direction of the port:<br>IN – Input<br>OUT – Output  | Set audio analog port direction as input<br>#PORT-DIRECTION<br>both.analog.1.audio,IN<CR>   |
| PORT-DIRECTION? | Get port direction.  | #PORT-DIRECTION?<br><direction_type>.<port_format>.<port_index>.<signal_type><CR>            | ~nn@PORT-DIRECTION<br><direction_type>.<port_format>.<port_index>.<signal_type>.<direction><CR><LF> | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional<br><port_format> – Type of signal on the port:<br>ANALOG_AUDIO<br>IR<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br>IR<br><direction> – Direction of the port:<br>IN – Input<br>OUT – Output  | Get audio analog port direction<br>#PORT-DIRECTION?<br>both.analog.1.audio<CR>              |
| PORTS-LIST?     | Get the port list of this machine.<br>NOTE: The response is returned in one line and terminated with<CR><LF>.<br>The response format lists port IDs separated by commas.<br>This is an Extended Protocol 3000 command.         | #PORTS-LIST?<CR>   | ~nn@PORTS-LIST<br>[<direction_type>.<port_format>.<port_index>,...]<CR><LF>                         | The following attributes comprise the port ID:<br><direction_type> – Direction of the port:<br>IN<br>OUT<br>BOTH<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br>RS-232<br>USB_C<br><port_index> – The port number as printed on the front or rear panel  | Get the ports list:<br>#PORTS-LIST?<CR>   |
| RESET           | Reset device<br>NOTE: To avoid locking the port due to a USB bug in Windows, disconnect USB connections immediately after running this command. If the port was locked, disconnect and reconnect the cable to reopen the port. | #RESET<CR>   | ~nn@RESET<br>ok<CR><LF>   |   | Reset the device:<br>#RESET<CR>   |
| ROLLBACK        | Rollback firmware to standby version.  | #ROLLBACK<CR>  | ~nn@ROLLBACK<br>ok<CR><LF>  |   | Perform firmware rollback:<br># ROLLBACK<CR>  |
| SECUR           | Start/stop security.<br>NOTE: The permission system works only if security is enabled with the "SECUR" command.  | #SECUR<CR>   | ~nn@SECUR<br>security_state<CR><LF>   | security_state – Security state<br>0 – OFF (disables security)<br>1 – ON (enables security)   | Enable the permission system:<br>#SECUR,0<CR>   |
| SECUR?          | Get security state.  | #SECUR?<CR>  | ~nn@SECUR<br>security_state<CR><LF>   | security_state – Security state<br>0 – OFF (disables security)<br>1 – ON (enables security)   | Get security state:<br>#SECUR?<CR>  |
| SIGNALS-LIST?   | Get signal ID list of this machine.<br>NOTE: The response is returned in one line and terminated with<CR><LF>.<br>The response format lists signal IDs separated by commas.<br>This is an Extended Protocol 3000 command.      | #SIGNALS-LIST?<CR><LF>   | ~nn@SIGNALS-LIST<br>[<direction_type>.<port_format>.<port_label>.<signal_type>.<index>,<CR><LF>     | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional (e.g. for RS-232)<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br>RS-232<br>USB_C<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO<br>RS232<br>USB<br><index> – Indicates a specific channel number when there are multiple channels of the same type | Get signal ID list:<br>#SIGNALS-LIST?<CR>   |

| Function         | Description  | Syntax   | Response  | Parameters/Attributes   | Example  |
|------------------|--|--|---|---|--|
| SN?              | Get device serial number.  | #SN?<br><CR>   | ~nn@SN_serial_num<br><CR><LF>   | serial_num – 14 decimal digits, factory assigned  | Get the device serial number:<br>#SN?<CR>  |
| STANDBY-VERSION? | Get standby firmware version.  | #STANDBY-VERSION?<CR>  | ~nn@STANDBY-VERSION?<br>standby_version<CR><LF>   | standby_version – XX.XX.XXXX where the digit groups are: major.minor.build version  | Get standby version<br>#STANDBY-VERSION?<CR>   |
| TIME             | Set device time and date..<br>NOTE: The year must be 4 digits.<br>The device does not validate the day of week from the date.<br>Time format - 24 hours.<br>Date format - Day, Month, Year.  | #TIME<br>day_of_week,date,data<CR>   | ~nn@TIME<br>day_of_week,date,data<CR><LF>   | day_of_week – One of {SUN,MON,TUE,WED,THU,FRI,SAT}<br>date – Format: DD-MM-YYYY where<br>YYYY = Year<br>MM = Month<br>DD = Day<br>data – Format: hh:mm:ss where<br>hh = hours<br>mm = minutes<br>ss = seconds   | Set device time and date to December 5, 2018 at 2:30pm:<br>#TIME mon_05-12-2018,14:30:00<CR>                 |
| TIME?            | Get device time and date..<br>NOTE: The year must be 4 digits.<br>The device does not validate the day of week from the date.<br>Time format - 24 hours.<br>Date format - Day, Month, Year.  | #TIME?<CR>   | ~nn@TIME<br>day_of_week,date,data<CR><LF>   | day_of_week – One of {SUN,MON,TUE,WED,THU,FRI,SAT}<br>date – Format: YYYY/MM/DD where<br>YYYY = Year<br>MM = Month<br>DD = Day<br>data – Format: hh:mm:ss where<br>hh = hours<br>mm = minutes<br>ss = seconds   | Get device time and date:<br>#TIME?<CR>  |
| TIME-LOC         | Set local time offset from UTC/GMT.<br>NOTE: If the time server is configured, device time calculates by adding UTC_offset to UTC time (that it got from the time server) + 1 hour if daylight savings time is in effect.<br>TIME command sets the device time without considering these settings.<br>NOTE: Daylight saving time not supported.<br>NOTE: Restart unit to take effect.            | #TIME-LOC<br>utc_off,dst_state<CR>   | ~nn@TIME-LOC<br>utc_off,dst_state<CR><LF>   | utc_off – Offset of device time from UTC/GMT (without daylight time correction), format HH:MM (':MM' is optional)<br>HH – Hours, -12 to 13<br>MM – Minutes, 00 to 59<br>dst_state – Daylight saving time state, 0 = no daylight saving time.  | Set local time offset to 3 with no daylight-saving time:<br>#TIME-LOC 3,0<CR><br>Or<br>#TIME-LOC 03:00,0<CR> |
| TIME-LOC?        | Get local time offset from UTC/GMT.<br>NOTE: If the time server is configured, device time is calculated by adding UTC_offset to UTC time (taken from the time server) + 1 hour if daylight savings time is in effect.<br>TIME command sets the device time without considering these settings.<br>NOTE: Daylight saving time not supported.   | #TIME-LOC?<CR>   | ~nn@TIME-LOC<br>utc_off,dst_state<CR><LF>   | utc_off – Offset of device time from UTC/GMT (without daylight time correction), format HH:MM<br>HH – Hours, -12 ~ 13<br>MM – Minutes, 00 ~ 59<br>dst_state – Daylight saving time state, 0 = no daylight saving time   | Get local time offset from UTC/GMT:<br>#TIME-LOC?<CR>  |
| TIME-SRV         | Set time server.<br>NOTE: This command is needed for setting UDP timeout for the current client list.  | #TIME-SRV<br>mode,time_server_ip,sync_hour<CR>                                     | ~nn@TIME-SRV<br>mode,time_server_ip,sync_hour,server_status<CR><LF>                       | mode – On/Off where 0 = Off, 1 = On<br>time_server_ip – Time server IP address<br>sync_hour – Hour in day for time server sync<br>server_status – On/Off  | Set time server with IP address of 128.138.140.44 to ON:<br>#TIME-SRV 1,128.138.140.44,0,1<CR>               |
| TIME-SRV?        | Get time server.<br>NOTE: This command is needed for setting UDP timeout for the current client list.  | #TIME-SRV?<CR>   | ~nn@TIME-SRV<br>mode,time_server_ip,sync_hour,server_status<CR><LF>                       | mode – On/Off where 0 = Off, 1 = On<br>time_server_ip – Time server IP address<br>sync_hour – Hour in day for time server sync<br>server_status – On/Off  | Get time server:<br>#TIME-SRV?<CR>   |
| UART             | Set com port configuration.<br>NOTE: In the FC-2x the serial port is selectable to RS-232 or RS-485 (usually serial port 1).<br>If Serial is configured when RS-485 is selected, the RS-485 UART port automatically changes.<br>The command is backward compatible, meaning that if the extra parameters do not exist, FW goes to.<br>RS-232.<br>Stop_bits 1.5 is only relevant for 5 data_bits. | #UART<br>com_id,baud_rate,data_bits,parity,stop_bits_mode,serial_type,485_term<CR> | ~nn@UART<br>com_id,baud_rate,data_bits,parity,stop_bits_mode,serial_type,485_term<CR><LF> | com_id – 1 to n (machine dependent)<br>baud_rate – 9600 - 115200<br>data_bits – 5-8<br>parity – Parity Type<br>0 – No<br>1 – Odd<br>2 – Even<br>stop_bits_mode – 1/1.5/2<br>serial_type – 232/485<br>0 – 232<br>1 – 485<br>485_term – 485 termination state<br>0 – disable<br>1 – enable<br>(optional - only used when serial_type is 485)                          | Set baud rate to 9600, 8 data bits, parity to none and stop bit to 1:<br>#UART 9600,8,node,1<CR>             |
| UART?            | Get com port configuration.<br>NOTE: In the FC-2x the serial port is selectable to RS-232 or RS-485 (usually serial port 1).<br>If Serial is configured when RS-485 is selected, the RS-485 UART port automatically changes.<br>The command is backward compatible, meaning that if the extra parameters do not exist, FW goes to.<br>RS-232.<br>Stop_bits 1.5 is only relevant for 5 data_bits. | #UART?<br>com_id<CR>   | ~nn@UART,com_id,baud_rate,data_bits,parity,stop_bits_mode,serial_type,485_term<CR><LF>    | com_id – 1 to n (machine dependent)<br>baud_rate – 9600 - 115200<br>data_bits – 5-8<br>parity – Parity Type<br>0 – No<br>1 – Odd<br>2 – Even<br>3 – Mark<br>4 – Space<br>stop_bits_mode – 1/1.5/2<br>serial_type – 232/485<br>0 – 232<br>1 – 485<br>485_term – 485 termination state<br>0 – disable<br>1 – enable<br>(optional - only used when serial_type is 485) | Set baud rate to 9600, 8 data bits, parity to none and stop bit to 1:<br>#UART 1,9600,8,node,1<CR>           |
| UPG-TIME?        | Get firmware version last upgrade date/time Add New Command for KDS-7  | #UPG-TIME?<br><CR>   | ~nn@UPG-TIME<br>date,data<CR><LF>   | date – Format: DD-MM-YYYY.<br>data – Format: hh:mm:ss where   | Get last upgrade date/time<br>#UPG-TIME?<CR>   |

| Function            | Description   | Syntax   | Response   | Parameters/Attributes   | Example  |
|---------------------|---|--|--|---|--|
| <b>UPGRADE</b>      | Perform firmware upgrade.<br>NOTE: Not necessary for some devices.<br>Firmware usually uploads to a device via a command like LDFW. Reset the device to complete the process. | #UPGRADE<CR>   | ~nn@UPGRADE<br>ok<CR><LF>  |   | Perform firmware upgrade:<br>#UPGRADE<CR>  |
| <b>VERSION?</b>     | Get firmware version number.  | #VERSION?<CR>  | ~nn@VERSION<br>firmware_version<CR><LF>  | firmware_version – XX.XX.XXXX where the digit groups are: major.minor.build version   | Get the device firmware version number:<br>#VERSION?<CR>   |
| <b>X-AUD-DESC?</b>  | Get audio signal info<br>NOTE:<br>+ This is an Extended Protocol 3000 command.<br>+ On KDS7 on support activated port   | #X-AUD-DESC?<br><direction_type>.<port_format>.<port_index><CR>  | ~nn@X-AUD-DESC?<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>.<ch_tot>.<samp_rate>.<aud_format><CR><LF> | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional (e.g. for RS-232)<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple ch_tot – Total number of channels<br><samp_rate> – Sample rate<br><aud_format> – Audio Format:<br>LPCM – Linear Pulse Code Modulation audio<br>Non-LPCM – Non Linear Pulse Code Modulation audio, like Dolby Digital, DTS, etc.<br>HBR – High Bitrate Audio, like Dolby TrueHD, DTS HD Master Audio | Get the audio signal info:<br>#X-AUD-DESC?<br>out.hdmi.1<CR>                                       |
| <b>X-AUD-LVL</b>    | Set audio level of a specific signal.<br>NOTE: This is an Extended Protocol 3000 command.   | #X-AUD-LVL<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>.<audio_level><CR>        | ~nn@X-AUD-LVL<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>.<audio_level><CR><LF>                       | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>OUT – Output<br><port_format> – Type of signal on the port:<br>ANALOG_AUDIO<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type.<br><audio_level> – Audio level in dB (range between -60 to +30) depending of the ability of the product.  | Set the audio level of a specific signal to 10:<br>#X-AUD-LVL<br>in.analog_audio.1.audio.1, 10<CR> |
| <b>X-AUD-LVL?</b>   | Get audio level of a specific signal.<br>NOTE: This is an Extended Protocol 3000 command.   | #X-AUD-LVL?<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index><CR>                     | ~nn@X-AUD-LVL<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>.<audio_level><CR><LF>                       | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>OUT – Output<br><port_format> – Type of signal on the port:<br>ANALOG_AUDIO<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type.<br><audio_level> – Audio level in dB (range between -60 to +30) depending of the ability of the product.  | Get the audio level of a specific signal:<br>#X-AUD-LVL?<br>out.analog_audio.1.audio.1<CR>         |
| <b>X-AV-SW-MODE</b> | Set auto-switch mode per output.<br>NOTE: This is an Extended Protocol 3000 command.  | #X-AV-SW-MODE<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>.<connection_mode><CR> | ~nn@X-AV-SW-MODE<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>.<connection_mode><CR><LF>                | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional (e.g. for RS-232)<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel.<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type.<br><connection_mode> – Connection mode<br>0 – manual<br>1 – priority<br>2 – last connected   | Set auto switch mode for HDMI OUT 1 (last connected):<br>#X-AV-SW-MODE<br>out.hdmi.1.video.1,2<CR> |

| Function      | Description   | Syntax   | Response  | Parameters/Attributes   | Example  |
|---------------|---|--|---|---|--|
| X-AV-SW-MODE? | Get auto-switch mode.<br>NOTE: This is an Extended Protocol 3000 command.   | #X-AV-SW-MODE?<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index><CR>  | ~nn@X-AV-SW-MODE?<br>E<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>,<connection_mode><CR><LF>   | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional (e.g. for RS-232)<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel.<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type.<br><connection_mode> – Connection mode<br>0 – manual<br>1 – priority<br>2 – last connected | Get auto switch mode for HDMI OUT 1:<br>#X-AV-SW-MODE?<br>out.hDMI.1.video.1<CR>   |
| X-MUTE        | Set mute ON/OFF on a specific signal.   | #X-MUTE<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>,<state><CR><LF>   | ~nn@ X-MUTE<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>,<state><CR><LF>  | <direction_type> – Direction of the port:<br>OUT – Output<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br>ALL – All audio output<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type<br><state> – OFF/ON (not case sensitive)   | Mute the audio on HDMI OUT 1:<br>#X-MUTE<br>out.hDMI.1.audio.1,ON<CR><br>Mute the audio on ALL OUT:<br>#X-MUTE<br>out.all.1.audio.1,ON<CR>   |
| X-MUTE?       | Get mute ON/OFF on a specific signal.   | #X-MUTE?<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index><CR>  | ~nn@ X-MUTE<br><direction_type>.<port_format>.<port_index>.<signal_type>.<index>,<state><CR><LF>  | <direction_type> – Direction of the port:<br>OUT – Output<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br>ALL – All audio output<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type<br><state> – OFF/ON (not case sensitive)   | Get the mute state of audio on HDMI OUT 1:<br>#X-MUTE?<br>out.hDMI.1.audio.1<CR>   |
| X-PRIORITY    | Set priority order.   | #X-PRIORITY<br><direction_type>.<port_format>.<port_index>.<signal_type>,[<direction_type>.<port_format>.<port_index>.<signal_type>,...]<CR>           | ~nn@X-PRIORITY<br><direction_type>.<port_format>.<port_index>.<signal_type>,[<direction_type>.<port_format>.<port_index>.<signal_type>,...]<CR><LF>           | <direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br><port_format> – Type of signal on the port:<br>HDMI<br>USB_C<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO   | Set video priority is 3,2,1<br>#X-PRIORITY<br>out.hDMI.1.video,[in.usb_c.3.video,in.hDMI.2.video,in.hDMI.1.video]<CR>  |
| X-PRIORITY?   | Get priority order.   | #X-PRIORITY?<br><direction_type>.<port_format>.<port_index>.<signal_type><CR>  | ~nn@X-PRIORITY<br><direction_type>.<port_format>.<port_index>.<signal_type>,[<direction_type>.<port_format>.<port_index>.<signal_type>,...]<CR><LF>           | <direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br><port_format> – Type of signal on the port:<br>HDMI<br>USB_C<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO   | Get video priority<br>#X-PRIORITY?<br>out.hDMI.1.video<CR>   |
| X-ROUTE       | Send routing command.<br>NOTE: It is recommended to use the command # SIGNALS-LIST to get the list of all signal IDs available in the system and which can be used in this command.<br>Video 1 is the default port in this command and is implied even if not written:<br>#X-ROUTE<br>out.hDMI.1,in.video.1<CR><br>is interpreted as:<br>#X-ROUTE<br>out.hDMI.1.video.1,in.hDMI.1.video.1<CR><br>This is an Extended Protocol 3000 command.<br>Brackets '[' and ']' are reserved Protocol 3000 characters that define a list of parameters as in [a,b,c,d]. | #X-ROUTE<br>[<direction_type1>,<port_type1>,<port_index1>,<signal_type1>,...],<direction_type2>,<port_type2>,<port_index2>,<signal_type2>,<index2><CR> | ~nn@X-ROUTE<br>[<direction_type1>,<port_type1>,<port_index1>,<signal_type1>,...],<direction_type2>,<port_type2>,<port_index2>,<signal_type2>,<index2><CR><LF> | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional (e.g. for RS-232)<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type.   | Route HDMI IN 2 to HDMI OUT 1:<br>#X-ROUTE<br>out.hDMI.1.video.1,in.hDMI.2.video.1<CR><br>Route of audio<br>hDMI.1.audio.1 signal to HDMI output, analog:<br>#X-ROUTE<br>[out.hDMI.1.audio.1,out.analog_audio.1.audio.1],in.hDMI.1.audio.1<CR> |

| Function | Description  | Syntax  | Response  | Parameters/Attributes   | Example  |
|----------|--|---|---|---|--|
| X-ROUTE? | Get routing status. NOTE: It is recommended to use the command #SIGNALS-LIST to get the list of all signal IDs available in the system and which can be used in this command.<br>VIDEO,1 are the default <signal_type> and <index> in this command and are implied even if not written:<br>#X-ROUTE<br>out.hdmi.1,in.video.1<CR><br>is interpreted as:<br>#X-ROUTE<br>out.hdmi.1.video.1,in.hdmi.1.video.1<br><CR><br>This is an Extended Protocol 3000 command. | #X-ROUTE?<br><direction_type1>,<port_type1>,<port_index1>,<signal_type1>,<index1><CR> | ~nn@X-ROUTE<br>~nn@X-ROUTE<br><direction_type1>,<port_type1>,<port_index1>,<signal_type1>,<index1>,<direction_type2>,<port_type2>,<port_index2>,<signal_type2>,<index2><CR><LF> | The following attributes comprise the signal ID:<br><direction_type> – Direction of the port:<br>IN – Input<br>OUT – Output<br>BOTH – Bi-directional (e.g. for RS-232)<br><port_format> – Type of signal on the port:<br>HDMI<br>ANALOG_AUDIO<br>STREAM<br><port_index> – The port number as printed on the front or rear panel<br><signal_type> – Signal ID attribute:<br>VIDEO<br>AUDIO<br><index> – Indicates a specific channel number when there are multiple channels of the same type. | Get the routing status:<br>#X-ROUTE?<br>out.hdmi.1.video.1<CR> |

## Result and Error Codes

### Syntax

In case of an error, the device responds with an error message. The error message syntax:

- **~NN@ERR XXX<CR><LF>** – when general error, no specific command
- **~NN@CMD ERR XXX<CR><LF>** – for specific command
- **NN** – machine number of device, default = 01
- **XXX** – error code

## Error Codes

| Error Name                 | Error Code | Description                                   |
|----------------------------|------------|---|
| P3K_NO_ERROR               | 0          | No error                                      |
| ERR_PROTOCOL_SYNTAX        | 1          | Protocol syntax                               |
| ERR_COMMAND_NOT_AVAILABLE  | 2          | Command not available                         |
| ERR_PARAMETER_OUT_OF_RANGE | 3          | Parameter out of range                        |
| ERR_UNAUTHORIZED_ACCESS    | 4          | Unauthorized access                           |
| ERR_INTERNAL_FW_ERROR      | 5          | Internal FW error                             |
| ERR_BUSY                   | 6          | Protocol busy                                 |
| ERR_WRONG_CRC              | 7          | Wrong CRC                                     |
| ERR_TIMEDOUT               | 8          | Timeout                                       |
| ERR_RESERVED               | 9          | (Reserved)                                    |
| ERR_FW_NOT_ENOUGH_SPACE    | 10         | Not enough space for data (firmware, FPGA...) |
| ERR_FS_NOT_ENOUGH_SPACE    | 11         | Not enough space – file system                |
| ERR_FS_FILE_NOT_EXISTS     | 12         | File does not exist                           |
| ERR_FS_FILE_CANT_CREATED   | 13         | File can't be created                         |
| ERR_FS_FILE_CANT_OPEN      | 14         | File can't open                               |
| ERR_FEATURE_NOT_SUPPORTED  | 15         | Feature is not supported                      |
| ERR_RESERVED_2             | 16         | (Reserved)                                    |
| ERR_RESERVED_3             | 17         | (Reserved)                                    |
| ERR_RESERVED_4             | 18         | (Reserved)                                    |
| ERR_RESERVED_5             | 19         | (Reserved)                                    |
| ERR_RESERVED_6             | 20         | (Reserved)                                    |
| ERR_PACKET_CRC             | 21         | Packet CRC error                              |
| ERR_PACKET_MISSED          | 22         | Packet number isn't expected (missing packet) |
| ERR_PACKET_SIZE            | 23         | Packet size is wrong                          |
| ERR_RESERVED_7             | 24         | (Reserved)                                    |
| ERR_RESERVED_8             | 25         | (Reserved)                                    |
| ERR_RESERVED_9             | 26         | (Reserved)                                    |
| ERR_RESERVED_10            | 27         | (Reserved)                                    |
| ERR_RESERVED_11            | 28         | (Reserved)                                    |
| ERR_RESERVED_12            | 29         | (Reserved)                                    |
| ERR_EDID_CORRUPTED         | 30         | EDID corrupted                                |
| ERR_NON_LISTED             | 31         | Device specific errors                        |
| ERR_SAME_CRC               | 32         | File has the same CRC – not changed           |
| ERR_WRONG_MODE             | 33         | Wrong operation mode                          |
| ERR_NOT_CONFIGURED         | 34         | Device/chip was not initialized               |



# kramer



**HDMI™**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



P/N:



Rev:



## SAFETY WARNING

Disconnect the unit from the power supply before opening and servicing

For the latest information on our products and a list of Kramer distributors, visit our website where updates to this user manual may be found.

We welcome your questions, comments, and feedback.

The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. All brand names, product names, and trademarks are the property of their respective owners.