



**NETWORK
TECHNOLOGIES
INCORPORATED**

1275 Danner Dr Tel:330-562-7070
Aurora, OH 44202 Fax:330-562-1999
www.networktechinc.com

VEEMUX[®] Series

SM-16X16-HD4K

**HDMI 4K Video Matrix Switch
Installation and Operation Manual**



Front and Rear View of SM-16X16-HD4K



Rear View of SM-16X16-HD4K with cable tray installed

TRADEMARK

VEEMUX is a registered trademark of Network Technologies Inc in the U.S. and other countries.

COPYRIGHT

Copyright © 2010, 2019 by Network Technologies Inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Network Technologies Inc, 1275 Danner Drive, Aurora, Ohio 44202.

CHANGES

The material in this guide is for information only and is subject to change without notice. Network Technologies Inc reserves the right to make changes in the product design without reservation and without notification to its users.

FIRMWARE VERSION

Current Firmware version 1.0

TABLE OF CONTENTS

Introduction	1
Supported Web Browsers.....	1
Materials	2
Features and Functions	3
Installation	4
To Mount to a Rack	4
Make All Connections.....	5
Operating the VEEMUX	8
Front Panel LCD with Keypad Control.....	8
LCD Menus.....	9
Save and Load (Recall) Config.....	10
RS232 Control	11
Baud Rate.....	11
Command Protocol.....	12
Autostatus.....	13
NTI Switch Control Program For Windows 9X, NT, 2000, XP, Vista, 7, 8 and 10	13
SerTest- RS232 Interface Test Program	14
Main Options.....	14
Matrix Operations.....	14
Ethernet Operations.....	14
Setup Options	15
Ethernet Control	16
Telnet Interface-Port 2000	16
Telnet Interface-Port 2005.....	18
Command Summary.....	18
Command Detail	19
RU-Read Unit Size	19
RO-Read Connection for Output Port	19
CS- Connect Output Port to Input Port.....	19
CA- Connect All Output Ports to Input Port.....	19
SS_01- Enable Auto Status Mode.....	20
SS_00- Disable Auto Status Mode.....	20
SX- Examine connections	20
Terminate telnet session	21
Web Interface	22
Enter the Password	22
Main Menu	23
Video Switch Page.....	24
Administration	25
System Configuration	25
Network Configuration.....	26
Video Input Names.....	27
Video Output Names	28
Scanning Sequences.....	29
User Config.....	31
DDC Options.....	32
DDC Mix	34
Update Firmware	35
Standby Mode	36
Logout.....	36
Support	37
Reboot	37
Device Discovery Tool	38
Infrared Remote Control	39
Materials	39
Buttons.....	40
Operation	41
Changing Ports	41

Channel Surfing.....	41
Jump To Input.....	42
Jump To Output.....	42
Connect All	42
Save and Recall.....	43
Multiple Switch Control	43
Canceling a Command	43
Technical Specifications For IRT-UNV	44
Troubleshooting the IRT-UNV	44
Troubleshooting the VEEMUX.....	44
General Technical Specifications.....	45
Index	45
Warranty Information.....	45

TABLE OF FIGURES

Figure 1- Secure switch to a rack	4
Figure 2- Connect video sources to VEEMUX.....	5
Figure 3- Connect display devices to VEEMUX.....	5
Figure 4- Connect RS232 control terminal to VEEMUX.....	6
Figure 5- Connect VEEMUX to local area network	6
Figure 6- Attach AC power cord to VEEMUX.....	7
Figure 7- Web interface Login page.....	22
Figure 8- Administrator Menu	23
Figure 9- Main menu and Video Switch page	23
Figure 10- System Configuration page	25
Figure 11- Network Configuration page	26
Figure 12- Video Input Names page	27
Figure 13- Video Output Names page	28
Figure 14- Scanning Sequence page	29
Figure 15- Users page	31
Figure 16- User configuration page	31
Figure 17- DDC Options page	32
Figure 18- DDC Mix page	34
Figure 19- Update Firmware page	35
Figure 20- VEEMUX in Standby Mode.....	36
Figure 21- Logout of the VEEMUX web interface	36
Figure 22- Support Tab.....	37
Figure 23- System Reboot	37
Figure 24- Device Discovery Tool page.....	38

INTRODUCTION

The VEEMUX HDMI 4K Video Matrix switch (VEEMUX) provides non-blocking access to 16 4k x 2k video sources from 16 displays. Locate computers up to 20 feet away from 4K @ 60Hz displays or 50 feet from 1080p @ 60Hz displays, enabling easy access to multiple servers in various locations. Cables longer than 50 feet can be used for 1080p displays provided they have the built-in digital video equalizer (also known as an "active HDMI cable").

Application Note: Greater distances can be achieved using an ST-C64K-300 Video Extender supporting up to 4K@30hz. The ST-C64K-300 does not support HDMI2.0 and HDCP2.2. Be sure the video source connected is providing a 4K@30Hz signal for the ST-C64K-300 extender to work.

Features:

- Configure and control the switch through serial port, front panel buttons, web interface, or optional infrared control.
- Supports HDMI interface for crisp and clear video quality on flat panel displays.
- Supports HDMI operation up to 18 Gb/second
- Resolutions to 3840x2160 (UHD), and 4096x2160 (4K) @ 60Hz / RGB/YCBCR 4:4:4.
 - Supports up to 12 bits deep color.
 - Supports 4:4:4, 4:2:2 and 4:2:0 pixel encoding.
- EDID learning for the support of any HDMI display device.
- Built in default EDID configuration tables for 1080p and 4K resolution.
- Each output provides one video signal.
- Each input can be independently connected to any or all outputs.
- Up to 16 users (including "root") can be configured to control the VEEMUX from the Web Interface
- HDMI 1.4 and 2.0 compatible.
- HDCP 1.4 and 2.2 support.
- Passes embedded audio.

Supported Web Browsers

Most modern web browsers should be supported. The following browsers have been tested:

- Microsoft Internet Explorer 6.0 or higher
- Netscape 7.0 or higher
- Mozilla FireFox 40 or higher
- Google Chrome 9.0.5 or higher
- Apple Safari 5.0.3 or higher
- Opera 11.0 or higher

Set your browser to always check if there is a newer version of the page than the version stored in cache. This action will ensure that it will display the most up-to-date information.

MATERIALS

Materials supplied with this kit:

- NTI SM-16X16-HD4K HDMI 4K Video Matrix Switch
- Power Cord- country specific
- IRT-UNV Remote Control
- CT6182 DB9 Female-to-RJ45 Female adapter
- CB4352- 5 foot CAT5 patch cable
- 4pcs #10-32 x 3/4" pan head screws and #10-32 cage nuts (server cabinet mounting hardware)
- 36 pcs zip ties

Materials Not supplied but REQUIRED:

- HD-xx-MM cable for each 4K monitor being connected to the switch and for each PC being connected- available in 3, 6,10, 15,20,30,50,75 and 100 foot lengths


where:

xx is the length of the cable in feet


MM indicates male-to-male connector

Note:

- HD-3/6/10/15/20-MM supports resolutions to 4Kx2K.
- HD-30/50/75/100-MM supports resolutions to 1080p.
 - HD-75/100-MM have a built-in digital video equalizer for extending HD signals up to 1080p at 60Hz. These cables are directional, with one plug end marked for the display.



FEATURES AND FUNCTIONS



Item	Type	Description
1	IR LED	For indicating when an infrared signal is being received from the IR remote control
2	IR Receiver	this receives the IR signal from the infrared remote control
3	Power/Standby LED	Indicates when the VEEMUX is either ready for user interface (green) or in standby mode (red)
4	System Reset button	press this button to cycle the VEEMUX processor and reboot the system
5	LCD Display	indicates what inputs (video sources) are connected to the labeled output (display device)
6	Menu buttons	Used to control LCD menu navigation
7	Out and In buttons	Used to select which outputs (display devices) to connect to which inputs (video sources) when pressed
8	Power Switch	To control the ON/OFF function of the switch
9	IEC Connector	For attachment of country-specific power cord
10	HDMI Female	For connecting to HDMI video sources
11	HDMI Female	For connection of HDMI display devices
12	RJ45 Female	RS232 (DCE) connection for attachment of RS232 control cable
13	RJ45 Female	For connection of CATx cable to Local Area Network (LAN) for WEB interface

INSTALLATION

This NTI switch was designed to be mounted to a rack. It includes rack mount flanges to make attachment to a rack easy and a cable tray to easily secure attached cables to prevent disconnection.

To Mount to a Rack

1. Install 4 cage nuts (supplied) to the rack in locations that line up with the holes in the mounting flanges on the NTI switch.
2. Secure the NTI switch to the rack using four #10-32X3/4" screws (supplied). Each screw should be of sufficient length to go completely through the NTI mounting flange, rack frame and fully engage all threads in the cage nut. Be sure to tighten all mounting screws securely.
3. Attach all cables securely to the switch and where necessary supply adequate means of strain relief for cables.




Figure 1- Secure switch to a rack

Make All Connections

1. Connect a HDMI male cable between each video source and an “HDMI INx” connector on the rear of the VEEMUX.




Figure 2- Connect video sources to VEEMUX

2. Connect a HDMI male cable between each display device and an “HDMI OUTx” connector on the rear of the VEEMUX.




Figure 3- Connect display devices to VEEMUX

- If the VEEMUX will be controlled using RS232, then make a connection between the "RS232" port on the VEEMUX and a serial port on a PC. A DB9M-to-RJ45F adapter and 5 foot CAT5 patch cable have been provided to help with this connection if needed.




Figure 4- Connect RS232 control terminal to VEEMUX

- To make a remote connection, over the Ethernet, from anywhere on the local area network, connect a CAT5/5e/6 Ethernet cable with RJ45 male connectors on the ends, wired straight through (pin 1 to pin 1, pin 2 to pin 2, etc.).




Figure 5- Connect VEEMUX to local area network

5. Connect the powercord to the VEEMUX and plug it in.




Figure 6- Attach AC power cord to VEEMUX

6. Power ON all components. (In any order, which ones are first and which are last does not matter.)

OPERATING THE VEEMUX


The VEEMUX video matrix switch has four methods of control:

- Front Panel LCD with Keypad
- Directly via an RS232 Interface
- Remotely via Ethernet
- Infrared Remote

Every unit comes standard with all control methods built-in. An IRT-UNV-IR Remote Control is required to use the Infrared option. No software is involved (see Infrared Control on page 39). With the RS232 option, there are no external devices to be purchased. NTI provides software commands as well as a test program to ensure the RS232 functions properly (see page 11 – RS232 Control).


Front Panel LCD with Keypad Control

The front panel LCD and keypad allow the user to monitor switch status and route any user to any video source on the switch. When the unit is first powered-up, each monitor is automatically connected to the video source of its equal number (i.e. monitor 1 to source 1, monitor 2 to source 2, monitor 3 to source 3, etc.). (After configurations have been saved (page 24), upon power-up the VEEMUX will load the configuration saved into memory location 0.) Along with the routing of the inputs (video sources) to the outputs (monitors) the keypad and LCD allow the users to configure the RS232 control interface. The keypad buttons perform the following functions:



Key Functions:

- Up Arrow**- Scroll up the menu
- Down Arrow**- Scroll down the menu
- Left Arrow (Enter Key)**- Select the menu item
- List** - Open the menu, or exit the menu (also used to back out of the menu, one step at a time)
- Out-1- through 16** Used in command sequence to select which output (display device) to connect
- In-1-though 16** Used in command sequence to select which input (video source) to connect



To quickly change a connection, simply press the associated port number and then the “In” or “Out” button to designate the video source or the display (respectively). Alternatively, the “In” or “Out” button can be pressed, then the port number, followed by the “Enter” button.

Multiple displays can be connected to a single video source using one command sequence:

`<In> xx<Out>xx<Out>xx<Out>xx<Out>xx<Enter>` or
`<Out>xx<Out>xx<Out>xx<Out>xx <In> xx <Enter>` (where xx is the port number)

To configure the VEEMUX, use the Menu keys.

Press the **List** button to list your main menu options:

- 1- Serial
- 2- Ethernet
- 3- DDC
- 4- Standby
- 5- Save Config
- 6- Load Config

Use the **Up** and **Down Arrow** keys to scroll through this list.

Use the **Enter** Key to select a menu item.

Press the **List** button again to exit the menu.

If, while in a menu, you pause for more than 5 seconds, you will automatically exit the menu.

LCD Menus

Serial Menu

Under the “Serial” menu are two parameters:

- 1- Baud rate
- 2- Address

These parameters are used when the VEEMUX is controlled through an RS232 connection (page 11). If you select Baud rate, use the arrow keys to toggle through the available baud rates. The baud rate can be set to 115200, 57600, 38400, 19200, 9600, 4800, 2400, or 1200.

If you select Address, use the arrow keys to toggle through the address options (01-15). This is also the switch address used in conjunction with the IR Remote operation (page 43).

Ethernet Menu

Under “Ethernet” menu are several parameters:

- 1- Mode
- 2- IP Address
- 3- Mask
- 4- Gateway
- 5- Pref. DNS
- 6- Alt. DNS

The Mode parameter will let you select between a manual IP setting, a DHCP assigned dynamic IP address setting, or disabling the Ethernet port. An asterisk indicates which mode is configured, an arrow shows which mode is being selected. To change the configured setting and move the asterisk, select the desired mode and press the **Enter** button.

If you choose a manual IP setting, the IP parameter provides the fields for entering a valid IP address. Use the up and down arrows to advance the numbers, and the **Enter** button to move from field to field. Press **List** to exit this screen.

Selections 3, 4 are necessary to apply valid values for your Subnet Mask and Gateway. Navigate these settings as described for setting the IP address.

Selections 5 and 6 are not used at this time and are therefore unnecessary.

DDC Menu

DDC enables the video source to get EDID information from the display device. This enables the video source to automatically select the optimal resolution for the display by receiving, at power up, information from the display device concerning its resolution specifications.

Under the “DDC” menu are five parameters:

- 1- **Chose Input** (Choose Input)
- 2- **All Inputs**
- 3- **FacDefault1**
- 4- **UsrDefault1**
- 5- **ReloadOptn**

1) **Choose Input**- select the EDID information source for each input individually, or

2) **All Inputs**- select EDID information source for all inputs at once.

Within these sections you will need to select between:

default 1- the inputs will get EDID information from a predefined table in the VEEMUX supporting 1080p resolution

default 2- the inputs will get EDID information from a predefined table in the VEEMUX supporting UHD resolutions

From Out (?)- select which Output port the Input will get EDID information from regardless of which output it is connected to

DDC Mix(?)- select which Input will receive EDID information that is common to the Outputs selected on the “DDC Mix” page (page 34) for that input

3) **FacDefault1**- Select this to use the factory default EDID data for DDC “Default 1” configuration

4) **UsrDefault1**- Select this to replace the EDID information stored in the VEEMUX for “Default 1” with the EDID data from the monitor presently connected to Output 1.

5) **ReloadOptn**- Select this and choose to **enable** or **disable** this feature. When enabled, the switch will refresh DDC data stored in the VEEMUX each time the VEEMUX is power-cycled. The DDC data will be based on the current DDC configuration settings.

Standby

The fourth option in the main menu is “Standby”. When Standby is selected, the VEEMUX switch will immediately go into a power saver mode and the LCD display will go blank. It will remain in this state until

- 1) any button is pressed on the front panel,
- 2) the Standby button is pressed on the optional IR Remote Control (page 40), or
- 3) the “Disable Standby” button is pressed in the web interface (page 36)

Save and Load (Recall) Config

The SM-16X16-HD4K includes the ability to save and recall up to 100 switch configurations using the LCD menu. The switch configurations define the current port connections, volume control settings, and video blank status.

Note: The IRT-UNV IR Remote (page 39) can also be used to access these configurations by using the “SAVE” and “RECALL” buttons.

To save a configuration, select “Save Config” from the main menu followed by a numeric button(s) (0-99) corresponding to the memory slot the configuration is to be saved in. Press **Enter** after your selection to force the current configuration to immediately be saved to the selected memory slot.

Configurations can be loaded (recalled) in much the same manner. To recall, select “Load Config” from the main menu followed by the numeric button(s) (0-99) corresponding to the memory slot from which the configuration is to be recalled. Press **Enter** after your selection to immediately force the switch to change the current switch configuration to match that of the configuration recalled.

RS232 CONTROL

RS232 enables the VEEMUX to be remotely controlled via RS232. To control the VEEMUX via RS232 the user has four options:

- write a program that runs on a PC using the Command Protocol (page 12)
- use the Matrix Switcher's Control Program (page 13)
- use the SerTest program (page 14)
- Remote Connection

The RS232 Interface is designed to meet the RS232C standard and can be controlled from any CPU or other controller with an RS232 communications port. The pin-out for the RJ45 connector on the unit is as follows:

RS232 (RJ45) CONNECTOR

PIN	SIGNAL	FUNCTION
1	-	No connection
2	-	No connection
3	RX+	Receive data (TXD at host)
4	GND	Ground
5	-	No connection
6	TX+	Transmit data (RXD at host)
7	-	No connection
8	-	No connection

A 5 foot patch cable and adapter, RJ45-to-DB9, have been provided for connection to most CPUs (see page 6).

Baud Rate

The baud rate can be changed by selecting MENU on the front panel keypad, using the OSD menu, using Telnet commands (page 16) or from the RS232 commands (page 12). The baud rate can be set to 115200, 57600, 38400, 19200, 9600, 4800, 2400, or 1200. A data protocol of 8 data bits, no parity, and 1 stop bit is used for communications. The default baud rate setting is 9600.

Command Protocol

CPU controller commands supported by the unit are defined below. All commands must be terminated with a <CR> (carriage return). When a command is sent, the entire string is echoed back along with a response from the addressed unit as shown in the Command Definitions table (below). All characters in the command string are case sensitive (see Command Definitions table), and all numbers below 10 must have a leading 0 (ex: 1 = 01).

Legend:

(All numbers must be two digits)

SW	:	Switch (01-15)	MM	:	Save Into Memory Bank (00-99)
BR	:	Baud Rate Code	LL	:	Load From Memory Bank (00-99)
OP	:	Output Port (01-MAXOUTPUTS)	<CR>	:	Carriage Return (Hex 0xD)
IP	:	Input Port (01-MAXINPUTS)	ip	:	IP address

Command Definitions

Command String	Good Response	Description
CS SW,IP,OP	*<CR>	VIDEO Connect One Output/User Port To Input/CPU Port
CA SW,IP	*<CR>	VIDEO Connect All Output/User Ports To Input/CPU Port
RO SW,OP	*<CR>IP<CR>	VIDEO Read Connection For Output/User Port
VB SW,OP,01	*<CR>	Blank the video for specific Output/User Port
VB SW,OP,00	*<CR>	Unblank the video for specific Output/User Port
CC SW,MM	*<CR>MM<CR>	Save Matrix Connections Into Memory Bank xx Xx=00-99
RC SW,LL	*<CR>LL<CR>	Restore Matrix Connections From Memory Bank
CB 00,BR	None	Change baud rate of serial line, BR=11(5200),57(600),38(400),19(200)96(00),48(00),24(00),12(00) Factory default is 9600
RS SW	*<CR>	Internal Reset
RV SW,00	*<CR>string0<CR>	Read NTI Version String
RU SW	*<CR>IP,OP<CR>	Read Unit Size
EA SW,ip	*<CR>	Set the IP address, ip is in xxx.xxx.xxx.xxx format, number of digits is minimum 1 and maximum 3 for each field Leading zeroes are accepted
EM SW,ip	*<CR>	Set the Subnet mask, ip is in xxx.xxx.xxx.xxx format, number of digits is minimum 1 and maximum 3 for each field. Leading zeroes are accepted
EG SW,ip	*<CR>	Set the default gateway, ip is in xxx.xxx.xxx.xxx format, number of digits is minimum 1 and maximum 3 for each field Leading zeroes are accepted
ET SW,timeout	*<CR>	Set the website timeout; timeout = numeric string of timeout in seconds. Values: 60, 300, 600, 900, 1800, 3600, 7200, 18000, 28800
RA SW*	<CR>ip<CR>	Read the IP address, ip is in xxx.xxx.xxx.xxx format, number of digits is minimum 1 and maximum 3 for each field Leading zeroes are accepted
RM SW*	<CR>ip<CR>	Read the Subnet mask, ip is in xxx.xxx.xxx.xxx format, number of digits is minimum 1 and maximum 3 for each field Leading zeroes are accepted
RG SW*	<CR>ip<CR>	Read the default gateway, ip is in xxx.xxx.xxx.xxx format, number of digits is minimum 1 and maximum 3 for each field Leading zeroes are accepted
RT SW*	<CR>timeout<CR>	Read the website timeout; timeout = numeric string of timeout in seconds. Values: 60, 300, 600, 900, 1800, 3600, 7200, 18000, 28800
SS SW,00	*<CR>	Disable Autostatus feature (see below)
SS SW,01	*<CR>	Enable Autostatus feature (see below)
GO SW,OP	*<CR>go SW,OP,IP<CR>	Read connection of a Video Output Port to Video Input Port
GM SW,00	*<CR>go SW,OP,IP (all ports)<CR>	Read connection matrix of all Video Output ports

If the first field is not a known command (as listed above) or SW field is different from the serial address programmed in the switch memory, the command will be ignored. If the SW field corresponds to the unit address, but the syntax is wrong after this field, the switch will answer with a bad response ?<CR>.

Autostatus

When Autostatus is enabled, any output-to-input connection change in the VEEMUX will cause an Autostatus message to be sent via RS232 to the administrator. The format of the message would be "pc SW,OP:IP<CR>"

Example of an Autostatus message:

```
pc 01,01:04<CR>
```

which means "At the switch with unit address 01, the output (01) has changed connection to input 04."

**Notes: Message to the administrator will be delayed by any RS232 traffic being received by the switch from the administrator.
Autostatus must be disabled before using SerTest or the Matrix Switcher's Control Program (page 13).**

By default, Autostatus is disabled and must be manually enabled. Autostatus is also disabled any time the power to the VEEMUX is interrupted.

NTI Switch Control Program For Windows 9X, NT, 2000, XP, Vista, 7, 8 and 10

The NTI Switch Control Program is an easy and powerful graphical program that controls NTI matrix switches through an RS232 interface. The NTI Switch Control Program is downloaded from <http://www.networktechinc.com/download/d-vmtx-dvi.html>.

To install the Program after downloading

1. Locate the **Setup.exe** in the directory the program was downloaded to and double-click on it
2. Follow the instructions on the screen

The NTI Switch Control Program performs best on monitors set to a screen resolution of at least 800 X 600. Instruction for using the NTI Switch Control Program is available by opening "MSCP Help" in the "NTI" program group once the program has been installed and is open on the screen.

To open "MSCP Help" from the Windows desktop

1. Click on **START**
2. Click on **PROGRAMS**
3. Click on **NTI**
4. Click on **MSCP Help**

Note: While in Scan Mode, the video radio buttons shown on the Switch page of the NTI Switch Control Program may not be in sync with the connection changes within the VEEMUX. Connections will change without updating the image on the screen.

SerTest- RS232 Interface Test Program

This software allows a user to test the functions of an NTI server switch, matrix switch or Multi-user/Multi-platform switch RS232 interface. The SerTest program is automatically loaded when installing the NTI Switch Control Program as described above. The SerTest program, located in the NTI program group, generates a main menu with the 4 selections described below:

Main Options

- Matrix Operations - send commands to the matrix unit.
- Ethernet Operations - set Ethernet connection variables
- Setup Options - set COM port, baud rate, and unit address
- About SerTest - display the program version

Matrix Operations

Key	Selection	Description
1)	Connect Video Output/User to an Input/CPU	- connect an output to an input
2)	Connect All Video Outputs/Users to an Input/CPU	- connect all outputs to an input
3)	Connect Audio Output/User to an Input/CPU	- connect an output to an input (audio ports only)
4)	Connect All Audio Outputs/Users to an Input	- connect all outputs to an input (audio ports only)
5)	Change Mute Status for Audio Output/User	- mute or un-mute the Audio port output
6)	Change Volume for Audio Output/User	- change Audio port output volume
7)	Read Connection for Video Output/User	-read the connection of a specific video output
8)	Read Connection for Audio Output/User	-read the connection of a specific audio output
9)	Read Mute and Volume for Audio Output/User	- read the volume and the mute status of the specified output (audio ports only)
a)	Save I/O Connections into Unit Memory	-save the connections into switch memory bank
b)	Restore I/O Connections from Unit Memory	-restore the connections from switch memory bank
c)	Change All Units Baud Rate (9600/COM1:)	-change RS-232 Baud rate of all switches -the current baud rate and serial port are displayed in parentheses
d)	Reset Unit	- send a reset command to the switch - the current unit address is displayed in parentheses
e)	Reset All Units	- send an internal reset command to all switches
f)	Read Unit Size	- read the switch size (number of inputs and outputs)
g)	Read Unit Version/Revision String	-read a string containing the switch version, type, and size
h)	Save All Units I/O Connections into Units Memory	-save the connections into switch memory bank, command for all switches
i)	Restore All Units I/O Connections from Units Memory	-restore the connections from switch memory bank, command for all switches

Grayed keys are not applicable to this product

Ethernet Operations

Key	Selection	Description
1)	Set Unit IP Address	- enter the desired IP address in xxx.xxx.xxx.xxx format - number of digits is minimum 1 and maximum 3 for each field. Leading zeroes are accepted
2)	Set Unit Subnet Mask	- enter the desired IP address in xxx.xxx.xxx.xxx format - number of digits is minimum 1 and maximum 3 for each field. Leading zeroes are accepted
3)	Set Unit Default Gateway	- enter the desired default gateway - number of digits is minimum 1 and maximum 3 for each field. Leading zeroes are accepted
4)	Set Unit Website Timeout	- set the website timeout; timeout = numeric string of timeout in seconds - Values: 60, 300, 600, 900, 1800, 3600, 7200, 18000, 28800 0 = no timeout
5)	Read Unit IP Address	- read the unit IP address in xxx.xxx.xxx.xxx format
6)	Read Unit Subnet Mask	- read the unit subnet mask in xxx.xxx.xxx.xxx format
7)	Read Unit Default Gateway	- read the unit default gateway in xxx.xxx.xxx.xxx format
8)	Read Unit Website Timeout	- read the current website timeout period in seconds - Values: 60, 300, 600, 900, 1800, 3600, 7200, 18000, 28800 0 = no timeout

Setup Options

Key	Selection	Description
1)	select Com port current: (COM1:)	- select PC serial port - the current PC serial port is displayed in parentheses
2)	select Baud rate current: (9600)	- select PC serial port baud rate - the current baud rate is displayed in parentheses
3)	set unit Address current: (1)	- select the unit address - the current address is displayed in parentheses
4)	set read timeout (5)	- select the time period (in seconds) the SerTest will wait for an answer to a command - the current time period is displayed in parentheses

For any selection that requires user input, the user is prompted. When commands are sent to the matrix unit, the command string and matrix unit responses are echoed to the screen. All commands generated by the program are formatted according to the information provided in sections above. If any transmission problems are detected, an error message is displayed.

Press <Esc> or <Enter> to back out to the main menu and press again to exit.

ETHERNET CONTROL

Telnet Interface-Port 2000

The Telnet Interface enables the user to control the switch using telnet client through an Ethernet connection. The telnet server (telnet must be enabled- see page 26) listens on ports 2000 and 2005. Port 2000 is for an operator telnet session while port 2005 is intended for a software control type session (see page 18 for more on Port 2005 control). For operator telnet control using the telnet interface and the current IP address, type the following in a command shell:

telnet 192.168.1.30 2000 (for Port 2005 control, substitute "2005" for "2000" in this command)

The VEEMUX will prompt the user for a password. The user must enter the password followed by <Enter>.

The factory default password is "nti".

Since Port 2005 control is initiated via software from a controller, rather than manually, the password requirement is not part of the command sequence.

With a proper password sent the VEEMUX will respond with:

***Password Successful
Connection Established***

The commands below are now available.

Telnet Interface- Port 2000 Commands

Command	Reply	Description
H(elp) or h(elp)	Displays the list of commands	Help
CS nn,mm	*<CR>	Connect One input nn To output mm
CA nn	*<CR>	Connect All Outputs To Input nn
RO mm	*<CR>nn<CR>	Read Connection For Output. Returns the number of the input nn connected to output mm
CC nn	*<CR>nn<CR>	Save Matrix Connections Into Memory Bank nn nn should be between 00 and 99
RC nn	*<CR>nn<CR>	Restore Matrix Connections From Memory Bank nn nn should be between 00 and 99
CB nn	*<CR>	Change baud rate of serial line, nn=12(00),24(00),48(00),96(00) Factory default is 9600.
RV 00	*<CR>string<CR>	Read NTI Version String
RU	*<CR>nn,mm<CR>	Read Unit Size Returns the number of inputs nn and the number of outputs mm
RS	*<CR>	Reset Unit
Ss nn,dwt	*<CR>	Set value of Scan Mode dwell time (see page 9) for specific Output (nn) dwt = 000-255 (seconds) 000= disable Scan Mode

Command	Reply	Description
Gs nn	*<CR> dwt<CR>	Read set Scanning Sequence dwell time value (dwt) for specific Output (nn) in seconds (see also "Scanning Sequences" on page 29)
Sa nn,mm	*<CR>	Set scan list of individual output nn to all inputs mm
Sc nn	*<CR>	Clear scan list of individual output nn
S+ nn,mm	*<CR>	Add input mm to Scan List of output nn
S- nn,mm	*<CR>	Remove input mm from Scan List of output nn
Sx nn	*<CR>oooxxxxooooxxx<CR>	Display the Scan List of output nn (o=skip x=don't skip)
CP	User is prompted to introduce the password twice	Change password- five (5) characters minimum
<Ctrl>-<X> (see note 4 below)	Good Bye. Connection to host lost.	Quit telnet session
H(elp) or h(elp)	Displays the list of commands	Help

Notes:

1. The commands must be typed exactly as shown in the chart. The commands are case sensitive.
2. If a mistake is made, the user must backspace to the beginning and completely retype the command.
3. If a command is sent that the VEEMUX does not recognize or exceeds the configuration of the switch, the reply "?" may be received. Check the command syntax and try again.
4. To quit the telnet session, press the keyboard keys <Ctrl><X> + <Enter>.

Telnet Interface-Port 2005

For a software control type of telnet interface session (versus operator telnet control through port 2000 as described on page 16), connect to the VEEMUX through the current IP address at port 2005. Use the command set below to control and acquire information from the VEEMUX.

Note: After establishing the connection, the unit will answer with a blinking prompt on the next line. If the connection fails it will answer with ?<CR>

Note: When using some controllers (Crestron for example), a slight delay may necessary to be added at the end of each command string.

Legend: (All numbers must be two digits)

OP : Output Port (01-MAXOUTPUTS)
 IP : Input Port (01-MAXINPUTS)
 <CR> : Carriage Return (Hex 0xD)

Command Summary

Command String	Good Response	Description
RU<CR>	ru IP,OP<CR>	Read unit size
RO OP<CR>	pc OP,IP<CR>	Read connection for OP
CS IP,OP<CR>	*<CR>	Connect OP to IP
CA IP<CR>	*<CR>	Connect all outputs to IP
SS 01<CR>	*<CR>	Enable auto-status mode
SS 00<CR>	*<CR>	Disable auto-status mode
SX<CR>	See details	Examine connections
XX<CR>	*<CR>	Close connection

A <CR> (carriage return, 0x0D) is considered to be the end of the command string. If a string exceeds 16 characters, an end of string will be inserted automatically to avoid buffer overflow. An eventual <LF> (line feed, new line, 0x0A) after a <CR> will be ignored. A bad string will always be responded to with the ASCII character '?' followed by a <CR>.

Note: Always be sure to terminate your telnet session with the <X> - <X> - <Enter> command string.

Command Detail

RU-Read Unit Size

Command:

Byte 1	Byte2	Byte3
'R' (0x52)	'U' (0x55)	<CR> (0x0D)

Response:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	Byte 9
'r' (0x72)	'u' (0x75)	Space (0x20)	Input – 1st digit (0x30...0x32)	Input – 2nd digit (0x30...0x39)	',' (0x2C)	Output – 1st digit (0x30...0x32)	Output-2nd digit (0x30...0x39)	<CR> (0x0D)

This command will read the size of the unit. The response returns the number of inputs and the number of outputs in two-digit, ASCII code format. If the numbers are smaller than 10, the 1st digit is '0'.

RO-Read Connection for Output Port

Command:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6
'R' (0x52)	'O' (0x4F)	Space (0x20)	Output – 1st digit (0x30...0x32)	Output – 2nd digit (0x30...0x39)	<CR> (0x0D)

Response:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	Byte 9
'p' (0x70)	'c' (0x63)	Space (0x20)	Output – 1st digit (0x30...0x32)	Output-2nd digit (0x30...0x39)	',' (0x2C)	Input – 1st digit (0x30...0x32)	Input – 2nd digit (0x30...0x39)	<CR> (0x0D)

This command will read the connection of an output port. The response returns the output port that is connected to the input port.

CS- Connect Output Port to Input Port

Command:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	Byte 9
'C' (0x43)	'S' (0x53)	Space (0x20)	Input –1st digit (0x30...0x32)	Input –2nd digit (0x30...0x39)	',' (0x2C)	Output – 1st digit (0x30...0x32)	Output – 2nd digit (0x30...0x39)	<CR> (0x0D)

Response:

Byte 1	Byte 2
'*' (0x2A)	<CR> (0x0D)

This command connects the specified input port to the specified output port.

CA- Connect All Output Ports to Input Port

Command:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6
'C' (0x43)	'A' (0x41)	Space (0x20)	Input – 1st digit (0x30...0x32)	Input - 2nd digit (0x30...0x39)	<CR> (0x0D)

Response:

Byte 1	Byte 2
'*' (0x2A)	<CR> (0x0D)

This command connects all output ports to the specified input port.

SS_01- Enable Auto Status Mode

Command:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6
'S' (0x53)	'S' (0x53)	Space (0x20)	'0' (0x30)	'1' (0x31)	<CR> (0x0D)

Response:

Byte 1	Byte 2
'*' (0x2A)	<CR> (0x0D)

Auto status mode is disabled by default whenever the connection is established, and this command must be entered to enable it. When auto status mode is enabled, a message will be sent whenever an input/output connection changes from any source. The format of this message is given in the table below. The first two numeric digits are the output port number and the two after the colon are the number of the input port that is now connected to it.

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	Byte 9
'p' (0x70)	'c' (0x63)	Space (0x20)	Output – 1st digit (0x30...0x32)	Output – 2nd digit (0x30...0x39)	':' (0x3A)	Input – 1st digit (0x30...0x32)	Input – 2nd digit (0x30...0x39)	<CR> (0x0D)

SS_00- Disable Auto Status Mode

Command:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6
'S' (0x53)	'S' (0x53)	Space (0x20)	'0' (0x30)	'0' (0x30)	<CR> (0x0D)

Response:

Byte 1	Byte 2
'*' (0x2A)	<CR> (0x0D)

This command disables auto status mode.

SX- Examine connections

Command:

Byte 1	Byte 2	Byte 3
'S' (0x53)	'X' (0x58)	<CR> (0x0D)

Response:

Multiple lines, one line for each output:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	Byte 9
'p' (0x70)	'c' (0x63)	Space (0x20)	Output – 1st digit (0x30...0x32)	Output – 2nd digit (0x30...0x39)	':' (0x3A)	Input – 1st digit (0x30...0x32)	Input – 2nd digit (0x30...0x39)	<CR> (0x0D)

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8	Byte 9
'p' (0x70)	'c' (0x63)	Space (0x20)	Output – 1st digit (0x30...0x32)	Output – 2nd digit (0x30...0x39)	':' (0x3A)	Input – 1st digit (0x30...0x32)	Input – 2nd digit (0x30...0x39)	<CR> (0x0D)

Last line:

Byte 1	Byte 2
'*' (0x2A)	<CR> (0x0D)

Terminate telnet session

Command:

Byte 1	Byte 2	Byte 3
'X' (0x58)	'X' (0x58)	<CR> (0x0D)

Response:

Byte 1	Byte 2
'*' (0x2A)	<CR> (0x0D)

The unit will respond with '*<CR>' and close the connection, terminating the telnet session. The unit is then available for future connections.

Web Interface

A user may control the connections of the VEEMUX using a Web Interface via any web browser (see page 1 for supported web browsers). With the VEEMUX connected to a LAN through an Ethernet cable, a user can access the web interface controls inside the VEEMUX.

FYI: To quickly locate a VEEMUX on the LAN and edit the IP address settings, use the Device Discovery Tool (page 38).

To access the web interface, type the current IP address into the address bar of the web browser.

Address

To open a SSL-encrypted connection, type:

Address

You will be prompted to accept a certificate. Accept the NTI certificate.

A "Login Page" will appear.

The screenshot displays the NTI Network Technologies web interface. At the top left is the NTI logo and company name. At the top right, system information is shown: Unit: sm-mxn-4k_test, Model: SM-16x16-4K, and Uptime: 3 hours, 11 mins. Below this is a navigation bar with 'Home' and 'Login' links. A 'Support' button is visible on the left. The main content area is titled 'Login' and contains a form titled 'Enter login credentials'. The form has two input fields: 'Username' with the value 'root' and a placeholder 'Enter the username to log in with', and 'Password' with masked characters '...' and a placeholder 'Enter the associated password'. A 'Login' button is located at the bottom left of the form. In the bottom right corner of the page, there is a 'goahead WEB SERVER' logo. The footer contains the copyright notice: 'Copyright © 2018 Network Technologies Inc. All rights reserved.'

Figure 7- Web interface Login page

Enter the Password

The cursor will be flashing inside the username box. Enter the administrative username (this cannot be changed), then enter the default password:

User Name = root (lower case letters only)

Password = nti (lower case letters only)

To change the password, see page 31.

If you are not the "root" user, access to the VEEMUX may be limited. Contact the VEEMUX administrator for your individual username and password.

For information on setting up as many as 15 additional users, see page 31.

Note: The browser must be configured to accept cookies in order for the user to successfully make use of the web interface.

With a successful login, the main menu and Video Switch page will appear.

Main Menu

The VEEMUX main menu provides control over all functions of the switch. The administrative menu includes options not available to other users with limited privileges.



When logged in a user without administrative privileges, only the SWITCH, LOGOUT, and SUPPORT menu options will be available.

For more on user management, see page 31.




Figure 8- Administrator Menu

(User Main Menu)

NTI NETWORK TECHNOLOGIES INCORPORATED

Unit: sm-mxn-4k_test Model: SM-16x16-4K Uptime: 3 hours, 15 mins

Home Video Switch Connections

Switch
Video Switch
Administration
Standby
Logout
Support
Reboot

Video Switch

Sort Ports by: Number Name

Stored Configurations: Load Save 0

Legend: Active Connection Connection to be applied

Inputs	Outputs															
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Port01 (1)																
Port02 (2)																
Port03 (3)																
4k pc (4)																
Port05 (5)																
Port06 (6)																
Port07 (7)																
Port08 (8)																
Port09 (9)																
Port10 (10)																
Port11 (11)																
Port12 (12)																
1080 pc (13)																
Port14 (14)																
Port15 (15)																
4k bluecray (16)																

Note: Click an Input to Set All Outputs to that Input.

Submit Clear Changes

Copyright © 2018 Network Technologies Inc. All rights reserved.

Figure 9- Main menu and Video Switch page

From the menu the administrative user can choose from several links to either view the status of the switch or change the configuration of it. As described on the following pages, each link will enable different areas of control.

Video Switch Page

The Video Switch page (Figure 9) displays the active connections (shown in orange) and enables the user to control the video connections of the VEEMUX. Up to 100 different connection configurations can be saved and later recalled by any connection method. Scanning Sequences (page 29) for each output can also be enabled.

Note: Changes made using the keypad (page 8) or by another user through the web interface will be updated automatically to your browser every 10 seconds.

Note: Configuration 0 will be automatically loaded when the VEEMUX is powered-up.

To change a connection, click on the radio button (square image with circle in the center) that intersects the input and output columns. A black dot will be placed in the circle to indicate the selection. Then press the **Submit** button. The display will be reloaded with the selections changed to orange to indicate they are now active. Multiple connections can be changed simultaneously.



To quickly clear the selected radio buttons press the **Clear Changes** button. This will only work if the **Submit** button has not already been pressed with the selections made.

To quickly connect all outputs to a single input, click on the desired input.

FYI: See page 30 for an example of using the Outputs Scanning Sequences feature.

To save a configuraton, from the **Stored Configurations** user interface, use the drop-down list to select the desired slot (numbers 0-99) to save the active configuration into and press the **Save** button.



Note: This will save the currently active configuration on the VEEMUX and the DDC configuration (page 32). If changes have been made in the web interface without first pressing the **Submit** button, those changes will not yet be part of the active configuration.

Note: If changes to the active configuration have been made by another user prior to saving the current connection selections, the changes made by the other user will be saved as the configuration.

The webpage configuration that loads after a **Save** is the configuration that was actually saved.

To load a saved configuration, from the **Stored Configurations** user interface, use the drop-down list to select the desired configuration. Then press the **Load** button. The VEEMUX will make the connections and the screen will refresh to show the connections associated with that configuration selection. This also loads the saved DDC configuration (page 32).

To blank the video to a specific output, click the box to the right of "Blank" that corresponds with the desired output to place a checkmark in it. The video going to that output will be disabled.

To enable the scanning sequence configured for an output, configure the automatic scanning sequence of inputs that should be viewed at the output (see page 29) and then click the box to the right of "Sequence Enabled" that corresponds with the desired output to place a checkmark in it. The video viewed from that output will switch from input to input according to the configured sequence.

Administration

Switch
Administration
System
Network
Video Input Names
Video Output Names
Scanning Sequence
User Config
DDC Options
DDC Mix Settings
Firmware
Standby
Logout
Support
Reboot

The Administration section provides links to pages for all configuration options in the VEEMUX switch. Only the user ROOT and users with administrative privileges have access to this section. The administration section is broken up into 10 topics:

System	Assign the switch name and serial port communication settings
Network	Assign all network settings for connection to LAN
Video Input Names	Assign port names to each cable connection from video sources for easy reference
Video Output Names	Assign port names to each cable connection from display devices for easy reference
Scanning Sequence	Assign dwell times for each input as it is assigned to each output's scanning sequence
User Config	Add, edit, and delete users and control user privileges
DDC Options	Configure how each input will receive EDID information
DDC Mix Settings	Select outputs/displays to be used for EDID mixing for each input
Firmware	Update the firmware as new versions become available

System Configuration

On the System Configuration page, under Administration, fields are provided to assign a unique name to the VEEMUX, set the baud rate for serial communications, and the serial address to be used in RS232 commands.

After applying the desired settings, press “**Save**” to finish.

System Configuration

The screenshot shows the 'System Configuration' page with the following sections:

- Unit Settings:** Name field with value 'sm-mux-4k_test' and a note 'Unique name for this unit'.
- Serial Port Settings:** Baud Rate dropdown set to '115200 bps' with a note 'Baud Rate for RS232 Commands'; Serial Address dropdown set to '1' with a note 'Address for RS232 Commands and System Address for IR Remote'.
- Configuration Backup & Restore:** 'Choose File' section with a 'Browse...' button and a note 'No file selected. Choose configuration file to restore. Note: system will reboot to apply the configuration.' Below this are buttons for 'Upload Config', 'Download Configuration File', 'Restore Defaults', and 'Save'.

Figure 10- System Configuration page

Download Configuration File - To save VEEMUX configuration and DDC settings for a future reload or to save time in configuring multiple VEEMUX switches, the configuration file for the VEEMUX can be downloaded to your PC using “**Configuration Backup & Restore**”. Click on “**Download Configuration File**” to save the VEEMUX configuration to your PC.

From your PC the downloaded configuration file can be edited using any text editor or html editor. Using an editor you can change settings, change IP address, etc. and then upload the result into an additional VEEMUX switch to save time.

Upload Config- Click on the **Browse** button to browse to the file, click on “**Upload Config**”, and restore the VEEMUX to the configuration stored in the uploaded file.

Restore Defaults- Click on “**Restore Defaults**” to remove all user-configured settings and restore the VEEMUX to a factory default configuration.

Note: Before restoring defaults, we recommend you download the existing configuration file to your PC.

After applying the desired settings, press “**Save**” to finish.

Network Configuration

ON the Network Configuration page, under Administration, the administrative user can configure the VEEMUX web interface connection. This will provide access to control of the VEEMUX from any web-accessible computer.

Network Configuration

The screenshot shows the Network Configuration page with two main sections: IP Settings and Server Settings. In the IP Settings section, the Mode dropdown menu is open, showing options: Static, DHCP, Static, and Disable. The Static option is highlighted. The IP Address field contains 192.168.3.61, Subnet Mask is 255.255.255.0, and Default Gateway is 192.168.3.3. The Server Settings section includes checkboxes for Enable Telnet (unchecked) and Allow HTTP Access (checked), and text input fields for HTTP Port (80), HTTPS Port (443), and Web Timeout (600). A Save button is located at the bottom left.

Figure 11- Network Configuration page

Mode – Choose between Static IP assignment, DHCP (dynamic IP assignment) or Disable the Ethernet port entirely.

IP Address- If using Static IP assignment, enter a valid IP address to use

Subnet Mask- Enter a valid subnet mask value

Default Gateway- Enter a valid gateway address

Preferred DNS- Enter a valid Domain Name Server address (not required)

Alternate DNS- Enter a valid alternate Domain Name Server address if desired (not required)

This change will take a few seconds and automatically redirect the user to the IP address specified.

If telnet is going to be used to control the VEEMUX, place a checkmark in the “Enable Telnet” block.

If you wish to disable non-secure web access to the VEEMUX, remove the checkmark from “Allow HTTP Access”. With this box empty, only secure shell web access will be allowed.

A standard port number can be assigned for the HTTP (non-secure) and HTTPS (secure) ports, numbers ranging from 0-65535. Default HTTP port is 80, and default HTTPS port is 443.

The Website Timeout option controls how long an inactive web connection will stay logged in. The range is 0-3200 minutes (0 disables it). Any change to the Website Timeout configuration takes effect immediately.

Press the “**Save**” button to save any changes made.

Video Input Names

From the Administration menu, the Video Input Names page can be displayed. This page enables the administrative user to change the name of the input ports displayed on the Video Switch page.

Video Input Names

Port1.	Port01 Name for input port 1
Port2.	Port02 Name for input port 2
Port3.	Port03 Name for input port 3
Port4.	4k pc Name for input port 4
Port5.	Port05 Name for input port 5
Port6.	Port06 Name for input port 6
Port7.	Port07 Name for input port 7
Port8.	Port08 Name for input port 8
Port9.	Port09 Name for input port 9
Port10.	Port10 Name for input port 10
Port11.	Port11 Name for input port 11
Port12.	Port12 Name for input port 12
Port13.	1080 pc Name for input port 13
Port14.	Port14 Name for input port 14
Port15.	Port15 Name for input port 15
Port16.	4k bluerey Name for input port 16

Save Reset

Figure 12- Video Input Names page

To change an Input Name, enter the name of the port for the desired input port number, and press “**Save**”.

If you make changes and change your mind and want to return the names back to what they were before changing them, press “**Reset**”. This must be done before pressing the “**Save**” button, or changes will not be able to be reversed.

Video Output Names

From the Administration menu, the Output Names page can be displayed. This page enables the Administrator to change the names of the output ports displayed on the Switch page.

Video Output Names

Video Output Names	
User1.	<input type="text" value="Output01"/> Name for output port 1
User2.	<input type="text" value="Output02"/> Name for output port 2
User3.	<input type="text" value="Output03"/> Name for output port 3
User4.	<input type="text" value="4k mon"/> Name for output port 4
User5.	<input type="text" value="Output05"/> Name for output port 5
User6.	<input type="text" value="Output06"/> Name for output port 6
User7.	<input type="text" value="Output07"/> Name for output port 7
User8.	<input type="text" value="Output08"/> Name for output port 8
User9.	<input type="text" value="Output09"/> Name for output port 9
User10.	<input type="text" value="Output10"/> Name for output port 10
User11.	<input type="text" value="4k TV"/> Name for output port 11
User12.	<input type="text" value="Output12"/> Name for output port 12
User13.	<input type="text" value="Output13"/> Name for output port 13
User14.	<input type="text" value="dell 1200 mon"/> Name for output port 14
User15.	<input type="text" value="Output15"/> Name for output port 15
User16.	<input type="text" value="Output16"/> Name for output port 16

Figure 13- Video Output Names page

To change an Output Name, enter the name of the port for the desired output port number, and press "**Save**".

If you make changes and change your mind and want to return the names back to what they were before changing them, press "**Reset**". This must be done before pressing the "**Save**" button, or changes will not be able to be reversed.

Scanning Sequences

From the Administration menu, the Scanning Sequence page can be displayed. The Scanning Sequence page displays the configuration of an automatic switching sequence from input (video source) to input for each output (monitor).

The page displays:

- output number being configured
- the Scanning Sequence function status for that output
- the length of time in seconds (dwell time) that each input will be viewed when connected- the dwell time value ranges from 0-255 seconds

Scanning Sequence

Scanning Sequence

Dwell Times for output: Output01 (1) ▼

Sequence Enabled

Input	Dwell time (seconds)
Port01 (1)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 1 - (0-255)seconds. 0=disable scan.</small>
Port02 (2)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 2 - (0-255)seconds. 0=disable scan.</small>
Port03 (3)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 3 - (0-255)seconds. 0=disable scan.</small>
4k pc (4)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 4 - (0-255)seconds. 0=disable scan.</small>
Port05 (5)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 5 - (0-255)seconds. 0=disable scan.</small>
Port06 (6)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 6 - (0-255)seconds. 0=disable scan.</small>
Port07 (7)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 7 - (0-255)seconds. 0=disable scan.</small>
Port08 (8)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 8 - (0-255)seconds. 0=disable scan.</small>
Port09 (9)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 9 - (0-255)seconds. 0=disable scan.</small>
Port10 (10)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 10 - (0-255)seconds. 0=disable scan.</small>
Port11 (11)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 11 - (0-255)seconds. 0=disable scan.</small>
Port12 (12)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 12 - (0-255)seconds. 0=disable scan.</small>
1080 pc (13)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 13 - (0-255)seconds. 0=disable scan.</small>
Port14 (14)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 14 - (0-255)seconds. 0=disable scan.</small>
Port15 (15)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 15 - (0-255)seconds. 0=disable scan.</small>
4k blueray (16)	<input style="width: 100px;" type="text" value="0"/> <small>Scan dwell time for input 16 - (0-255)seconds. 0=disable scan.</small>

Figure 14- Scanning Sequence page

The output selection at the top of the page can be changed to any output to display the Scan Sequence Input dwell time values for that output.

The inputs and the amount of time that each will be viewed (0-255 seconds) can be set to cycle sequentially for each connected output. If an input is set to 0 seconds, that input will not be viewed and will be skipped from the scanning sequence. To include an input in the sequence, enter a dwell time period from 1-255 seconds, and press **“Save”**.

NTI VEEMUX HDMI 4K VIDEO MATRIX SWITCH

If you make changes and change your mind and want to return the values back to what they were before changing them, press **“Reset”**. This must be done before pressing the **“Save”** button, or changes will not be able to be reversed.

To enable the scanning sequence for the output shown, place a checkmark in the **“Sequence Enabled”** block.

*Tip: To quickly enable the scan sequence for multiple outputs, use the **“Sequence Enable”** blocks found on the Switch Page (page 18).*

Note: If only one input has a dwell time value entered, then the output connection to that input will not end when the Scanning Sequence is enabled.

Example of using Outputs Scanning Sequences

Problem: A synchronous scan is desired for all outputs with a dwell time of 3 minutes per input, and no two outputs should be looking at the same input at any given time.

Solution:

1. Set the dwell time for all inputs listed in each output at 180 seconds (3 minutes). Press **“Save”** each time changes are made to the selected output.
2. Go to the Video Switch page (page 18) and set each output to an input of the same number (1 to 1, 2 to 2, 3 to 3, etc..). Click on **“Submit”** at the bottom of the Video Switch Page to submit selections and establish a connection and starting point for the scanning sequence. (Blocks shown in yellow in the third image indicate connections made.)
3. Click on the **“Sequence Enable”** box for each output (from the Video Switch Page).
4. Click on **“Submit”** again to begin the scanning sequence for each output.

From the moment the configuration is submitted, a synchronous scan will begin on all outputs. Each output will connect to its respective input for 3 minutes. After 3 minutes, the outputs will each switch to the next consecutive input and remain connected for 3 minutes. This cycle will continue indefinitely until sequencing is disabled.

Scanning Sequence

Scanning Sequence

Dwell Times for output: Output1 (1) ▾

Sequence Enabled

Input	Dwell time (seconds)
Port1 (1)	180 <small>Scan dwell time for input 1 - (0-255)seconds. 0=disable :</small>
Port2 (2)	180 <small>Scan dwell time for input 2 - (0-255)seconds. 0=disable :</small>
Port3 (3)	180 <small>Scan dwell time for input 3 - (0-255)seconds. 0=disable :</small>
Port4 (4)	180 <small>Scan dwell time for input 4 - (0-255)seconds. 0=disable :</small>

Step 1- setup dwell times

Sort Ports by: ▾

Legend
 Active Connection
 Connection to be applied

Inputs	1	2	3	4	5	6	7	8
Port1 (1)	●	○	○	○	○	○	○	○
Port2 (2)	○	●	○	○	○	○	○	○
Port3 (3)	○	○	●	○	○	○	○	○
Port4 (4)	○	○	○	●	○	○	○	○
Port5 (5)	○	○	○	○	●	○	○	○
Port6 (6)	○	○	○	○	○	●	○	○
Port7 (7)	○	○	○	○	○	○	●	○
Port8 (8)	○	○	○	○	○	○	○	●

Sequence Enabled

Note: Click an Input to Set All Outputs to that Input.

Sort Ports by: ▾

Legend
 Active Connection
 Connection to be applied

Inputs	1	2	3	4	5	6	7	8
Port1 (1)	●	○	○	○	○	○	○	○
Port2 (2)	○	●	○	○	○	○	○	○
Port3 (3)	○	○	●	○	○	○	○	○
Port4 (4)	○	○	○	●	○	○	○	○
Port5 (5)	○	○	○	○	●	○	○	○
Port6 (6)	○	○	○	○	○	●	○	○
Port7 (7)	○	○	○	○	○	○	●	○
Port8 (8)	○	○	○	○	○	○	○	●

Sequence Enabled

Step 2- setup starting point for scan and click “Submit”

Step 3- enable scanning sequences and click “Submit”

Step 4- Click on “Submit” to begin

User Config

From the Administration menu, select the User Config to display a list of the users that have been configured on the VEEMUX.

- To add a user, select “Add New User”.
- To change the configuration of a user, select the Username, or “Edit”.
- To delete a user, select “Delete” for that user.

Users

Users				
Num.	Username	Enabled	Admin	Action
1	root	yes	yes	Edit
2	user1	yes	no	Edit Delete

[Add New User](#)

Figure 15- Users page

Whether you add a user, or edit a user, the “Configure User” page will open. If this is a new user being added, enter a user name, decide if the user should have administrative privileges or not, enable their access to the VEEMUX (or not), and assign a password.

- Usernames and passwords are case sensitive.
- Usernames can be from 1 to 16 characters in length and can be alphabetical or numeric.
- Passwords can be from 5 to 16 characters in length and can be alphabetical or numeric.

Note: A password must be entered for the user to be enabled, even if the “Enable” block is checked and the user is saved without a valid password being entered.

Configure User

Account Settings

Username	<input type="text" value="user1"/> <small>The username for this user</small>
Admin	<input type="checkbox"/> <small>Grant this user administrative privileges</small>
Enabled	<input checked="" type="checkbox"/> <small>Users can only access the system if their account is enabled</small>
Password	<input type="password" value="••••••"/> <small>The user's password to login to the system (for local authentication)</small>
Confirm	<input type="password" value="••••••"/> <small>Confirm the entered password</small>
Title	<input type="text"/> <small>The user's title within the company</small>
Department	<input type="text"/> <small>The user's department within the company</small>
Company	<input type="text"/> <small>The name of the user's company</small>

Figure 16- User configuration page

After making any changes, be sure to click “Save”.

DDC Options

From the Administration menu, the DDC Options page can be displayed. DDC enables the video source to get EDID information from the display device. This enables the video source to automatically select the optimal resolution for the display by receiving, at power up, information from the display device concerning its resolution specifications.

DDC Options

Figure 17- DDC Options page

EDID information can be provided to the video source by the VEEMUX as follows:

Default1- The video source on the input port will receive EDID information from the VEEMUX through an onboard table of values. The values for Default 1 support computer monitors. The factory default value is 1920x1080@60Hz(1080p).

Default2- The video source on the input port will receive EDID information from the VEEMUX. The value for Default 2 is 3840x2160@60Hz(UHD)

Load from Output- select the radio button for this option and enter the output number associated with the monitor that the CPU should get its EDID information from.

Mixed- The video source on the input port will receive EDID information that is common to the outputs selected on the “DDC Mix” page (page 34) for that input.

Update DDC setting on Power cycle and on Load Stored Switch Config- place a checkmark in the box to refresh DDC data stored in the VEEMUX each time the VEEMUX is power-cycled or when a stored configuration (page 24) that includes this DDC configuration is loaded. The DDC data will be updated based on the configuration on this page.

Save and Store to Switch Configuration 0- press to save the DDC Configuration settings to Switch Configuration 0 so that when the VEEMUX is power cycled and the “Update DDC setting on Power Cycle...” (above) is checked, the DDC Configuration will be loaded as configured above.

Modify Default1 DDC with User1 DDC- click this button to load the EDID information to “Default1” from the video display connected to Output 1

Modify Default1 DDC with Factory Default- click this button to restore “Default1” with factory supplied EDID information

Once any changes are made, press “**Save**” to have them take effect.

Notes:

- In order for the video sources to correctly receive the EDID information from the switch at boot-up, the switch must be powered-up before all attached video sources.**

Disable HDCP 2.2

Place a checkmark in the **Disable HDCP 2.2** box if you wish to disable the port's compatibility with HDCPv2.2.

Normally, if a video source senses that the VEEMUX is compliant, it will provide HDCP 2.2 compliant video. Then, provided the connected monitor is also HDCP 2.2 compliant, a picture will be displayed. If the monitor connected to a port is not compliant with HDCP 2.2 (i.e. only compliant with HDCP 1.4), then no picture would be displayed. To display a picture on a non-HDCP 2.2 compliant monitor, place a checkmark here to disable the feature for the source supplying video to that output port.

DDC Mix

From the Administration menu, the DDC Mix page can be displayed. DDC Mix provides a means to decide which outputs (displays) will be used to provide EDID information to the selected input. The VEEMUX will compare EDID information from all selected outputs and provide EDID information that is common to those displays to the video source. If the “Mixed” option is desired for an input on the “DDC Options” page (page 32), settings of the DDC Mix for that input (below) should be selected and saved first.

If the DDC Mix configuration for an input is not configured and the “Mixed” option for the input is selected on the DDC Options page, a minimal default collection of EDID information will be provided to the video source.

DDC Mix

DDC Mix

Select Input: Port01 (1) ▼

Select the Input port that will receive EDID information common to the outputs (displays) selected below.

Output	Select Output's to Mix
Output01 (1)	<input type="checkbox"/> Select output 1 to mix for ddc data.
Output02 (2)	<input type="checkbox"/> Select output 2 to mix for ddc data.
Output03 (3)	<input type="checkbox"/> Select output 3 to mix for ddc data.
4k mon (4)	<input type="checkbox"/> Select output 4 to mix for ddc data.
Output05 (5)	<input type="checkbox"/> Select output 5 to mix for ddc data.
Output06 (6)	<input type="checkbox"/> Select output 6 to mix for ddc data.
Output07 (7)	<input type="checkbox"/> Select output 7 to mix for ddc data.
Output08 (8)	<input type="checkbox"/> Select output 8 to mix for ddc data.
Output09 (9)	<input type="checkbox"/> Select output 9 to mix for ddc data.
Output10 (10)	<input type="checkbox"/> Select output 10 to mix for ddc data.
4k TV (11)	<input type="checkbox"/> Select output 11 to mix for ddc data.
Output12 (12)	<input type="checkbox"/> Select output 12 to mix for ddc data.
Output13 (13)	<input type="checkbox"/> Select output 13 to mix for ddc data.
dell 1200 mon (14)	<input type="checkbox"/> Select output 14 to mix for ddc data.
Output15 (15)	<input type="checkbox"/> Select output 15 to mix for ddc data.
Output16 (16)	<input type="checkbox"/> Select output 16 to mix for ddc data.
Disable Extended EDID	<input type="checkbox"/> Use this for old DVI monitors which may not support extended EDID

Save
Save For All Inputs

To save time and use the EDID information from the same outputs for all inputs (video sources), make the output selections above and then click on “Save For All Inputs”.

Figure 18- DDC Mix page

Update Firmware

From the Administration menu, the Update Firmware page can be displayed. The Update Firmware page shows the current version of the firmware and enables the Administrator to update the firmware to the latest version available.

Update Firmware




Figure 19- Update Firmware page

WARNING: Failure to carefully follow these directions can permanently damage the VEEMUX. Please read these directions in full before continuing. Do not, under any circumstances, reset or power-down the VEEMUX while the firmware is being updated. Do not attempt to update the firmware if a power-failure is likely.

Note: The Firmware can only be updated from the non-secure (http) website. If you attempt to access this page from the secure (https) website, you will be automatically redirected to the non-secure site.

To update the firmware:

1. Contact NTI for the latest firmware file name `veemux-hd4k-vx-x.bin` (where x.x is the version number) and copy it to your computer.
2. On the Update Firmware page, in the “Update File” block, browse to the firmware file.
3. Press **Upgrade**.

Note: If an update is attempted using the wrong firmware for the section an error message will be received. No update will occur.

4. The VEEMUX will upload the firmware and then restart itself (this may take up to 4 minutes), logging out all connections. After the restart, approximately 4 more minutes, the VEEMUX will be ready to resume operation.

If a message appears stating that the Upload has failed, or that a non-fatal error has occurred:

1. Ensure that the file being uploaded is the NTI firmware file.
2. Repeat the process from step 2 above.

Note: The following message does not indicate that damage to the product has occurred.

If a message appears stating that there has been a fatal error:

1. **DO NOT RESET OR POWER-DOWN THE VEEMUX.**
2. Repeat the update process from the first step 2 above.
3. If you get another Fatal Error message, call NTI tech-support at 1-800-742-8324 or 330-562-7070.

FYI: The VEEMUX should continue to run normally unless it is reset. However, damage may have occurred to the web server firmware that will prevent the product from starting up correctly.

Standby Mode

From the menu, the user can quickly place the VEEMUX in Standby Mode. When in Standby, the VEEMUX will still be powered-ON but all functions will stop. The VEEMUX will be in a power-saving ready-to-use state.




Figure 20- VEEMUX in Standby Mode

By simply selecting “Standby” from the side menu, the VEEMUX is placed in Standby Mode. When in Standby Mode, the VEEMUX will not provide video to any displays and cannot be manipulated further until standby is disabled.

Standby Mode can be disabled either

- by pressing “Disable Standby” through the web interface (above),
- by pressing any button on the front panel keypad
- by using the IR Remote control (optional)

Logout

To quickly logout of the web interface, select “Logout” from the menu. You will immediately be logged out and presented with a login screen.




Figure 21- Logout of the VEEMUX web interface

Support

The Support link on the menu drops down to two choices, **Manual** and **Downloads**.

The **Manual** link will open the pdf manual for the VEEMUX.

The **Downloads** link

(<http://www.networktechinc.com/download/d-4k-hdmi-matrix-switch.html>)

will open the firmware downloads page for the SM-16X16-HD4K Video Matrix Switch at NTI. From there you can see what versions of firmware are available and determine if the version in your VEEMUX is current or in need of an upgrade (page 35).




Figure 22- Support Tab

Reboot

To quickly reboot the VEEMUX, select “Reboot” from the side menu. This will force the VEEMUX to power cycle its processor. A reboot will take approximately 45 seconds to occur. Refresh your browser and log back in to the VEEMUX as desired.




Figure 23- System Reboot

DEVICE DISCOVERY TOOL

In order to easily locate the VEEMUX on a network, or to change network settings, the NTI Device Discovery Tool may be used. The Discovery Tool can be found at <http://www.networktechinc.com/download/d-4k-hdmi-matrix-switch.html>.

Unzip and save to a location on your PC. To open it just double-click on the file `NTIDiscover.jar`. This will open your browser and display the Device Discovery Tool page.

Note: The Device Discovery Tool requires the Java Runtime Environment (version 6 or later) to operate. Here is a [link to the web page from which it can be downloaded](#).

Note: The computer using the Discovery Tool and the VEEMUX must be connected to the same physical network in order for the Device Discovery Tool to work.

Network Technologies Inc Device Discovery Tool

- **START**
 - When you load this page, the NTI Device Discovery Applet should load. Accept the Certificate to allow this applet access to your network. Press the button entitled **Detect NTI Devices** to start the discovery process. After a short time, the tool will display all NTI devices on your network, along with their network settings.

Note: Do not close this page while the NTI Discovery Tool is running. Close the NTI Device Discovery Application first, **then** this webpage.
- **How To Use the Discovery Tool**
 - **To Change A Device's Settings**, within the row of the device whose setting you wish to change, type in a new setting and press the **Enter** key or the **Submit** button on that row. You can also press the **Submit All** button to submit all changes at once.
 - **To Refresh the list of devices**, press the **Refresh** button.
 - **To Blink the LEDs of the unit**, press the **Blink LED** button (This feature not supported on all products). The **Blink LED** button will change to a **Blinking...** button. The LEDs of the unit will blink until the **Blinking...** button is pressed, or the NTI Device Discovery Application is closed. The LEDs will automatically cease blinking after 2 hours.
 - **To Stop the LEDs of the unit blinking**, press the **Blinking...** button. The **Blinking...** button will change to a **Blink LED** button.




Figure 24- Device Discovery Tool page

Use the Device Discovery Tool to display all NTI VEEMUXs on your network, along with their network settings. Follow the instructions on the Device Discovery Tool page to use the tool and to change the device settings if so desired.



The "Blink LED" button is not supported on this product.

INFRARED REMOTE CONTROL

The IRT-UNV Infrared Remote Control allows the user to remotely and intuitively control up to 15 NTI SM-16X16-HD4K video matrix switches, providing the ability to route connections, save and recall switch configurations, and put the switch into Standby.

Features:

- Routing of video signals
- Ability to switch one input to all outputs
- Scroll through inputs for a single output by using the Input +/- keys (similar to changing channels)
- Automatically scan through all channels for a single output
- Save or Recall up to 10 matrix switch preset configurations
- Control up to 15 NTI switches (systems) with a single remote
- Put the switch in Standby

Materials

Materials supplied with the IRT-UNV:

- NTI IRT-UNV Infrared Remote Control
- 2- AAA Batteries (installed)

Buttons

The IRT-UNV Infrared Remote Control user interface consists of a keypad with 29 buttons. The buttons have the following functions:

- **Numerical Values (0-9)**
 - Selects port numbers (for IN, OUT)
 - Selects memory locations (for saved configurations)
- *** (Asterisk)**
 - Pressed to select all outputs
- **OUT**
 - Pressed to indicate an output port selection
- **IN**
 - Pressed to indicate an input port selection
- **IN +/-**
 - Cycles through input ports (up or down), connecting to each one (similar to changing channels)

Note: This affects only the selected output port

- **SAVE**
 - Pressed to save the current switch configuration (port connections and volume settings)
 - Up to 10 configurations can be saved (0-9)
- **RECALL**
 - Pressed to recall a switch configuration (port connections and volume settings)
 - Up to 10 configuration can be recalled (0-9)
- **SYS**
 - Pressed to select the desired NTI system to be controlled
 - Only used when controlling multiple systems
 - Must be followed by a system number: 1-15
- **ENTER**
 - Pressed to immediately accept the command (normal delay is approx. 5 seconds).
- **ESC**
 - Pressed to cancel the current command

Note: If the command has not yet been accepted, all button presses in the command sequence will be cleared

- **Standby**  Pressed to put the unit into or out of standby mode
- **VIDEO**  **THIS BUTTON IS NOT USED FOR THIS PRODUCT**
- **BLANK Video** 
 - Turns OFF Video for the selected output
 - Can be used with *(Asterisk button) to turn OFF video for all outputs
 - Video will be turned ON by pressing the Blank Video button again, or by switching ports

Note: Blank and Un-Blank commands are applied only to the selected output



- **AUDIO**  **THIS BUTTON IS NOT USED FOR THIS PRODUCT**
- **VOL +/-** **THIS BUTTON IS NOT USED FOR THIS PRODUCT**
- **MUTE Audio**  **THIS BUTTON IS NOT USED FOR THIS PRODUCT**
- **SCAN**
 - Pressed to toggle the scan enable/disable feature for the selected port
 - Must be preceded by an output port number (1 or 2 digits), or the * (Asterisk) button to toggle all ports

Note: If the dwell time for a port is set for 0 seconds, it will not be scanned (page 29)
- **PREV -THIS BUTTON IS NOT USED FOR THIS PRODUCT**

Operation

Operation of the IRT-UNV is intuitive. The number of button presses required to complete any operation is kept to a minimum. This is accomplished using intelligent software within the NTI Matrix Switch. Additionally, the Matrix Switch allows for multiple ways for the user to complete the same operation – ensuring that the Remote will work as expected, regardless of who uses it.

Changing Ports

The first, and most important operational use of the IR Remote is changing ports of the switch. This requires the selection of both input and output ports. There are several methods of control.

Channel Surfing

The “IN +/-” and “SCAN” buttons can be used to surf through input port connections. However, since there are multiple outputs/users, the question becomes “which output connection is being changed?” As a result, it is required that an output be selected prior to using the “IN +/-” buttons.

The output port can be selected in two ways:

- by pressing the “OUT” button before selecting the output port number
- by pressing the “OUT” button after selecting the output port number

In both cases, the user must enter the output port number using the Numeric Keys (0-9). However, when the “OUT” button is pressed prior to selecting the port number, there will be a two (2) second delay after the last digit of the output port is entered that must expire before the output port is accepted. To avoid this delay, press the “ENTER” button to immediately accept the port number.

Once the output port has been accepted, there will be a five (5) second timeout, during which the user must press another button (“IN +,” “IN -,” or “SCAN”). Each subsequent press of “IN+” or “IN-” will renew the timeout, waiting for you to press it again (to advance or go back by one more Input channel). If no new command is sent to the switch before the timeout expires, the switch will forget the selected output, and pressing the “IN +/-” buttons will have no effect.

All output channels can surf inputs at once by pressing the “ * ” button prior to pressing the “IN +/-” buttons.

Examples:

Change connection of Output 1 from Input 1 to Input 3:

```
<OUT> + <1> + wait 2 seconds + <IN+> + <IN+>
<OUT> + <1> + <ENTER> + <IN+> + <IN+> (must press <IN+> within 5 seconds of pressing <ENTER>)
<1> + <OUT> + <IN+> + <IN+> (must press <IN+> within 5 seconds of pressing <OUT>)
```

Jump To Input

With the output port selected, a user knowing the desired input port number can enter it using the Numeric keys (0-9). Just as with using the “OUT” button, pressing the “IN” button after the number will force the command immediately. If the “IN” button is pressed prior to the port number, the “ENTER” button must be pressed to avoid a two (2) second delay before the input port is accepted.

Examples:

Quick method to change Output 1 from Input x (any) to Input 8:

<1> + <OUT> + <8> + <IN>

Quick method to change Output 12 from Input x (any) to Input 20:

<1> + <2> + <OUT> + <2> + <0> + <IN>

Jump To Output

Users can also change ports by specifying the input port number first. Similar to selecting the output port first, the “IN” button can be pressed either before or after entering the port number. Once the input port has been selected, the output port can be selected, following the same format as “Jump to Input...”

Expiration of a five (5) second timeout will force the switch to forget the entered input port number.

Example:

Quick method to change Input 1 from Output x (any) to Output 8:

<1> + <IN> + <8> + <OUT> (must enter the <x> + <OUT> command within 5 seconds of pressing <IN>)

Connect All

It may be desirable to broadcast the video signals from one input to all of the outputs. In this situation, the user can quickly make all of these connections by using the “*” (asterisk) button which selects all outputs. With the input port selected, pressing the “*” button will immediately force the command to connect all output ports to the selected input.

Example :

Connect all users to Input 2:

<2> + <IN> + <*>

The “*” button can also be pressed prior to selecting the input port. In this case, the command will take effect once the input port has been selected.

<*> + <2> + <IN>

If no command is received before the five (5) second timeout expires, the switch will forget the “*” key-press.

Save and Recall

This video matrix switch provides the ability to save and recall up to 100 switch configurations. The switch configurations define the current port connections, volume control settings, and video blank status. The IRT-UNV IR Remote can be used to access these configurations by using the "SAVE" and "RECALL" buttons.

To save a configuration, press the "SAVE" button followed by Numeric key(s) 0-99 corresponding to the memory slot the configuration is to be saved in. After the numeric key(s) press the "Enter" button. If the "Enter" button is not pressed, after two seconds the function will timeout and the number entered will be saved as that configuration.

Configurations can be recalled in much the same manner. To recall, press the "RECALL" button followed by the numeric key (s) corresponding to the memory slot from which the configuration is to be recalled. After the numeric key(s) press the "Enter" button. If the "Enter" button is not pressed, after two seconds the function will timeout and the number entered will be recalled to the current configuration.

Multiple Switch Control

All compatible NTI matrix switches will work with the same IRT-UNV IR Remote control. As a result, a user with multiple NTI matrix switches may find that, if the switches are installed too close together, both switches may respond to an IR command intended only for one switch. Or, the user may want to control multiple switches with a single remote, instead of having one remote per switch. To accommodate this situation, the IRT-UNV IR Remote provides the "SYS" button, which can be used to select the NTI switch to be controlled.

All switches will have the capability to allow the user to set the switch address (0-15). Each switch to be separately controlled must be set to a different address prior to using the Remote Control. With the addresses set, press the "SYS" button on the IRT-UNV, followed by a two digit number corresponding to the address of the matrix switch to be controlled.

Upon accepting the "SYS" command, the switch with the corresponding address will illuminate the "IR" LED and respond to all IR Remote commands and will blink the "IR" LED on the front of the switch for visual indication. All other switches will ignore any further commands, until the "SYS" button is pressed again. To select a new NTI switch to control, press the "SYS" button again and repeat the process.

Canceling a Command

Considering the number of key presses required for some of the commands, it's possible that the user may inadvertently press an incorrect button. Should this happen, the user can press the "ESC" button to cancel a command. Provided the command has not been accepted by the system, pressing the "ESC" button will cause the switch to "forget" or "erase" all button commands from the current command sequence. Once the command sequence has been cancelled, the user can begin entering the command again.

Technical Specifications For IRT-UNV

Number of Controllable Systems	Max: 15
Pushbutton Control	29 keys
Power supply	2x AAA Battery
Chassis material	Plastic
Approvals	RoHS

Troubleshooting the IRT-UNV

PROBLEM	SOLUTION
IRT-UNV is not selecting outputs or inputs	<ul style="list-style-type: none"> • Check battery • The IRT-UNV may be configured to control the wrong switch- see "Multiple Switch Control" above.

Troubleshooting the VEEMUX

PROBLEM	SOLUTION
VEEMUX will not boot up	<ol style="list-style-type: none"> 1. Make an RS232 connection to the VEEMUX as described on page 6. 2. Set the terminal program to communicate at 115200bps. 3. Power ON the VEEMUX and, as it is powering up, press and hold the <Tab> key until a boot prompt appears (VEEMUX>) in the terminal program. 4. At the boot prompt type the following: <div style="text-align: center;"><code>VEEMUX>nand erase config</code> and press the <Enter> key.</div> 5. Power-cycle the VEEMUX. It should bootup and resume normal operation with all factory default settings restored. Any customized settings previously entered will be erased and will need to be re-entered.

GENERAL TECHNICAL SPECIFICATIONS

Video	
Video Bandwidth	18 GB/s
Max. Resolution supported	3840x2160 (UHD), and 4096x2160 (4K) @ 60Hz / RGB/YCBCR 4:4:4.
HDMI Compatibility	HDMI 1.4 and 2.0
HDCP Support	v1.4 and v2.2
Color Depth	Up to 12 bits per color
Pixel Encoding	4:4:4,4:2:2, 4:2:0
Control	
Serial	RS232, RJ45 female connector
Ethernet	RJ45 female connector
Infrared	IR Receiver (works with remote control transmitter)
Power	IEC connector for 100-240VAC power connection
General	
Dimensions (WxDxH)	19x13.75x1.75

INDEX

Backup.....	25	password	22
baud rate.....	11	reboot.....	37
control options	8	Restore	25
DDC	10, 32, 34	RS232 pinout	11
Device Discovery Tool	38	Scanning Sequences	29
firmware	35	SerTest	14
front panel LCD.....	8	standby mode	36
IP address.....	22, 26	Telnet Interface	16
IRT-UNV	39	Telnet-Port 2005	18
Java Runtime Environment	38	user management.....	31
LAN.....	22	username and password.....	22
materials supplied	2	Video Switch	24
Matrix Switcher's Control Program	13	web browsers.....	1

WARRANTY INFORMATION

The warranty period on this product (parts and labor) is two (2) years from the date of purchase. Please contact Network Technologies Inc at **(800) 742-8324** (800-RGB-TECH) or **(330) 562-7070** or visit our website at <http://www.networktechinc.com> for information regarding repairs and/or returns. A return authorization number is required for all repairs/returns.