

 [View product details](#)



iCON™ USB-C HDMI® 4K

PushGo Alta transforms any small room into a fully equipped, connected meeting space—no setup, programming, or IT support required. Each system arrives pre-configured and ready to perform. Simply connect your devices, power on, and your room is ready to go.

Once connected, Alta delivers crisp 4K video to your display and clear, evenly balanced audio through your speakers. From the sleek 10" touchscreen, you can switch inputs, manage connected sources, or adjust room settings such as lights or shades—all from one intuitive interface.

With PushGo Meet now built in, Alta also brings your daily meeting schedule directly to the touchscreen. Once connected to your Outlook or Google Calendar account, your meetings appear directly on the PushGo touchscreen so you can start sessions with a single tap, stay aligned with real-time updates, and move through your day without interruption.

Alta also supports flexible multiview layouts, allowing multiple sources to be displayed simultaneously for collaborative discussions and side-by-side comparisons.

Bringing the comfort and intelligence of smart-home automation into your workspace, PushGo Alta turns everyday meetings into seamless, polished experiences.

Customization Available: Enjoy complimentary logo placement on your touchscreen. After your order, we'll contact you to finalize details. Additional interface or hardware customizations are available for an added cost.

Key Features

- Fully pre-configured and ready to perform
- Plug-and-play design for same-day setup
- Premium 10" touchscreen control for inputs, sources, and room settings
- Stunning 4K video and high-quality audio output
- Supports up to four HDMI devices
- Flexible multiview layouts for viewing multiple sources at once
- Built-in calendar-connected meeting control with PushGo Meet
- Connects with Outlook and Google Calendar after account setup
- Daily meeting schedule displayed directly on the PushGo touchscreen
- One-touch meeting start from the touchscreen
- Real-time schedule updates for newly added, moved, or canceled meetings
- View current and upcoming meetings at a glance
- Compatible with Zoom, Microsoft Teams, Webex, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Ideal for huddle rooms and small meeting spaces

Specifications

iCON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

ICON-E1

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

MVS-41

Standards & Compliance

Signal Standards	HDMI 2.0b
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	4 x HDMI IN (Type A, 19-pin female)
-------------	-------------------------------------

HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
Control	RS-232 3-pin - 3.81mm phoenix connector (bi-directional), IR 3.5mm jack
SPDIF (RCA)	Yes
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	18 Gbps
Color Space	RGB, YPbPr, YCbCr
Color Depth	8-bit
MTBF	60,000 – 120,000 hours
HDMI Audio Format	PCM 2.0, Dolby Digital, DTS

Communications & Control

Control Ports	RS-232, IR
IR Remote	Yes
Control Connector Type	3.5mm TRS, Mini phoenix (3.81mm)

Power

Power Input	AC 100 - 240V 50/60Hz
Power Supply	DC 12V/2.5A
Power Consumption	10W (max)

Enclosure

Rack Mounting Option	No
Product Dimensions (W x D x H)	8.66 in x 3.94 in x 1.18 in (219.96mm x 100.08mm x 29.97mm)
Weight	1.37 lbs (620g)

Warranty

Parts	5 year
Labor	5 year

TL-SG108PE 8 port switch

Connector Types & Features

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps

Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mb
Jumbo Frame	15 KB

Power

Power Consumption	74.27W (max)
-------------------	--------------

Enclosure

Product Dimensions (W × D × H)	6.2 in × 4.0 in × 1.0 in (158mm × 101mm × 25mm)
--------------------------------	---

Warranty

Parts	1 year
Labor	1 year