

[View product details](#)



**USB-C HDMI 4K**

PushGo Aspen transforms conference rooms and training spaces into fully equipped, connected meeting environments with a complete all-in-one meeting system. Designed as a “meeting space system in a box,” PushGo Aspen combines control, video routing, audio, switching, and cabling into a single solution for versatile collaboration.

Delivered pre-configured and pre-programmed, PushGo Aspen arrives ready for same-day installation, so rooms can be operational immediately with reliable performance. Its 10-inch touchscreen provides intuitive control for switching sources, managing displays, and adjusting lighting or shades. Ultra-clear video and rich audio deliver polished, professional presentations every time.

With PushGo Meet now built in, Aspen also brings your daily meeting schedule directly to the touchscreen. Once connected to your Outlook or Google Calendar account, your meetings appear directly on the PushGo touchscreen so you can start sessions with a single tap, stay aligned with real-time updates, and move through your day without interruption.

Aspen also supports multiple connected devices and flexible multiview layouts, allowing side-by-side comparisons, multi-presenter sessions, and interactive group discussions.

By combining all-in-one simplicity with advanced collaboration capabilities, PushGo Aspen delivers seamless, high-performance meeting experiences for larger and more versatile rooms.

**Customization Available:** Each PushGo package can be tailored to your specific needs, including hardware options. Contact us for more details on how to customize your system.

### Key Features

- Fully pre-configured and ready to perform
- Plug-and-play design for same-day setup
- Premium 10" touchscreen control for sources, displays, and room settings
- Ultra-clear video and rich audio output
- Supports up to six HDMI or USB-C devices
- Flexible multiview layouts for screen sharing of multiple sources
- Built-in calendar-connected meeting control with PushGo Meet
- Connects with Outlook and Google Calendar after account setup
- Daily meeting schedule displayed directly on the PushGo touchscreen
- One-touch meeting start from the touchscreen
- Real-time schedule updates for newly added, moved, or canceled meetings
- View current and upcoming meetings at a glance
- Compatible with Zoom, Microsoft Teams, Webex, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Ideal for conference rooms, training spaces, and offices

### Specifications

#### ICON-T10

#### Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

#### Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

#### Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

#### Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

#### Enclosure

Mounting Option	Table
Product Dimensions (W x D x H)	9.66 in x 6.46 in x 1.06 in (245.36mm x 164.08mm x 26.92mm)
Weight	1.96 lbs (889g)

### Warranty

Parts	5 year
Labor	5 year

## ICON-E1

### Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

### Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

### Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

### Enclosure

Product Dimensions (W x D x H)	3.69 in x 2.63 in x 0.38 in (93.7mm x 66.8mm x 9.7mm)
Weight	0.65 lbs (295g)

### Warranty

Parts	5 year
Labor	5 year

## PS-610

### Standards & Compliance

Signal Standards	HDMI 2.0, USB 3.0, DP-Alt Mode, HDBaseT 3.0
HDCP	HDCP 2.2

### Connector Types

HDMI Inputs	3 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)

HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	2 x USB IN (USB-C)
USB Output	1 x USB OUT (USB-B)
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

### Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	12 Gbps
PIP	Split-screen, Windowed
HDMI Audio Format	LPCM

### Communications & Control

Control Ports	LAN, RS-232, IR
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

### Power

Power Input	DC 24V/8A (US/EU standard, CE/FCC/UL certified)
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	150W (max)

### Enclosure

Product Dimensions (W × D × H)	TX: 8.66 in × 5.91 in × 1.73 in (219.96mm × 150.11mm × 43.94mm) RX: 5.51 in × 4.13 in × 0.85 in (140.01mm × 104.90mm × 21.59mm)
Weight	TX: 2.67 lbs (1211g) RX: 0.93 lbs (422g)

### Warranty

Parts	5 year
Labor	5 year

### TL-SG108PE 8 port switch

#### Connector Types & Features

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps

Packet Buffer Memory	1.5 Mb
----------------------	--------

Jumbo Frame	15 KB
-------------	-------

### Power

Power Consumption	74.27W (max)
-------------------	--------------

### Enclosure

Product Dimensions (W × D × H)	6.2 in × 4.0 in × 1.0 in (158mm × 101mm × 25mm)
--------------------------------	---

### Warranty

Parts	1 year
-------	--------

Labor	1 year
-------	--------