



[View product details](#)

iCON™ USB-C HDMI 4K Dante

PushGo Stowe transforms executive boardrooms and large collaboration spaces into fully equipped, connected meeting environments with a complete all-in-one meeting system. Engineered as a “meeting space system in a box,” PushGo Stowe delivers professional-grade video, audio, control, switching, and scheduling in a single solution for high-performance meetings.

Delivered pre-configured and pre-programmed, PushGo Stowe arrives ready for same-day installation, providing reliable operation from day one. Once connected, Stowe’s professional PTZ camera captures every participant in sharp, true-to-life detail, while integrated Dante audio and DSP fill the room with clean, natural sound.

From the sleek 10” touchscreen, you can control switching, camera settings, displays, audio, and room settings such as lights or shades—all from one intuitive interface.

With PushGo Meet now built in, Stowe brings your daily meeting schedule directly to the touchscreen. Once connected to your Outlook or Google Calendar account, your meetings appear directly on the PushGo touchscreen so you can start sessions with a single tap, stay aligned with real-time updates, and move through your day without interruption.

A secondary wall-mounted scheduling panel also provides clear room visibility and easy calendar-connected room management.

By combining professional-grade video, integrated Dante audio, touchscreen control, and built-in scheduling awareness, PushGo Stowe delivers polished, reliable, and high-performance meeting experiences for executives and large teams.

Customization Available: Each PushGo package can be tailored to your specific needs, including hardware options. Contact us for more details on how to customize your system.

Key Features

- Fully pre-configured and ready to perform
- Plug-and-play design for same-day setup
- Premium 10" touchscreen control for switching, camera, displays, audio, and room settings
- Professional PTZ camera with optical zoom
- Integrated Dante audio with DSP
- Flexible multiview layouts for simultaneous screen sharing
- Supports up to six HDMI or USB-C devices
- Built-in calendar-connected meeting control with PushGo Meet
- Connects with Outlook and Google Calendar after account setup
- Daily meeting schedule displayed directly on the PushGo touchscreen
- One-touch meeting start from the touchscreen
- Real-time schedule updates for newly added, moved, or canceled meetings
- View current and upcoming meetings at a glance
- Secondary room scheduling touchscreen with calendar integration
- Don't Blink™ Switching for seamless, instant source transitions
- Compatible with Zoom, Microsoft Teams, Webex, Google Meet, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Ideal for executive offices, boardrooms, and training spaces

Specifications

iCON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

iCON-E1

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

PS-610

Standards & Compliance

Signal Standards	HDMI 2.0, USB 3.0, DP-Alt Mode, HDBaseT 3.0
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	3 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	2 x USB IN (USB-C)
USB Output	1 x USB OUT (USB-B)
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	12 Gbps
PIP	Split-screen, Windowed
HDMI Audio Format	LPCM

Communications & Control

Control Ports	LAN, RS-232, IR
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

Power

Power Input	DC 24V/8A (US/EU standard, CE/FCC/UL certified)
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	150W (max)

Enclosure

Product Dimensions (W x D x H)	TX: 8.66 in x 5.91 in x 1.73 in (219.96mm x 150.11mm x 43.94mm) RX: 5.51 in x 4.13 in x 0.85 in (140.01mm x 104.90mm x 21.59mm)
Weight	TX: 2.67 lbs (1211g) RX: 0.93 lbs (422g)

Warranty

Parts	5 year
Labor	5 year

NICGIGA 16 port PoE Switch

Standards & Compliance

Standard	IEEE 802.3af/at compliant
----------	---------------------------

Connector Types & Features

Switch Type	Unmanaged, plug-and-play
Ports	16 x PoE+ ports, 2 x Gigabit uplink ports, 1 x SFP port
Switching Capacity	12 Gbps

Power

Power Consumption	250W (max)
-------------------	------------

Warranty

Parts	1 year
Labor	1 year

VIP-CAM-30-20X

Standards & Compliance

Signal Standards	HDMI 1.3
HDCP	HDCP 1.4

Connector Types

HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
USB Output	USB-B

Performance

PTZ	Yes
Focal Length	f = 4.7 mm – 94.0 mm
Protocols	RTSP, RTMP, ONVIF
Field of View	2.9° to 59.5°
Iris	F1.6 – F3.5
Minimum Illumination	0.5 Lux (Color), 0.1 Lux (B/W)

Lens Zoom	20× Optical, 8× Digital
PoE Support	IEEE 802.3af / IEEE 802.3at (PoE / PoE+)

Communications & Control

Control Ports	LAN, RS-232, IR
Control Connector Type	RJ45, 8-pin mini-DIN connector

Enclosure

Rack Mounting Option	Wall, Ceiling
Product Dimensions (W × D × H)	8.9 in × 6.2 in × 8.1 in (226mm × 157mm × 206mm)
Weight	3.75 lbs (1701g)

Warranty

Parts	5 year
Labor	5 year

DIO-AMP150

Standards & Compliance

Signal Standards	Dante, AES67
Amplifier Type	Class D

Connector Types

Line In	1 x Line In 5-pin 3.81mm phoenix connector
Line Out	1 x Line Out 5-pin 3.81 phoenix connector 1 x 4/8Ω AMP OUT MSTB 2,5/4-GF-5.08 1 x 70V/100V AMP OUT MSTB 2,5/4-GF-5.08

Performance

Amplifier Output (W)	150W single-channel, 75W two-channel
Dante Port	Single
DSP	Yes

Communications & Control

Control Ports	LAN, RS-232
Network	Dante® AES67
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Consumption	150W (max)
-------------------	------------

Enclosure

Rack Mounting Option	Yes
----------------------	-----

Warranty

Parts	5 year
Labor	5 year

RoomView-110W

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)

Power

Power Input	POE, 24V DC/1A 1 x 2 phoenix connector
Power Consumption	6W (max)

Enclosure

Rack Mounting Option	Wall
----------------------	------

Warranty

Parts	5 year
Labor	5 year