

[View product details](#)



PushGo Vail transforms hybrid meeting rooms and executive spaces into fully equipped, connected meeting environments with a complete all-in-one meeting system. Built as a “meeting space system in a box,” PushGo Vail combines professional video, audio, control, switching, and cabling into one streamlined solution for seamless remote collaboration.

Delivered pre-configured and pre-programmed, PushGo Vail arrives ready for same-day installation, allowing remote meeting spaces to be operational immediately. Its 4K PTZ camera, beamforming microphone array, and integrated soundbar automatically track active speakers, while Smart Gallery mode creates individual video tiles for each participant, providing professional-grade clarity and presence.

The 10-inch touchscreen provides intuitive control over camera angles, audio levels, and lighting. Compatible with Zoom, Microsoft Teams, and Google Meet, PushGo Vail ensures every virtual meeting feels natural and unified.

With PushGo Meet now built in, Vail also brings your daily meeting schedule directly to the touchscreen. Once connected to your Outlook or Google Calendar account, your meetings appear directly on the PushGo touchscreen so you can start sessions with a single tap, stay aligned with real-time updates, and move through your day without interruption.

By combining intelligent video, high-quality audio, touchscreen control, and built-in scheduling awareness, PushGo Vail delivers polished, efficient, and professional remote meeting experiences.

Customization Available: Each PushGo package can be tailored to your specific needs, including hardware options. Contact us for more details on how to customize your system.

Key Features

- Fully pre-configured and ready to perform
- Plug-and-play design for same-day setup
- Premium 10" touchscreen control for camera, audio, sources, and room settings
- All-in-one 4K PTZ camera, microphone, and soundbar
- AI auto-tracking and Smart Gallery view
- Flexible multiview layouts for simultaneous screen sharing
- Supports up to six HDMI or USB-C devices
- Don't Blink™ Switching for seamless, instant source transitions
- Built-in calendar-connected meeting control with PushGo Meet
- Connects with Outlook and Google Calendar after account setup
- Daily meeting schedule displayed directly on the PushGo touchscreen
- One-touch meeting start from the touchscreen
- Real-time schedule updates for newly added, moved, or canceled meetings
- View current and upcoming meetings at a glance
- Compatible with Zoom, Microsoft Teams, Google Meet, GoToMeeting, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Ideal for hybrid meeting rooms, executive offices, and small conference spaces

Specifications

iCON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

iCON-E1

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

PS-610

Standards & Compliance

Signal Standards	HDMI 2.0, USB 3.0, DP-Alt Mode, HDBaseT 3.0
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	3 x HDMI IN (Type A, 19-pin female)
-------------	-------------------------------------

HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	2 x USB IN (USB-C)
USB Output	1 x USB OUT (USB-B)
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	12 Gbps
PIP	Split-screen, Windowed
HDMI Audio Format	LPCM

Communications & Control

Control Ports	LAN, RS-232, IR
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

Power

Power Input	DC 24V/8A (US/EU standard, CE/FCC/UL certified)
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	150W (max)

Enclosure

Product Dimensions (W x D x H)	TX: 8.66 in x 5.91 in x 1.73 in (219.96mm x 150.11mm x 43.94mm) RX: 5.51 in x 4.13 in x 0.85 in (140.01mm x 104.90mm x 21.59mm)
Weight	TX: 2.67 lbs (1211g) RX: 0.93 lbs (422g)

Warranty

Parts	5 year
Labor	5 year

TL-SG108PE 8 port switch

Connector Types & Features

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps

Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mb
Jumbo Frame	15 KB

Power

Power Consumption	74.27W (max)
-------------------	--------------

Enclosure

Product Dimensions (W × D × H)	6.2 in × 4.0 in × 1.0 in (158mm × 101mm × 25mm)
--------------------------------	---

Warranty

Parts	1 year
Labor	1 year

HUDDLE-CAM-500

Standards & Compliance

Signal Standards	HDMI 2.0, USB-A, USB-C (DP-Alt Mode)
HDCP	HDCP 1.4, HDCP 2.2
Regulatory Certifications	CE, FCC, RoHS

Connector Types

HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
USB Output	USB-C (DP-Alt Mode), USB-A

Communications & Control

Control Ports	LAN, RS-232
Control Connector Type	RJ45, 8-pin mini-DIN connector

Enclosure

Rack Mounting Option	Wall, Ceiling
Product Dimensions (W × D × H)	8.9 in × 6.2 in × 8.1 in (226.06mm × 157.48mm × 205.74mm)
Weight	3.75 lbs (1701g)

Warranty

Parts	5 year
Labor	5 year