

UX-4400 4x4 4K HDMI Matrix Switcher with HDCP 2.2



The **UX-4400** provides switching of up to four HDMI 2.0 inputs and outputs with advanced EDID management and HDCP 2.2 compliance. The UX-4400 offers full Ultra HD/4K support and multiple control options including RS-232C and LAN ports. PureLink's legendary EDID management system ensures compatibility across multiple display types and delivers consistent connectivity with quick, clean switching from source to display for a seamless presentation experience.

Key Features

- 4x4 HDMI 2.0 matrix switching
- Resolutions up to 4K@50/60 Hz (4:4:4 pixel format)
- HDMI 2.0, HDCP 2.2 support
- Advanced EDID Management
- Bi-directional RS232/LAN control
- Locking HDMI ports

Technical Specifications

CONNECTOR TYPES

- (4) HDMI Input
- (4) HDMI Output
- (1) RS-232C Serial
- (1) LAN (TCP/IP)

SUPPORTED RESOLUTIONS

- Up to Ultra HD/4K
- 4096 x 2160 @50/60Hz (RGB 4:4:4 YCbCr 4:4:4, 4:2:2, 4:2:0)

DATA RATE

- 18 Gbps

SUPPORTED FORMATS

- HDMI 2.0, HDCP 2.2

OPERATING TEMPERATURE

- 32° F to 104° F (0° to 47° C)

STORAGE TEMPERATURE

- 40° F to 158° F (-40° to 70° C)

HUMIDITY

- 0 ~ 90% non-condensing

MTBF

- 95,000 hours

POWER CONSUMPTION

- 60W (DC + 12V 5.0A power supply)

DIMENSIONS (W X D X H)

- 19" x 8.0" x 1.75" in.
- (482.6 x 203.2 x 44.45 mm)

WEIGHT

- 6.7 lbs (3.04 kg)

