



User Manual

HDTVFIXHDMI99

Supports 9 HDMI inputs & 9 HDMI Outputs



Version:V2017.001



Content

1. Introduction	3
2. Features	3
3. Specification	4
4. Packing	4
5. WEB/APP control	8
6. RS 232 control command	9
7. Common Porblem shooting	9
8. After Sales	10
9. Version Information.....	11

1. Introduction

This WolfPack HDTVFIXHDMI99 is a new generation HDMI matrix switchers developed to meet with the large market needs. Users can control the switchers via mobile phone, iPad and WEB bi-directional control. Also support Centralized management by IOS/ Android APPs, compatible with HDMI1.4a, HDCP compatible, support EDID management functions. High-performance with resolution up to 4K2K30Hz switchers support audio video simultaneously switching are widely used in conference room, control center, multimedia room and other applications.

2. Features



- Compatible with 4K2K30Hz 3D@60Hz
- Deep Color support 48/36/30/24-bit
- Support LPCM 7.1CH, Dolby True HD, Dolby digital + and DTS-HD Master Audio output
- Support any signal source displayed simultaneously on multiple displays
- Support WEB control and APP management, more flexible and user friendly
- Two-key control method enabling easier and more effective controlling, support 1 port input and multiple ports output when switching images
- Indicator lights of visual buttons enabling the input and output channel operation status to be visible

- Broadcast level exchange chip increased integration enabling image switching can be realized by a single chip
- Bi-directional control enabling images can be switched simultaneously by WEB and APP in real time
- Centralized control function enabling multiple matrices can be controlled by a single control unit. No need to manually modify configuration data
- Opening Web control codes enabling secondary development
- Supports EDID learning and EDID adaptive function enabling it to meet the needs of field diversification display devices, and also improved compatibility
- Support RS-232, front-panel, WEB control
- Spiral power connectors guaranteed stable power supplying
- Using silicone buttons with blue background light

3. Specifications


Model	HDTVFIXHDMI99
Description	9x9 HDMI matrix switcher
Input	9* HDMI inputs
Output	9* HDMI outputs
Protocol	Support HDMI1.4a, HDCP compatible, EDID Learning
Resolution	4K2K@30Hz and under
Transmission Distance	HDMI: 10m
Control	Dual RS232(In/ out), LAN(WEB GUI), front buttons, APP
Dimension	480×252×44(mm)
Weight	4KG
Consumption	23W
Power Supply	AC 110V-240V 50/60HZ
Working Humidity	10%-90%
Working Temperature	-10℃ - 50℃
Storage Temperature	-25℃ - 55℃

4. Packing

HDTVFIXHDMI99	1	Unit
Power Cord	1	Pcs

5. WEB control


It can support WEB interface control, the default IP is 192.168.0.80, enter 192.168.0.80 to a browser, showing below interface:




Note: Before using all the function will need to Login first.

After clicking Login showing below interface, both of the user name and password are:

admin




After logging in successfully, on the top will show: **Home, Manager, Switch, Caption, Setup, Logout and More** icons. Click Manager will show below interface:




Note: In this icon, users can check all the matrices in the same local area network. Users also can rename and open a window of the selected matrix.

Switch icon:




Note: Users can switch here.

Caption icon:




Note: Users can change the scene, input and output names here.

Setup icon:



Note: Users can change IP address, user name and password here.

More icon:



Note: Users can upgrade system from here.


APP Control

It also supports IOS and Android App control, users only need to well connected the matrix with the router or local network. Then download the APP from the application store. The steps and interfaces show as below:

Step 1: Make sure the matrix well connected with the router or local network, and open the APP:



Step 2: Enter the IP address of the matrix:



Step 3: After log in successfully, users can switch, change the inputs and outputs name directly.



6. RS232 control command

Baud rate: 115200

data bit: 8

Stop bit: 1

Check bit: None

Type	Control command	Function description
Command	[x1]All.	Switch [x1] input to all the outputs
	All[1].	Switch all the channels to be one to one. Eg.1->1, 2->2, 3->3.....
	[x1]X[x2].	Switch [x1] input to [x2] output
	[x1]X[x2]&[x3]&[x4].	Switch [x1] input to [x2], [x3], [x4]
	Save[Y].	Save current status to [Y], [Y] can be number1-9
	Recall[Y].	Recall the saved [Y] scene
	BeepON.	Buzzer on
	BeepOFF.	Buzzer off

Note:

- [x1], [x2], [x3], [x4] are the inputs and outputs, normally depend on the matrix, if the matrix is a 10x10 matrix, then the effective range are from 1 to 10. Can't send this kinds of words ['And']
- Every command need to add the words '-'
- The letters can be capital and small letter

7. Common problem shooting

No signal on the display?

- ◆ Make sure all the power code well connected
- ◆ Check the display switcher and make sure it's in good condition

- ◆ Make sure the the DVI cable between the device and display are short than 7 meters
- ◆ Reconnect the DVI cable and restart the system
- ◆ Make sure the signal sources are on
- ◆ Check the cables between the devices and displays are connected correctly.
- ◆ Dial the switcher 7 to 1, then dial the switcher1,2 and choose the corresponding inputs.
- ◆ Make sure the resolution less than WUXGA(1920*1200)/ 60HZ
- ◆ Make sure the display can support the output resolution.

8. After-Sales

8.1 Warranty Information

The Company warrants that the process and materials of the product are not defective under normal use and service for 2 (2) years following the date of purchase from the Company or its authorized distributors.

If the product does not work within the guaranteed warranty period, the company will choose and pay for the repair of the defective product or component, the delivery of the equivalent product or component to the user for replacement of the defective item, or refund the payment which users have made.

The replaced product will become the property of the Company.

The replacement product could be new or repaired.

Whichever is longer, any replacement or repaired of the product or component is for a period of ninety (90) days or the remaining period of the initial warranty. The Company shall not be responsible for any software, firmware, information, or memory data contained in, stored in, or integrated with the product repaired by the customer's return, whether or not during the warranty period.

8.2 Warranty limitations and exceptions

Except above limited warranty, if the product is damaged by over usage, incorrectly use, ignore, accident, unusual physical pressure or voltage, unauthorized modification, alteration or services rendered by someone other than the Company or its authorized agent, the company will not have to bear additional obligations. Except using the product properly in the proper application or normal usage

9. Version Information

Description of version (Document number: HDTVFIXHDMI99)		
Date	Version number	Description
Feb 2018	V1.01.01	First version